

DR217-8 SERIES RADIAL LEADED INDUCTORS

Features

- Designed for EMI Filters & Switching Power Supplies
- Inductance Range from 4.7 μ H to 100mH
- Operating Temp. -20°C to +80°C
- Tinned Leads with Leaded Solder is Available (note 5)



ELECTRICAL SPECIFICATIONS AT 25°C

Part Number	Inductance (μ H) @1kHz	DCR (Ohm) Max.	Rated Current (A) Max. I sat	Rated Current (A) Max. I rms
DR217-8-472	4.7	0.008	10.00	6.0
DR217-8-682	6.8	0.011	8.00	5.5
DR217-8-103	10	0.017	7.00	4.5
DR217-8-153	15	0.022	5.50	4.0
DR217-8-223	22	0.026	4.50	3.7
DR217-8-333	33	0.032	3.80	3.3
DR217-8-473	47	0.035	3.20	3.0
DR217-8-683	68	0.047	2.60	2.6
DR217-8-104	100	0.09	2.20	2.0
DR217-8-154	150	0.129	1.80	1.6
DR217-8-224	220	0.162	1.50	1.5
DR217-8-334	330	0.212	1.20	1.2
DR217-8-474	470	0.38	1.00	1.0
DR217-8-684	680	0.548	0.84	0.84
DR217-8-105	1000	0.844	0.66	0.66
DR217-8-155	1500	1.18	0.55	0.55
DR217-8-225	2200	2.0	0.46	0.44
DR217-8-335	3300	2.53	0.38	0.38
DR217-8-475	4700	3.19	0.32	0.32
DR217-8-685	6800	5.69	0.26	0.25
DR217-8-106	10000	7.3	0.22	0.22
DR217-8-156	15000	10.5	0.18	0.18
DR217-8-226	22000	21.8	0.14	0.13
DR217-8-336	33000	25.7	0.12	0.12
DR217-8-476	47000	36.1	0.10	0.10
DR217-8-686	68000	57.3	0.08	0.08
DR217-8-107	100000	89.7	0.06	0.06

MECHANICAL SPECIFICATIONS



- DATATRONIC:** 28151 Highway 74, Romoland, CA 92585 Tel: 951-928-7700 Toll Free Tel: 888-889-5391 Fax: 951-928-7701
Email: ddisales@datatronics.com
499 King's Road, Hong Kong Tel: (852) 2562 3858, (852) 2564 8477 Fax: (852) 2565 7214, (852) 2563 1290
All specifications are subject to change without notice. Page 2 of 2