3 Way Direct Acting

DS1571



Features:

- Direct acting 3-way solenoid valve
- Normally closed switching
- Supplied complete with exhaust port

Description:

A three way direct acting solenoid valve for on/off control of non-aggressive fluids and gases such as air, oil or water. Model 80C has normally closed switching and is supplied complete with exhaust port.

Ambient Temp	-20°C to 55°C
Fluid Temp	-10°C to 120°C
Viscosity	Max 37 cSt, 5°E
Body	Brass with Stainless Steel inner port
Seals	Viton
Coil Voltage	12V and 24Vdc, 24V, 110V and 230 Vac
Voltage Tolerance	± 10% (+10% -5% - 5% on pure DC)
Power Consumption	8 Watts AC/DC
Duty Cycle	100% continuous rating
Protection	IP65
Response Time	10 to 30ms

General Note
TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

© TT electronics plc

TT Electronics | Roxspur Measurement & Control
2 Downgate Drive, Sheffield, South Yorkshire, S4 8BT, UK |Ph: +44 (0) 114-244-2521
www.ttelectronics.com | RoxspurSales@ttelectronics.com