


# Round cylinder DSNU-32-320-PPV-A

Part number: 196029

**FESTO**



## Data sheet

| Feature                                  | Value                                                              |
|------------------------------------------|--------------------------------------------------------------------|
| Stroke                                   | 320 mm                                                             |
| Piston diameter                          | 32 mm                                                              |
| Piston rod thread                        | M10x1.25                                                           |
| Type code                                | DSNU                                                               |
| Cushioning                               | Pneumatic cushioning, adjustable at both ends                      |
| Mounting position                        | Any                                                                |
| Design                                   | Piston rod<br>Piston<br>Cylinder barrel                            |
| Position sensing                         | For proximity sensor                                               |
| Symbol                                   | 00991235                                                           |
| Operating pressure                       | 1 bar ... 10 bar                                                   |
| Mode of operation                        | Double-acting                                                      |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)         | 2 - Moderate corrosion stress                                      |
| Ambient temperature                      | -20 °C ... 80 °C                                                   |
| Cushioning length                        | 14 mm                                                              |
| Theoretical force at 6 bar, retracting   | 415 N                                                              |
| Theoretical force at 6 bar, advancing    | 482.5 N                                                            |
| Moving mass                              | 409 g                                                              |
| Product weight                           | 866 g                                                              |
| Type of mounting                         | With accessories                                                   |
| Pneumatic connection                     | G1/8                                                               |
| Note on materials                        | RoHS-compliant                                                     |
| Cover material                           | Wrought aluminum alloy                                             |
| Seals material                           | NBR<br>TPE-U(PU)                                                   |
| Piston rod material                      | High-alloy steel                                                   |
| Material of cylinder barrel              | High-alloy stainless steel                                         |