



Power Schottky Rectifier with common cathode

$$\begin{aligned} I_{FAV} &= 2 \times 15 \text{ A} \\ V_{RRM} &= 45 \text{ V} \\ V_F &= 0.43 \text{ V} \end{aligned}$$

V_{RSM}	V_{RRM}	Type
V	V	
45	45	DSSK 28-0045B



TO-220 AB
(B-Type)



A = Anode, C = Cathode, TAB = Cathode

Symbol	Conditions	Maximum Ratings		Features
I_{FRMS}		35	A	- International standard package - Very low V_F - Extremely low switching losses - Low I_{RM}-values - Epoxy meets UL 94V-0
I_{FAV}	$T_C = 135^\circ\text{C}$; rectangular, $d = 0.5$	15	A	
I_{FAV}	$T_C = 135^\circ\text{C}$; rectangular, $d = 0.5$; per device	30	A	
I_{FSM}	$T_{VJ} = 45^\circ\text{C}$; $t_p = 10 \text{ ms}$ (50 Hz), sine	320	A	
E_{AS}	$I_{AS} = 15 \text{ A}$; $L = 180 \mu\text{H}$; $T_{VJ} = 25^\circ\text{C}$; non repetitive	32	mJ	
I_{AR}	$V_A = 1.5 \cdot V_{RRM}$ typ.; $f = 10 \text{ kHz}$; repetitive	1.5	A	Applications - Rectifiers in switch mode power supplies (SMPS) - Free wheeling diode in low voltage converters
$(dv/dt)_{cr}$		1000	V/ μs	
T_{VJ}		-55...+150	$^\circ\text{C}$	
T_{VJM}		150	$^\circ\text{C}$	
T_{stg}		-55...+150	$^\circ\text{C}$	
P_{tot}	$T_C = 25^\circ\text{C}$	90	W	Advantages - High reliability circuit operation - Low voltage peaks for reduced protection circuits - Low noise switching - Low losses
M_d	mounting torque (Version B only)	0.4...0.6	Nm	
Weight	typical	2	g	

Symbol	Conditions	Characteristic Values	
		typ.	max.
I_R ①	$V_R = V_{RRM}$; $T_{VJ} = 25^\circ\text{C}$	20	mA
	$V_R = V_{RRM}$; $T_{VJ} = 100^\circ\text{C}$	100	mA
V_F	$I_F = 15 \text{ A}$; $T_{VJ} = 125^\circ\text{C}$	0.43	V
	$I_F = 15 \text{ A}$; $T_{VJ} = 25^\circ\text{C}$	0.48	V
	$I_F = 30 \text{ A}$; $T_{VJ} = 125^\circ\text{C}$	0.60	V
R_{thJC}		1.4	K/W
R_{thCH}	0.5		K/W

Pulse test: ① Pulse Width = 5 ms, Duty Cycle < 2.0 %
Data according to IEC 60747 and per diode unless otherwise specified.

Dimensions see Outlines.pdf

Recommended replacement:
DSB30C45PB/DSB60C45PB




Fig. 1 Maximum forward voltage drop characteristics




Fig. 2 Typ. value of reverse current I_R versus reverse voltage V_R




Fig. 3 Typ. junction capacitance C_T versus reverse voltage V_R




Fig. 4 Average forward current $I_{F(AV)}$ versus case temperature T_C




Fig. 5 Forward power loss characteristics




Fig. 6 Transient thermal impedance junction to case at various duty cycles

Note: All curves are per diode

IXYS reserves the right to change limits, Conditions and dimensions.

© 2006 IXYS All rights reserved