

Part Number: E1524S

Revision Level: 1

Date: 10/26/2007

4C 14 SOLID BC SR-PVC PVC
Fire Alarm/Life Safety Cable
A. CONSTRUCTION

Conductor:	#14 AWG Bare Copper	0.064" nom.
Insulation:	0.013" Wall Semi-Rigid Polyvinyl Chloride	0.090" nom.
Cable:	4C @ 4.00" LHL	0.218" nom.
Jacket:	0.015" Wall Polyvinyl Chloride - Red	0.248" +/- 0.012"
Print Legend:	CAROL A (R) 14 AWG - - E1524S - - 75C E66267-8 (UL) TYPE FPLR - - MADE IN USA (DATE CODE & SEQUENTIAL FOOTAGE 1000' TO 0')	

DIAMETERS
B. INDUSTRY APPROVALS

 National Electrical Code
 UL Standard 1424

 Article 760
 Type FPLR

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (V _{rms}):	300V
CONDUCTOR D.C. RESISTANCE:	2.5 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	32.54 pF/ft @ 1kHz nom
CHARACTERISTIC IMPEDANCE:	59.1 Ohms @ 1MHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	Red
3	Brown
4	Blue