General Cable Product Data Sheet

RoHS Compliant Directive 2002/95/EC

Part Number: E3000S | Revision Level: 3 | Date: 10/29/2007

2C 22 SOLID BC FLEX FLEX — **Sound, Alarm & Security Cable**

A. CONSTRUCTION

		DIAMETERS
Conductor:	#22 AWG Solid Bare Copper	0.025” nom.
Insulation:	0.007” Wall FLEXGUARD*	0.039” nom.
Cable:	2C @ 4.00" LHL	0.078” nom.
Jacket:	0.015” Wall FLEXGUARD* - Natural	0.108" +/- 0.005"
Print Legend:	***CAROL A (R) 22 AWG - - E3000S - - 75C E60233-8 60C (UL) CL3P --- C (UL) CMP - - MADE IN USA (DATE CODE & SEQUENTIAL FOOTAGE 1000’ TO 0’)***	

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 13	Type CL3P
National Electrical Code	Article 800
UL Standard 444	Type CMP

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (Vrms):	300V
CONDUCTOR D.C. RESISTANCE:	16.2 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	31.9 pF/ft @ 1kHz nom
CHARACTERISTIC IMPEDANCE:	63.7 Ohms @ 1MHz nom

D. COLOR CODE *(Listed as Individual Conductors or Pairs of Conductors)*

1	Black
2	Red

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.

*FLEXGUARD is a trademark of General Cable Corporation for polymer alloy insulation and jackets.