



## Miniature LEDs (2.0mm Diameter)

|         | Line No. | Part No. | Lens        | Luminous Intensity at 20mA |         | Viewing Angle 2θ½ | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|---------|----------|----------|-------------|----------------------------|---------|-------------------|-------------------------|---------|--------------------------|---------|
|         |          |          |             | Minimum                    | Typical |                   | Typical                 | Maximum |                          |         |
| ● RED   | 1        | E3       | Translucent | 0.5mcd                     | 3.0mcd  | 45°               | 2.1V                    | 2.7V    | 700nm                    | A       |
| ● GREEN | 2        | E5       | Translucent | 0.5mcd                     | 3.0mcd  | 45°               | 2.1V                    | 2.7V    | 560nm                    | A       |




## T-1 LEDs (Very Bright)

|          | Line No. | Part No. | Lens        | Luminous Intensity at 20mA |         | Viewing Angle 2θ½ | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|----------|----------|----------|-------------|----------------------------|---------|-------------------|-------------------------|---------|--------------------------|---------|
|          |          |          |             | Minimum                    | Maximum |                   | Typical                 | Maximum |                          |         |
| ● RED    | 3        | E100     | Clear       | 90mcd                      | 200mcd  | 50°               | 2.1V                    | 3.0V    | 625nm                    | B       |
| ● ORANGE | 4        | E102     | Clear       | 90mcd                      | 200mcd  | 50°               | 2.1V                    | 3.0V    | 610nm                    | B       |
|          | 5        | E103     | Translucent | 56mcd                      | 160mcd  | 50°               | 2.1V                    | 3.0V    | 610nm                    | B       |
| ● YELLOW | 6        | E104     | Clear       | 90mcd                      | 200mcd  | 50°               | 2.2V                    | 3.0V    | 585nm                    | B       |
|          | 7        | E105     | Translucent | 56mcd                      | 160mcd  | 50°               | 2.2V                    | 3.0V    | 585nm                    | B       |
| ● GREEN  | 8        | E106     | Clear       | 90mcd                      | 200mcd  | 50°               | 2.2V                    | 3.0V    | 565nm                    | B       |
| ● RED    | 9        | E112     | Diffused    | 36mcd                      | 100mcd  | 60°               | 2.1V                    | 3.0V    | 625nm                    | B       |
| ● ORANGE | 10       | E113     | Diffused    | 36mcd                      | 100mcd  | 60°               | 2.1V                    | 3.0V    | 610nm                    | B       |
| ● YELLOW | 11       | E114     | Diffused    | 36mcd                      | 100mcd  | 60°               | 2.2V                    | 3.0V    | 585nm                    | B       |
| ● GREEN  | 12       | E116     | Diffused    | 36mcd                      | 100mcd  | 60°               | 2.2V                    | 3.0V    | 565nm                    | B       |






## T-1 LEDs with Resistor - 5V

|          | Line No. | Part No. | Lens     | Voltage Range |         | Luminous Intensity at 5VDC |         | Viewing Angle 2θ½ | Current Range at 5VDC |         | Peak Wave Length at 5VDC | Drawing |
|----------|----------|----------|----------|---------------|---------|----------------------------|---------|-------------------|-----------------------|---------|--------------------------|---------|
|          |          |          |          | Minimum       | Maximum | Minimum                    | Maximum |                   | Minimum               | Maximum |                          |         |
| ● RED    | 1        | E404-5V  | Diffused | 4.0VDC        | 6.0VDC  | 70mcd                      | 200mcd  | 60°               | 8mA                   | 15.5mA  | 660nm                    | A       |
| ● YELLOW | 2        | E449-5V  | Diffused | 4.0VDC        | 6.0VDC  | 8mcd                       | 15mcd   | 60°               | 8mA                   | 15.5mA  | 590nm                    | A       |
| ● GREEN  | 3        | E451-5V  | Diffused | 4.0VDC        | 6.0VDC  | 12mcd                      | 20mcd   | 60°               | 8mA                   | 15.5mA  | 565nm                    | A       |




## T-1 Low Current LEDs (2mA)

|          | Line No. | Part No. | Lens     | Luminous Intensity at 2mA |         | Viewing Angle 2θ½ | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|----------|----------|----------|----------|---------------------------|---------|-------------------|-------------------------|---------|--------------------------|---------|
|          |          |          |          | Minimum                   | Typical |                   | Typical                 | Maximum |                          |         |
| ● RED    | 4        | E28      | Diffused | 8.0mcd                    | 20.0mcd | 60°               | 1.85V                   | 2.50V   | 660nm                    | B       |
| ● RED    | 5        | E30      | Diffused | 0.8mcd                    | 2.00mcd | 60°               | 2.00V                   | 2.50V   | 625nm                    | B       |
| ● YELLOW | 6        | E31      | Diffused | 0.8mcd                    | 2.00mcd | 60°               | 2.10V                   | 2.50V   | 590nm                    | B       |
| ● GREEN  | 7        | E32      | Diffused | 0.8mcd                    | 2.00mcd | 60°               | 2.20V                   | 2.50V   | 565nm                    | B       |




## T-1 Bi-Color LEDs (Two Leads)

|                  | Line No. | Part No. | Lens           | Luminous Intensity at 20mA |         | Viewing Angle 2θ½ | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|------------------|----------|----------|----------------|----------------------------|---------|-------------------|-------------------------|---------|--------------------------|---------|
|                  |          |          |                | Minimum                    | Maximum |                   | Typical                 | Maximum |                          |         |
| ● RED & GREEN    | 8        | E207     | White Diffused | 8mcd                       | 40mcd   | 60°               | 2.0V                    | 2.5V    | 625nm                    | C       |
| ● RED & YELLOW   | 9        | E208     | White Diffused | 8mcd                       | 40mcd   | 60°               | 2.0V                    | 2.5V    | 625nm                    | D       |
| ● GREEN & YELLOW | 10       | E209     | White Diffused | 8mcd                       | 40mcd   | 60°               | 2.2V                    | 2.5V    | 565nm                    | E       |




## T-1 Bi-Color LEDs (Three Leads)

|                  | Line No. | Part No. | Lens           | Luminous Intensity at 20mA |         | Viewing Angle 2θ½ | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Leads                                        | Drawing |
|------------------|----------|----------|----------------|----------------------------|---------|-------------------|-------------------------|---------|--------------------------|----------------------------------------------|---------|
|                  |          |          |                | Minimum                    | Maximum |                   | Typical                 | Maximum |                          |                                              |         |
| ● RED & GREEN    | 1        | E219     | White Diffused | 12.5mcd                    | 50mcd   | 60°               | 2.0V                    | 2.5V    | 625nm                    | 1.Red Anode<br>2.Cathode<br>3.Green Anode    | A       |
|                  |          |          |                | 12.5mcd                    | 50mcd   | 60°               | 2.2V                    | 2.5V    | 565nm                    |                                              |         |
| ● GREEN & YELLOW | 2        | E220     | White Diffused | 12.5mcd                    | 50mcd   | 60°               | 2.2V                    | 2.5V    | 565nm                    | 1.Green Anode<br>2.Cathode<br>3.Yellow Anode | A       |
|                  |          |          |                | 12.5mcd                    | 50mcd   | 60°               | 2.1V                    | 2.5V    | 590nm                    |                                              |         |
| ● RED & GREEN    | 3        | E293     | White Diffused | 90mcd                      | 300mcd  | 60°               | 1.85V                   | 2.5V    | 660nm                    | 1.Red Cathode<br>2.Anode<br>3.Green Cathode  | A       |
|                  |          |          |                | 20mcd                      | 40mcd   | 60°               | 2.20V                   | 2.5V    | 565nm                    |                                              |         |




## Mini LEDs

|                       | Line No. | Part No. | Lens        | Luminous Intensity at 10mA |         | Viewing Angle 2θ½ | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|-----------------------|----------|----------|-------------|----------------------------|---------|-------------------|-------------------------|---------|--------------------------|---------|
|                       |          |          |             | Minimum                    | Maximum |                   | Typical                 | Maximum |                          |         |
| ● ULTRA BRIGHT RED    | 4        | E260     | Translucent | 20.0mcd                    | 60.0mcd | 130°              | 1.85V                   | 2.5V    | 660nm                    | B       |
| ● HIGH EFFICIENCY RED | 5        | E261     | Translucent | 4.0mcd                     | 7.0mcd  | 130°              | 2.0V                    | 2.5V    | 625nm                    | B       |
| ● ORANGE              | 6        | E262     | Translucent | 3.0mcd                     | 7.0mcd  | 130°              | 2.0V                    | 2.6V    | 610nm                    | B       |
| ● YELLOW              | 7        | E263     | Translucent | 2.0mcd                     | 3.5mcd  | 130°              | 2.1V                    | 2.5V    | 590nm                    | B       |
| ● SUPER BRIGHT GREEN  | 8        | E264     | Translucent | 10.0mcd                    | 16.0mcd | 130°              | 2.2V                    | 2.5V    | 565nm                    | B       |




## T-1 Flat Top LEDs

|          | Line No. | Part No. | Lens     | Luminous Intensity at 10mA |         | Viewing Angle 2θ½ | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|----------|----------|----------|----------|----------------------------|---------|-------------------|-------------------------|---------|--------------------------|---------|
|          |          |          |          | Minimum                    | Maximum |                   | Typical                 | Maximum |                          |         |
| ● RED    | 9        | E265     | Diffused | 40.0mcd                    | 80.0mcd | 100°              | 1.85V                   | 2.5V    | 660nm                    | C       |
| ● RED    | 10       | E266     | Diffused | 3.2mcd                     | 12.5mcd | 100°              | 2.0V                    | 2.5V    | 625nm                    | C       |
| ● ORANGE | 11       | E267     | Diffused | 3.2mcd                     | 12.5mcd | 100°              | 2.0V                    | 2.6V    | 610nm                    | C       |
| ● YELLOW | 12       | E268     | Diffused | 1.3mcd                     | 8.0mcd  | 100°              | 2.1V                    | 2.5V    | 590nm                    | C       |
| ● GREEN  | 13       | E269     | Diffused | 8.0mcd                     | 20.0mcd | 100°              | 2.2V                    | 2.5V    | 565nm                    | C       |





## T-1, Right Angle LEDs (3mm)

|          | Line No. | Part No. | Lens     | Luminous Intensity at 10mA |         | Viewing Angle 20½ | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|----------|----------|----------|----------|----------------------------|---------|-------------------|-------------------------|---------|--------------------------|---------|
|          |          |          |          | Typical                    | Maximum |                   | Typical                 | Maximum |                          |         |
| ● RED    | 1        | E341     | Diffused | 12.5mcd                    | 32.0mcd | 60°               | 2.0V                    | 2.5V    | 625nm                    | A       |
| ● YELLOW | 2        | E344     | Diffused | 5.0mcd                     | 20.0mcd | 60°               | 2.1V                    | 2.5V    | 590nm                    | A       |
| ● GREEN  | 3        | E346     | Diffused | 5.0mcd                     | 20.0mcd | 60°               | 2.2V                    | 2.5V    | 565nm                    | A       |





## T-1¾ LEDs (Very Bright)

|          | Line No. | Part No. | Lens     | Luminous Intensity at 20mA |         | Viewing Angle 20½ | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|----------|----------|----------|----------|----------------------------|---------|-------------------|-------------------------|---------|--------------------------|---------|
|          |          |          |          | Minimum                    | Maximum |                   | Typical                 | Maximum |                          |         |
| ● RED    | 4        | E118     | Diffused | 36mcd                      | 100mcd  | 60°               | 2.1V                    | 3.0V    | 625nm                    | B       |
| ● ORANGE | 5        | E119     | Diffused | 36mcd                      | 100mcd  | 60°               | 2.1V                    | 3.0V    | 610nm                    | B       |
| ● YELLOW | 6        | E120     | Diffused | 36mcd                      | 100mcd  | 60°               | 2.2V                    | 3.0V    | 585nm                    | B       |
| ● GREEN  | 7        | E121     | Diffused | 36mcd                      | 100mcd  | 60°               | 2.2V                    | 3.0V    | 565nm                    | B       |





## T-1 and T-1<sup>3/4</sup> ,Ultra Bright, Red GaAlAs LEDs

|       | Line No. | Part No. | Size               | Lens     | Luminous Intensity at 20mA |         | Viewing Angle 2θ <sup>1/2</sup> | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|-------|----------|----------|--------------------|----------|----------------------------|---------|---------------------------------|-------------------------|---------|--------------------------|---------|
|       |          |          |                    |          | Minimum                    | Maximum |                                 | Typical                 | Maximum |                          |         |
| ● RED | 1        | E169     | T-1                | Clear    | 360mcd                     | 500mcd  | 50°                             | 1.85V                   | 2.50V   | 660nm                    | A       |
| ● RED | 2        | E170     | T-1                | Clear    | 500mcd                     | 700mcd  | 50°                             | 1.85V                   | 2.50V   | 660nm                    | A       |
| ● RED | 3        | E171     | T-1                | Clear    | 700mcd                     | 1000mcd | 50°                             | 1.85V                   | 2.50V   | 660nm                    | A       |
| ● RED | 4        | E197     | T-1                | Clear    | 1200mcd                    | 1400mcd | 50°                             | 1.85V                   | 2.50V   | 660nm                    | A       |
| ● RED | 5        | E181     | T-1 <sup>3/4</sup> | Clear    | 500mcd                     | 1000mcd | 30°                             | 1.85V                   | 2.5V    | 660nm                    | B       |
| ● RED | 6        | E183     | T-1 <sup>3/4</sup> | Clear    | 1300mcd                    | 1600mcd | 30°                             | 1.85V                   | 2.5V    | 660nm                    | B       |
| ● RED | 7        | E184     | T-1 <sup>3/4</sup> | Clear    | 2000mcd                    | 3500mcd | 30°                             | 1.85V                   | 2.5V    | 660nm                    | B       |
| ● RED | 8        | E301     | T-1 <sup>3/4</sup> | Diffused | 110mcd                     | 200mcd  | 60°                             | 1.85V                   | 2.5V    | 660nm                    | B       |
| ● RED | 9        | E303     | T-1 <sup>3/4</sup> | Diffused | 200mcd                     | 300mcd  | 60°                             | 1.85V                   | 2.5V    | 660nm                    | B       |
| ● RED | 10       | E304     | T-1 <sup>3/4</sup> | Diffused | 300mcd                     | 500mcd  | 60°                             | 1.85V                   | 2.5V    | 660nm                    | B       |





## T-1 and T-1<sup>3/4</sup>, Ultra Bright, Orange InGaAlP LEDs

|          | Line No. | Part No. | Size               | Lens               | Luminous Intensity at 20mA |         | Viewing Angle 2θ <sup>1/2</sup> | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|----------|----------|----------|--------------------|--------------------|----------------------------|---------|---------------------------------|-------------------------|---------|--------------------------|---------|
|          |          |          |                    |                    | Minimum                    | Maximum |                                 | Typical                 | Maximum |                          |         |
| ● ORANGE | 11       | E199     | T-1                | Orange Translucent | 500mcd                     | 1600mcd | 50°                             | 1.8V                    | 2.3V    | 620nm                    | C       |
| ● ORANGE | 12       | E194     | T-1 <sup>3/4</sup> | Orange Translucent | 700mcd                     | 3000mcd | 30°                             | 1.8V                    | 2.3V    | 620nm                    | D       |





## T-1 and T-1<sup>3/4</sup>, Ultra Bright , Yellow InGaAlP LEDs

|          | Line No. | Part No. | Size               | Lens               | Luminous Intensity at 20mA |         | Viewing Angle 2θ <sup>1/2</sup> | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|----------|----------|----------|--------------------|--------------------|----------------------------|---------|---------------------------------|-------------------------|---------|--------------------------|---------|
|          |          |          |                    |                    | Minimum                    | Maximum |                                 | Typical                 | Maximum |                          |         |
| ● YELLOW | 13       | E198     | T-1                | Yellow Translucent | 300mcd                     | 1000mcd | 50°                             | 2.0V                    | 2.5V    | 595nm                    | E       |
| ● YELLOW | 14       | E195     | T-1 <sup>3/4</sup> | Yellow Translucent | 400mcd                     | 1600mcd | 30°                             | 2.0V                    | 2.5V    | 595nm                    | F       |





## T-1 and T-1<sup>3/4</sup>, Super Bright, Green GaP LEDs

|         | Line No. | Part No. | Size               | Lens     | Luminous Intensity at 20mA |         | Viewing Angle 2θ <sub>1/2</sub> | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|---------|----------|----------|--------------------|----------|----------------------------|---------|---------------------------------|-------------------------|---------|--------------------------|---------|
|         |          |          |                    |          | Minimum                    | Maximum |                                 | Typical                 | Maximum |                          |         |
| ● GREEN | 1        | E166     | T-1                | Clear    | 100mcd                     | 300mcd  | 50°                             | 2.2V                    | 2.5V    | 565nm                    | A       |
| ● GREEN | 2        | E196     | T-1                | Diffused | 40mcd                      | 60mcd   | 60°                             | 2.2V                    | 2.5V    | 565nm                    | A       |
| ● GREEN | 3        | E168     | T-1 <sup>3/4</sup> | Clear    | 100mcd                     | 200mcd  | 30°                             | 2.2V                    | 2.5V    | 565nm                    | B       |





## T-1 and T-1<sup>3/4</sup>, Mega Bright Green, GaN LEDs

|         | Line No. | Part No. | Size               | Lens  | Luminous Intensity at 20mA |           | Viewing Angle 2θ <sub>1/2</sub> | Forward Voltage at 20mA |         | Reverse Current (V <sub>R</sub> =5.0V) | Peak Wave Length at 20mA | Drawing |
|---------|----------|----------|--------------------|-------|----------------------------|-----------|---------------------------------|-------------------------|---------|----------------------------------------|--------------------------|---------|
|         |          |          |                    |       | Minimum                    | Typical   |                                 | Typical                 | Maximum |                                        |                          |         |
| ● GREEN | 4        | E902     | T-1                | Clear | 2000mcd                    | 6800mcd   | 15°                             | 3.5V                    | 4.0V    | 50μA                                   | 525nm                    | C       |
| ● GREEN | 5        | E903     | T-1 <sup>3/4</sup> | Clear | 2500mcd                    | 10,000mcd | 15°                             | 3.5V                    | 4.0V    | 50μA                                   | 525nm                    | D       |



## T-1 and T-1<sup>3/4</sup>, Super Bright, Blue GaN LEDs


|        | Line No. | Part No. | Size               | Lens  | Luminous Intensity at 20mA |          | Viewing Angle 2θ <sup>1/2</sup> | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|--------|----------|----------|--------------------|-------|----------------------------|----------|---------------------------------|-------------------------|---------|--------------------------|---------|
|        |          |          |                    |       | Minimum                    | Maximum  |                                 | Typical                 | Maximum |                          |         |
| ● BLUE | 1        | E472     | T-1                | Clear | 20.0mcd                    | 90.0mcd  | 20°                             | 4.5V                    | 5.5V    | 430nm                    | A       |
| ● BLUE | 2        | E474     | T-1 <sup>3/4</sup> | Clear | 60.0mcd                    | 150.0mcd | 16°                             | 4.5V                    | 5.5V    | 430nm                    | B       |






## T-1 and T-1<sup>3/4</sup>, Mega Bright Blue GaN LEDs

|        | Line No. | Part No. | Size               | Lens  | Luminous Intensity at 20mA |         | Viewing Angle 2θ <sup>1/2</sup> | Forward Voltage at 20mA |         | Reverse Current (V <sub>R</sub> =5.0V) | Peak Wave Length at 20mA | Drawing |
|--------|----------|----------|--------------------|-------|----------------------------|---------|---------------------------------|-------------------------|---------|----------------------------------------|--------------------------|---------|
|        |          |          |                    |       | Minimum                    | Typical |                                 | Typical                 | Maximum |                                        |                          |         |
| ● BLUE | 3        | E482     | T-1                | Clear | 500mcd                     | 2000mcd | 15°                             | 3.6V                    | 4.0V    | 50μA                                   | 470nm                    | C       |
| ● BLUE | 4        | E484     | T-1 <sup>3/4</sup> | Clear | 750mcd                     | 3000mcd | 15°                             | 3.6V                    | 4.0V    | 50μA                                   | 470nm                    | D       |











## T-1, T-1<sup>3/4</sup> and SMT Bright White LEDs

|         | Line No. | Part No. | Size               | Lens  | Luminous Intensity at 20mA |         | Viewing Angle 2θ½ | Forward Voltage at 20mA |         | Reverse Current (V <sub>R</sub> =5.0V) | Chromaticity Coordinates |        | Drawing |
|---------|----------|----------|--------------------|-------|----------------------------|---------|-------------------|-------------------------|---------|----------------------------------------|--------------------------|--------|---------|
|         |          |          |                    |       | Minimum                    | Typical |                   | Typical                 | Maximum |                                        | X Typ.                   | Y Typ. |         |
| ○ WHITE | 1        | E1007    | T-1                | Clear | 50mcd                      | 180mcd  | 50°               | 3.8V                    | 4.5V    | 10μA                                   | 0.31                     | 0.32   | A       |
| ○ WHITE | 2        | E1006    | T-1 <sup>3/4</sup> | Clear | 80mcd                      | 200mcd  | 30°               | 3.8V                    | 4.5V    | 10μA                                   | 0.31                     | 0.32   | B       |
| ○ WHITE | 3        | E1008    | SMT                | Clear | 90mcd                      | 150mcd  | 120°              | 3.5V                    | 4.0V    | 10μA                                   | 0.31                     | 0.32   | C       |





## T-1 and T-1¾ ,Ultra Bright, Red GaAlAs LEDs

|       | Line No. | Part No. | Size | Lens     | Luminous Intensity at 20mA |         | Viewing Angle 2θ½ | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|-------|----------|----------|------|----------|----------------------------|---------|-------------------|-------------------------|---------|--------------------------|---------|
|       |          |          |      |          | Minimum                    | Maximum |                   | Typical                 | Maximum |                          |         |
| ● RED | 1        | E169     | T-1  | Clear    | 360mcd                     | 500mcd  | 50°               | 1.85V                   | 2.50V   | 660nm                    | A       |
| ● RED | 2        | E170     | T-1  | Clear    | 500mcd                     | 700mcd  | 50°               | 1.85V                   | 2.50V   | 660nm                    | A       |
| ● RED | 3        | E171     | T-1  | Clear    | 700mcd                     | 1000mcd | 50°               | 1.85V                   | 2.50V   | 660nm                    | A       |
| ● RED | 4        | E197     | T-1  | Clear    | 1200mcd                    | 1400mcd | 50°               | 1.85V                   | 2.50V   | 660nm                    | A       |
| ● RED | 5        | E181     | T-1¾ | Clear    | 500mcd                     | 1000mcd | 30°               | 1.85V                   | 2.5V    | 660nm                    | B       |
| ● RED | 6        | E183     | T-1¾ | Clear    | 1300mcd                    | 1600mcd | 30°               | 1.85V                   | 2.5V    | 660nm                    | B       |
| ● RED | 7        | E184     | T-1¾ | Clear    | 2000mcd                    | 3500mcd | 30°               | 1.85V                   | 2.5V    | 660nm                    | B       |
| ● RED | 8        | E301     | T-1¾ | Diffused | 110mcd                     | 200mcd  | 60°               | 1.85V                   | 2.5V    | 660nm                    | B       |
| ● RED | 9        | E303     | T-1¾ | Diffused | 200mcd                     | 300mcd  | 60°               | 1.85V                   | 2.5V    | 660nm                    | B       |
| ● RED | 10       | E304     | T-1¾ | Diffused | 300mcd                     | 500mcd  | 60°               | 1.85V                   | 2.5V    | 660nm                    | B       |





## T-1 and T-1¾, Ultra Bright, Orange InGaAlP LEDs

|          | Line No. | Part No. | Size | Lens               | Luminous Intensity at 20mA |         | Viewing Angle 2θ½ | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|----------|----------|----------|------|--------------------|----------------------------|---------|-------------------|-------------------------|---------|--------------------------|---------|
|          |          |          |      |                    | Minimum                    | Maximum |                   | Typical                 | Maximum |                          |         |
| ● ORANGE | 11       | E199     | T-1  | Orange Translucent | 500mcd                     | 1600mcd | 50°               | 1.8V                    | 2.3V    | 620nm                    | C       |
| ● ORANGE | 12       | E194     | T-1¾ | Orange Translucent | 700mcd                     | 3000mcd | 30°               | 1.8V                    | 2.3V    | 620nm                    | D       |





## T-1 and T-1¾, Ultra Bright , Yellow InGaAlP LEDs

|          | Line No. | Part No. | Size | Lens               | Luminous Intensity at 20mA |         | Viewing Angle 2θ½ | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|----------|----------|----------|------|--------------------|----------------------------|---------|-------------------|-------------------------|---------|--------------------------|---------|
|          |          |          |      |                    | Minimum                    | Maximum |                   | Typical                 | Maximum |                          |         |
| ● YELLOW | 13       | E198     | T-1  | Yellow Translucent | 300mcd                     | 1000mcd | 50°               | 2.0V                    | 2.5V    | 595nm                    | E       |
| ● YELLOW | 14       | E195     | T-1¾ | Yellow Translucent | 400mcd                     | 1600mcd | 30°               | 2.0V                    | 2.5V    | 595nm                    | F       |





## T-1 and T-1<sup>3/4</sup>, Super Bright, Green GaP LEDs

|         | Line No. | Part No. | Size               | Lens     | Luminous Intensity at 20mA |         | Viewing Angle 2θ <sub>1/2</sub> | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|---------|----------|----------|--------------------|----------|----------------------------|---------|---------------------------------|-------------------------|---------|--------------------------|---------|
|         |          |          |                    |          | Minimum                    | Maximum |                                 | Typical                 | Maximum |                          |         |
| ● GREEN | 1        | E166     | T-1                | Clear    | 100mcd                     | 300mcd  | 50°                             | 2.2V                    | 2.5V    | 565nm                    | A       |
| ● GREEN | 2        | E196     | T-1                | Diffused | 40mcd                      | 60mcd   | 60°                             | 2.2V                    | 2.5V    | 565nm                    | A       |
| ● GREEN | 3        | E168     | T-1 <sup>3/4</sup> | Clear    | 100mcd                     | 200mcd  | 30°                             | 2.2V                    | 2.5V    | 565nm                    | B       |





## T-1 and T-1<sup>3/4</sup>, Mega Bright Green, GaN LEDs

|         | Line No. | Part No. | Size               | Lens  | Luminous Intensity at 20mA |           | Viewing Angle 2θ <sub>1/2</sub> | Forward Voltage at 20mA |         | Reverse Current (V <sub>R</sub> =5.0V) | Peak Wave Length at 20mA | Drawing |
|---------|----------|----------|--------------------|-------|----------------------------|-----------|---------------------------------|-------------------------|---------|----------------------------------------|--------------------------|---------|
|         |          |          |                    |       | Minimum                    | Typical   |                                 | Typical                 | Maximum |                                        |                          |         |
| ● GREEN | 4        | E902     | T-1                | Clear | 2000mcd                    | 6800mcd   | 15°                             | 3.5V                    | 4.0V    | 50μA                                   | 525nm                    | C       |
| ● GREEN | 5        | E903     | T-1 <sup>3/4</sup> | Clear | 2500mcd                    | 10,000mcd | 15°                             | 3.5V                    | 4.0V    | 50μA                                   | 525nm                    | D       |



## T-1 and T-1<sup>3/4</sup>, Super Bright, Blue GaN LEDs



|        | Line No. | Part No. | Size               | Lens  | Luminous Intensity at 20mA |          | Viewing Angle 2θ <sup>1/2</sup> | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|--------|----------|----------|--------------------|-------|----------------------------|----------|---------------------------------|-------------------------|---------|--------------------------|---------|
|        |          |          |                    |       | Minimum                    | Maximum  |                                 | Typical                 | Maximum |                          |         |
| ● BLUE | 1        | E472     | T-1                | Clear | 20.0mcd                    | 90.0mcd  | 20°                             | 4.5V                    | 5.5V    | 430nm                    | A       |
| ● BLUE | 2        | E474     | T-1 <sup>3/4</sup> | Clear | 60.0mcd                    | 150.0mcd | 16°                             | 4.5V                    | 5.5V    | 430nm                    | B       |



## T-1 and T-1<sup>3/4</sup>, Mega Bright Blue GaN LEDs


|        | Line No. | Part No. | Size               | Lens  | Luminous Intensity at 20mA |         | Viewing Angle 2θ <sup>1/2</sup> | Forward Voltage at 20mA |         | Reverse Current (V <sub>R</sub> =5.0V) | Peak Wave Length at 20mA | Drawing |
|--------|----------|----------|--------------------|-------|----------------------------|---------|---------------------------------|-------------------------|---------|----------------------------------------|--------------------------|---------|
|        |          |          |                    |       | Minimum                    | Typical |                                 | Typical                 | Maximum |                                        |                          |         |
| ● BLUE | 3        | E482     | T-1                | Clear | 500mcd                     | 2000mcd | 15°                             | 3.6V                    | 4.0V    | 50μA                                   | 470nm                    | C       |
| ● BLUE | 4        | E484     | T-1 <sup>3/4</sup> | Clear | 750mcd                     | 3000mcd | 15°                             | 3.6V                    | 4.0V    | 50μA                                   | 470nm                    | D       |







## T-1 and T-1¾, Mega Bright White LEDs

|         | Line No. | Part No. | Size | Lens  | Luminous Intensity at 20mA |         | Viewing Angle 2θ½ | Forward Voltage at 20mA |         | Reverse Current (V <sub>R</sub> =5.0V) | Chromaticity Coordinates |        | Drawing |
|---------|----------|----------|------|-------|----------------------------|---------|-------------------|-------------------------|---------|----------------------------------------|--------------------------|--------|---------|
|         |          |          |      |       | Minimum                    | Typical |                   | Typical                 | Maximum |                                        | X Typ.                   | Y Typ. |         |
| ○ WHITE | 1        | E1004    | T-1  | Clear | 700mcd                     | 2800mcd | 25°               | 3.6V                    | 4.0V    | 50μA                                   | 0.31                     | 0.32   | A       |
| ○ WHITE | 2        | E1003    | T-1¾ | Clear | 1400mcd                    | 5600mcd | 15°               | 3.6V                    | 4.0V    | 50μA                                   | 0.31                     | 0.32   | B       |




## T-1¾ Full Color LEDs

|         | Line No. | Part No. | Lens           | Luminous Intensity at 20mA |         | Viewing Angle 2θ½ | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|---------|----------|----------|----------------|----------------------------|---------|-------------------|-------------------------|---------|--------------------------|---------|
|         |          |          |                | Minimum                    | Maximum |                   | Typical                 | Maximum |                          |         |
| ○ WHITE | 3        | E1000    | Clear          | 90mcd                      | 200mcd  | 15°               | 2.0V                    | 2.5V    | 625nm                    | C       |
|         |          |          |                | 50mcd                      | 90mcd   | 15°               | 2.2V                    | 2.5V    | 565nm                    |         |
|         |          |          |                | 12.5mcd                    | 40mcd   | 15°               | 4.5V                    | 5.5V    | 430nm                    |         |
| ○ WHITE | 4        | E1001    | Diffused White | 20.0mcd                    | 90.0mcd | 30°               | 2.0V                    | 2.5V    | 625nm                    | C       |
|         |          |          |                | 20.0mcd                    | 70.0mcd | 30°               | 2.2V                    | 2.5V    | 565nm                    |         |
|         |          |          |                | 3.2mcd                     | 12.5mcd | 30°               | 4.5V                    | 5.5V    | 430nm                    |         |




## T-1 and T-1<sup>3/4</sup>, Infrared LEDs: 880nm, 940nm

|          | Line No. | Part No. | Size               | Lens       | Radiant Power at 20mA |           | Viewing Angle 2θ <sup>1/2</sup> | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|----------|----------|----------|--------------------|------------|-----------------------|-----------|---------------------------------|-------------------------|---------|--------------------------|---------|
|          |          |          |                    |            | Minimum               | Typical   |                                 | Typical                 | Maximum |                          |         |
| INFRARED | 1        | E21      | T-1                | Clear      | 2.0mW/sr              | 10.0mW/sr | 30°                             | 1.2V                    | 1.5V    | 940nm                    | A       |
| INFRARED | 2        | E22      | T-1                | Trans.Blue | 2.0mW/sr              | 4.0mW/sr  | 30°                             | 1.4V                    | 1.7V    | 880nm                    | A       |
| INFRARED | 3        | E23      | T-1 <sup>3/4</sup> | Clear      | 8.0mW/sr              | 20.0mW/sr | 30°                             | 1.2V                    | 1.5V    | 940nm                    | B       |
| INFRARED | 4        | E24      | T-1 <sup>3/4</sup> | Trans.Blue | 5.0mW/sr              | 20.0mW/sr | 30°                             | 1.4V                    | 1.7V    | 880nm                    | B       |




## T-1<sup>3/4</sup> LEDs with Resistor - 5V

|          | Line No. | Part No. | Lens     | Voltage Range |         | Luminous Intensity at 5VDC |         | Viewing Angle 2θ <sup>1/2</sup> | Current Range at 5VDC |         | Peak Wave Length at 5VDC | Drawing |
|----------|----------|----------|----------|---------------|---------|----------------------------|---------|---------------------------------|-----------------------|---------|--------------------------|---------|
|          |          |          |          | Minimum       | Maximum | Minimum                    | Maximum |                                 | Minimum               | Maximum |                          |         |
| ● RED    | 5        | E304-5V  | Diffused | 4.0VDC        | 6.0VDC  | 100mcd                     | 300mcd  | 60°                             | 8mA                   | 15.5mA  | 660nm                    | C       |
| ● RED    | 6        | E148-5V  | Diffused | 4.0VDC        | 6.0VDC  | 5mcd                       | 30mcd   | 60°                             | 8mA                   | 15.5mA  | 625nm                    | C       |
| ● YELLOW | 7        | E149-5V  | Diffused | 4.0VDC        | 6.0VDC  | 5mcd                       | 20mcd   | 60°                             | 8mA                   | 15.5mA  | 590nm                    | C       |
| ● GREEN  | 8        | E151-5V  | Clear    | 4.0VDC        | 6.0VDC  | 20mcd                      | 150mcd  | 30°                             | 8mA                   | 15.5mA  | 565nm                    | C       |
| ● GREEN  | 9        | E150-5V  | Diffused | 4.0VDC        | 6.0VDC  | 5mcd                       | 20mcd   | 60°                             | 8mA                   | 15.5mA  | 565nm                    | C       |




## T-1<sup>3/4</sup> LEDs with Resistor - 12V

|          | Line No. | Part No. | Lens     | Voltage Range |         | Luminous Intensity at 12VDC |         | Viewing Angle 2θ <sup>1/2</sup> | Current Range at 12VDC |         | Peak Wave Length at 12VDC | Drawing |
|----------|----------|----------|----------|---------------|---------|-----------------------------|---------|---------------------------------|------------------------|---------|---------------------------|---------|
|          |          |          |          | Minimum       | Maximum | Minimum                     | Maximum |                                 | Minimum                | Maximum |                           |         |
| ● RED    | 10       | E304-12V | Diffused | 9.5VDC        | 13.0VDC | 100mcd                      | 300mcd  | 60°                             | 8mA                    | 15.5mA  | 660nm                     | D       |
| ● YELLOW | 11       | E149-12V | Diffused | 9.5VDC        | 13.0VDC | 5mcd                        | 15mcd   | 60°                             | 8mA                    | 15.5mA  | 590nm                     | D       |
| ● GREEN  | 12       | E151-12V | Diffused | 9.5VDC        | 13.0VDC | 12mcd                       | 20mcd   | 60°                             | 8mA                    | 15.5mA  | 565nm                     | D       |




## T-1<sup>3/4</sup> Low Current LEDs (2mA)

|          | Line No. | Part No. | Lens     | Luminous Intensity at 2mA |         | Viewing Angle 2θ <sub>1/2</sub> | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|----------|----------|----------|----------|---------------------------|---------|---------------------------------|-------------------------|---------|--------------------------|---------|
|          |          |          |          | Minimum                   | Typical |                                 | Typical                 | Maximum |                          |         |
| ● RED    | 1        | E29      | Diffused | 8.0mcd                    | 20.0mcd | 60°                             | 1.85V                   | 2.5V    | 660nm                    | A       |
| ● RED    | 2        | E33      | Diffused | 0.8mcd                    | 2.0mcd  | 60°                             | 2.0V                    | 2.5V    | 625nm                    | A       |
| ● YELLOW | 3        | E34      | Diffused | 0.8mcd                    | 2.0mcd  | 60°                             | 2.1V                    | 2.5V    | 590nm                    | A       |
| ● GREEN  | 4        | E35      | Diffused | 0.8mcd                    | 2.0mcd  | 60°                             | 2.2V                    | 2.5V    | 565nm                    | A       |




## T-1<sup>3/4</sup> Flashing LEDs

|          | Line No. | Part No. | Lens     | Forward D.C. Voltage |         |      | Forward Current (mA) |         |     | Luminous Intensity at 9.0 VDC |        | Viewing Angle 2θ <sub>1/2</sub> | Frequency (Hz) | Peak Wave Length | Drawing |
|----------|----------|----------|----------|----------------------|---------|------|----------------------|---------|-----|-------------------------------|--------|---------------------------------|----------------|------------------|---------|
|          |          |          |          | Min                  | Typical | Max  | Min                  | Typical | Max | Min                           | Max    |                                 |                |                  |         |
| ● RED    | 5        | E157     | Diffused | 3.5                  | 12.0    | 13.0 | 38                   | 56      | 70  | 100mcd                        | 300mcd | 60°                             | 2.5 - 1.5      | 660nm            | B       |
|          | 6        | E158     | Clear    | 3.5                  | 12.0    | 13.0 | 38                   | 56      | 70  | 400mcd                        | 900mcd | 30°                             | 2.5 - 1.5      | 660nm            | B       |
|          | 7        | E159     | Diffused | 3.5                  | 12.0    | 13.0 | 38                   | 56      | 70  | 20mcd                         | 80mcd  | 60°                             | 2.5 - 1.5      | 625nm            | B       |
| ● YELLOW | 8        | E160     | Diffused | 3.5                  | 12.0    | 13.0 | 38                   | 56      | 70  | 5mcd                          | 32mcd  | 60°                             | 2.5 - 1.5      | 590nm            | B       |
| ● GREEN  | 9        | E161     | Diffused | 3.5                  | 12.0    | 13.0 | 38                   | 56      | 70  | 5mcd                          | 32mcd  | 60°                             | 2.5 - 1.5      | 565nm            | B       |






## T-1<sup>3/4</sup> Bi-Color LEDs (Very Bright)

|                  | Line No. | Part No. | Lens           | Luminous Intensity at 20mA |         | Viewing Angle 2θ <sub>1/2</sub> | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Leads                                        | Drawing |
|------------------|----------|----------|----------------|----------------------------|---------|---------------------------------|-------------------------|---------|--------------------------|----------------------------------------------|---------|
|                  |          |          |                | Minimum                    | Maximum |                                 | Typical                 | Maximum |                          |                                              |         |
| ● RED & GREEN    | 10       | E203     | White Diffused | 20.0mcd                    | 90.0mcd | 60°                             | 2.0V                    | 2.5V    | 625nm                    | 1.Red Anode<br>2.Cathode<br>3.Green Anode    | C       |
| ● RED & GREEN    | 11       | E204     | White Diffused | 3.2mcd                     | 8.0mcd  | 60°                             | 2.0V                    | 2.5V    | 625nm                    | 1.Red Cathode<br>2.Anode<br>3.Green Cathode  | C       |
| ● RED & YELLOW   | 12       | E205     | White Diffused | 20.0mcd                    | 90.0mcd | 60°                             | 2.0V                    | 2.5V    | 625nm                    | 1.Red Anode<br>2.Cathode<br>3.Yellow Anode   | C       |
| ● GREEN & YELLOW | 13       | E206     | White Diffused | 20.0mcd                    | 90.0mcd | 60°                             | 2.2V                    | 2.5V    | 565nm                    | 1.Green Anode<br>2.Cathode<br>3.Yellow Anode | C       |




## T-1<sup>3/4</sup> Bi-Color Ultra Bright LEDs

|             | Line No. | Part No. | Lens           | Luminous Intensity at 20mA |                  | Viewing Angle 20° | Forward Voltage at 20mA |              | Peak Wave Length at 20mA | Leads                                          | Drawing |
|-------------|----------|----------|----------------|----------------------------|------------------|-------------------|-------------------------|--------------|--------------------------|------------------------------------------------|---------|
|             |          |          |                | Minimum                    | Maximum          |                   | Typical                 | Maximum      |                          |                                                |         |
| RED & GREEN | 1        | E231     | White Diffused | 100mcd<br>40mcd            | 300mcd<br>80mcd  | 60°<br>60°        | 1.85V<br>2.20V          | 2.5V<br>2.5V | 660nm<br>565nm           | 1. Red Anode<br>2. Cathode<br>3. Green Anode   | A       |
| RED & GREEN | 2        | E232     | Clear          | 300mcd<br>80mcd            | 700mcd<br>200mcd | 30°<br>30°        | 1.85V<br>2.20V          | 2.5V<br>2.5V | 660nm<br>565nm           | 1. Red Anode<br>2. Cathode<br>3. Green Anode   | A       |
| RED & GREEN | 3        | E291     | Clear          | 300mcd<br>80mcd            | 700mcd<br>200mcd | 24°<br>24°        | 1.85V<br>2.20V          | 2.5V<br>2.5V | 660nm<br>565nm           | 1. Red Cathode<br>2. Anode<br>3. Green Cathode | A       |
| RED & GREEN | 4        | E292     | White Diffused | 100mcd<br>40mcd            | 300mcd<br>80mcd  | 24°<br>24°        | 1.85V<br>2.20V          | 2.5V<br>2.5V | 660nm<br>565nm           | 1. Red Cathode<br>2. Anode<br>3. Green Cathode | A       |




## T-1<sup>3/4</sup> Bi-Color LEDs (Two Leads)

|                | Line No. | Part No. | Lens           | Luminous Intensity at 20mA |                | Viewing Angle 20° | Forward Voltage at 20mA |              | Peak Wave Length at 20mA | Drawing |
|----------------|----------|----------|----------------|----------------------------|----------------|-------------------|-------------------------|--------------|--------------------------|---------|
|                |          |          |                | Minimum                    | Maximum        |                   | Typical                 | Maximum      |                          |         |
| RED & GREEN    | 5        | E210     | White Diffused | 20.0mcd<br>12.5mcd         | 50mcd<br>40mcd | 60°<br>60°        | 2.0V<br>2.2V            | 2.5V<br>2.5V | 625nm<br>565nm           | B       |
| RED & YELLOW   | 6        | E211     | White Diffused | 20mcd<br>5mcd              | 50mcd<br>20mcd | 60°<br>60°        | 2.0V<br>2.1V            | 2.5V<br>2.5V | 625nm<br>590nm           | C       |
| GREEN & YELLOW | 7        | E212     | White Diffused | 12.5mcd<br>5.0mcd          | 40mcd<br>20mcd | 60°<br>60°        | 2.2V<br>2.2V            | 2.5V<br>2.5V | 565nm<br>590nm           | D       |




## T-1<sup>3</sup>/<sub>4</sub> Fresnel LEDs

|          | Line No. | Part No. | Lens     | Luminous Intensity at 20mA |         | Viewing Angle 2θ <sup>1</sup> / <sub>2</sub> | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|----------|----------|----------|----------|----------------------------|---------|----------------------------------------------|-------------------------|---------|--------------------------|---------|
|          |          |          |          | Minimum                    | Maximum |                                              | Typical                 | Maximum |                          |         |
| ● RED    | 1        | E276     | Diffused | 30.0mcd                    | 50.0mcd | 70°                                          | 1.85V                   | 2.5V    | 660nm                    | A       |
| ● YELLOW | 2        | E277     | Diffused | 3.2mcd                     | 5.0mcd  | 70°                                          | 2.1V                    | 2.5V    | 590nm                    | A       |
| ● GREEN  | 3        | E278     | Diffused | 3.2mcd                     | 5.0mcd  | 70°                                          | 2.2V                    | 2.5V    | 565nm                    | A       |



## T-1<sup>3</sup>/<sub>4</sub> Flat Top LEDs

|          | Line No. | Part No. | Lens     | Luminous Intensity at 10mA |         | Viewing Angle 2θ <sup>1</sup> / <sub>2</sub> | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|----------|----------|----------|----------|----------------------------|---------|----------------------------------------------|-------------------------|---------|--------------------------|---------|
|          |          |          |          | Minimum                    | Maximum |                                              | Typical                 | Maximum |                          |         |
| ● RED    | 4        | E270     | Diffused | 25.0mcd                    | 60.0mcd | 70°                                          | 1.85V                   | 2.5V    | 660nm                    | B       |
| ● RED    | 5        | E271     | Diffused | 3.2mcd                     | 12.5mcd | 70°                                          | 2.0V                    | 2.5V    | 625nm                    | B       |
| ● ORANGE | 6        | E272     | Diffused | 3.2mcd                     | 12.5mcd | 70°                                          | 2.0V                    | 2.6V    | 610nm                    | B       |
| ● YELLOW | 7        | E273     | Diffused | 1.3mcd                     | 8.0mcd  | 70°                                          | 2.1V                    | 2.5V    | 590nm                    | B       |
| ● GREEN  | 8        | E274     | Diffused | 5.0mcd                     | 20.0mcd | 80°                                          | 2.2V                    | 2.5V    | 565nm                    | B       |



## T-1<sup>3</sup>/<sub>4</sub>, Right Angle Leads, LEDs (5mm)

|          | Line No. | Part No. | Lens     | Luminous Intensity at 10mA |         | Viewing Angle 2θ <sup>1</sup> / <sub>2</sub> | Forward Voltage at 20mA |         | Peak Wave Length at 20mA | Drawing |
|----------|----------|----------|----------|----------------------------|---------|----------------------------------------------|-------------------------|---------|--------------------------|---------|
|          |          |          |          | Minimum                    | Maximum |                                              | Typical                 | Maximum |                          |         |
| ● RED    | 9        | E241     | Diffused | 12.5mcd                    | 32.0mcd | 60°                                          | 2.0V                    | 2.5V    | 625nm                    | C       |
| ● ORANGE | 10       | E242     | Diffused | 12.5mcd                    | 32.0mcd | 60°                                          | 2.0V                    | 2.6V    | 610nm                    | C       |
| ● YELLOW | 11       | E244     | Diffused | 5.0mcd                     | 20.0mcd | 60°                                          | 2.1V                    | 2.5V    | 590nm                    | C       |
| ● GREEN  | 12       | E246     | Diffused | 5.0mcd                     | 20.0mcd | 60°                                          | 2.2V                    | 2.5V    | 565nm                    | C       |