

塑封超快速整流二极管


反向电压 200 --- 1000V

正向电流 0.5 --- 0.7A

Plastic Ultra-Fast Recover Rectifiers

Reverse Voltage 200 to 1000V

Forward Current 0.5 to 0.7A



特征 Features

- 反向漏电流低 Low reverse leakage
- 正向浪涌承受能力较强 High forward surge capability
- 高温焊接保证 High temperature soldering guaranteed:
260℃/10 秒, 0.375" (9.5mm) 引线长度。
260℃/10 seconds, 0.375" (9.5mm) lead length,
- 引线可承受5 磅 (2.3kg) 拉力。 5 lbs. (2.3kg) tension
- 引线 and 管体皆符合RoHS标准 。
Lead and body according with RoHS standard

机械数据 Mechanical Data

- 端子: 镀锡轴向引线 Terminals: Plated axial leads
- 极性: 色环端为负极 Polarity: Color band denotes cathode end
- 安装位置: 任意 Mounting Position: Any

极限值和温度特性 TA = 25℃ 除非另有规定。

Maximum Ratings & Thermal Characteristics Ratings at 25℃ ambient temperature unless otherwise specified.

	符号 Symbols	EG 01Z	EG 01	EG 01A	EG 01C	单位 Unit
最大可重复峰值反向电压 Maximum repetitive peak reverse voltage	V _{RRM}	200	400	600	1000	V
最大均方根电压 Maximum RMS voltage	V _{RMS}	140	280	420	700	V
最大直流阻断电压 Maximum DC blocking voltage	V _{DC}	200	400	600	1000	V
最大正向平均整流电流 Maximum average forward rectified current	I _{F(AV)}	0.7		0.5		A
峰值正向浪涌电流 8.3ms单一正弦半波 Peak forward surge current 8.3 ms single half sine-wave	I _{FSM}	15		10		A
典型热阻 Typical thermal resistance	R _{θJA}	65				℃/W
工作结温和存储温度 Operating junction and storage temperature range	T _J , T _{STG}	-55 --- +150				℃

电特性 TA = 25℃ 除非另有规定。


Electrical Characteristics Ratings at 25℃ ambient temperature unless otherwise specified.

	符号 Symbols	EG 01Z	EG 01	EG 01A	EG 01C	单位 Unit
最大正向电压 Maximum forward voltage I _F = 1.0A	V _F	1.9	2.0	2.0	3.3	V
最大反向电流 Maximum reverse current T _A = 25℃ T _A =100℃	I _R	5.0 100				μA
最大反向恢复时间 MAX. Reverse Recovery Time I _F =0.5A I _R =1.0A I _{RR} =0.25A	t _{rr}	50			75	nS
典型结电容 Type junction capacitance V _R = 4.0V, f = 1MHz	C _j	18				pF

特性曲线 Characteristic Curves


正向特性曲线（典型值）

TYPICAL FORWARD CHARACTERISTIC



正向电流降额曲线

FORWARD CURRENT DERATING CURVE



浪涌特性曲线（最大值）

MAXIMUM NON REPETITIVE
PEAK FORWARD SURGE CURRENT