


4 PIN DIP HIGH VOLTAGE PHOTOTRANSISTOR PHOTOCOUPLER

EL851 series

Features

- High collector- emitter voltage ($V_{CEO}=350V$)
- Current transfer ratio
(CTR: 50 to 600% at $I_F=5mA$, $V_{CE}=5V$)
- High isolation voltage between input and output
Viso = 5000 Vrms
- Compact dual-in-line package
- Pb free and RoHS compliant.
- UL approved (No E214129)
- VDE approved (No 132249)
- SEMKO approved
- NEMKO approved
- DEMKO approved
- FIMKO approved
- CSA approved




Description

The EL851 series devices consist an infrared emitting diodes, optically coupled to a phototransistor detector.

The devices are in a 4-pin DIP package and available in wide-lead spacing and SMD option.

Applications

- Telephone line interface
- Interface to power supply circuit
- Controller for SSRs. DC motor
- Programmable Controllers



1. Anode
2. Cathode
3. Emitter
4. Collector

4 PIN DIP HIGH VOLTAGE PHOTOTRANSISTOR PHOTOCOUPLER

EL851 series

Absolute Maximum Ratings (T_a=25 °C)

Parameter		Symbol	Rating	Unit
Input	Forward current	I _F	80	mA
	Peak forward current (1μs pulse)	I _{FM}	1	A
	Reverse voltage	V _R	6	V
	Power dissipation	P _D	150	mW
Output	Collector power dissipation	P _C	300	mW
	Collector-Emitter voltage	V _{CEO}	350	V
	Collector Current	I _C	100	mA
	Emitter-Collector voltage	V _{ECO}	7	V
Total power dissipation		P _{tot}	260	mW
Isolation voltage ^{*1}		V _{iso}	5000	V _{rms}
Operating temperature		T _{opr}	-55~+100	°C
Storage temperature		T _{stg}	-55~+150	°C
Soldering temperature ^{*2}		T _{sol}	260	°C

Notes

*1 AC for 1 minute, R.H.= 40 ~ 60% R.H. In this test, pins 1 & 2 are shorted together, and pins 3 & 4 are shorted together.

*2 For 10 seconds.

4 PIN DIP HIGH VOLTAGE PHOTOTRANSISTOR PHOTOCOUPLER

EL851 series

Electrical Characteristics ($T_a=25^{\circ}\text{C}$ unless specified otherwise)

Input

Parameter	Symbol	Min.	Typ.*	Max.	Unit	Condition
Forward voltage	V_F	-	1.2	1.4	V	$I_F = 10\text{mA}$
Reverse current	I_R	-	-	10	μA	$V_R = 5\text{V}$
Input capacitance	C_{in}	-	30	-	pF	$V = 0, f = 1\text{MHz}$

Output

Parameter	Symbol	Min.	Typ.*	Max.	Unit	Condition
Collector-Emitter dark current	I_{CEO}	-	-	100	nA	$V_{CE} = 200\text{V}$
Collector-Emitter breakdown voltage	BV_{CEO}	350	-	-	V	$I_C = 0.1\text{mA}$
Emitter-Collector breakdown voltage	BV_{ECO}	7	-	-	V	$I_E = 0.1\text{mA}$
Collector-Emitter capacitance	C_{CE}	-	10	-	pF	$V_{CE} = 0\text{V}, f = 1\text{MHz}$

Transfer Characteristics

Parameter	Symbol	Min.	Typ.*	Max.	Unit	Condition
Current Transfer Ratio	CTR	50	-	600	%	$I_F = 5\text{mA}, V_{CE} = 5\text{V}$
Collector-emitter saturation voltage	$V_{CE(sat)}$	-	-	0.4	V	$I_F = 20\text{mA}, I_C = 1\text{mA}$
Isolation resistance	R_{IO}	10^{11}	-	-	Ω	$V_{IO} = 500\text{Vdc}$
Input-output capacitance	C_{IO}	-	0.6	-	pF	$V_{IO} = 0, f = 1\text{MHz}$
Rise time	t_r	-	4	18	μs	$V_{CE} = 2\text{V},$ $I_C = 2\text{mA}, R_L = 100\Omega$
Fall time	t_f	-	5	18		

* Typical values at $T_a = 25^{\circ}\text{C}$

Typical Performance Curves

Figure 1. Forward Current vs Forward Voltage




Figure 2. Current Transfer Ratio vs Forward Current




Figure 3. Collector Current vs Collector-emitter Voltage




Figure 4. Relative Current Transfer Ratio vs Ambient Temperature






Figure 5. Collector-emitter Saturation Voltage vs Ambient Temperature









Figure 9. Switching Time Test Circuit & Waveforms

4 PIN DIP HIGH VOLTAGE PHOTOTRANSISTOR PHOTOCOUPLER

EL851 series

Order Information

Part Number

EL851Y(Z)-V

Note




- Y = Lead form option (S, S1, M or none)
Z = Tape and reel option (TA, TB, TU, TD or none)
V = VDE safety (optional)

Option	Description	Packing quantity
None	Standard DIP-4	100 units per tube
M	Wide lead bend (0.4 inch spacing)	100 units per tube
S (TA)	Surface mount lead form + TA tape & reel option	1000 units per reel
S (TB)	Surface mount lead form + TB tape & reel option	1000 units per reel
S1 (TA)	Surface mount lead form (low profile) + TA tape & reel option	1000 units per reel
S1 (TB)	Surface mount lead form (low profile) + TB tape & reel option	1000 units per reel
S (TU)	Surface mount lead form + TU tape & reel option	1500 units per reel
S (TD)	Surface mount lead form + TD tape & reel option	1500 units per reel
S1 (TU)	Surface mount lead form (low profile) + TU tape & reel option	1500 units per reel
S1 (TD)	Surface mount lead form (low profile) + TD tape & reel option	1500 units per reel




Package Drawings

(Dimensions in mm)

Standard DIP Type




Option M Type




4 PIN DIP HIGH VOLTAGE PHOTOTRANSISTOR PHOTOCOUPLER

EL851 series


Option S Type



Option S1 Type



Recommended pad layout for surface mount leadform



Device Marking



Notes


EL	denotes Everlight
851	denotes Part Number
Y	denotes 1 digit Year code
WW	denotes 2 digit Week code
V	denotes VDE safety

4 PIN DIP HIGH VOLTAGE PHOTOTRANSISTOR PHOTOCOUPLER


EL851 series

Tape & Reel Packing Specifications


Option TA



Option TB



Tape dimensions





Dimension No.	A	B	Do	D1	E	F
Dimension(mm)	10.4±0.1	4.55±0.1	1.5±0.1	1.5±0.05	1.75±0.1	7.5±0.1
Dimension No.	Po	P1	P2	t	W	K
Dimension(mm)	4.0±0.1	12.0±0.1	2.0±0.1	0.33±0.1	16.0+0.3/ -0.1	4.55±0.1

4 PIN DIP HIGH VOLTAGE PHOTOTRANSISTOR PHOTOCOUPLER


EL851 series

Option TD




Direction of feed from reel

Option TU




Direction of feed from reel

Tape dimensions



Dimension No.	A	B	C	D	E	F
Dimension(mm)	16.00±0.3	7.5±0.1	1.75±0.1	8.0±0.1	2.0±0.1	4.0±0.1
Dimension No.	G	H	I	J	K	
Dimension(mm)	1.5+0.1/-0	10.4±0.1	0.4±0.05	4.55±0.1	5.1±0.1	

Solder Reflow Temperature Profile



DISCLAIMER

1. The specifications in this datasheet may be changed without notice. EVERLIGHT reserves the authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for use as outlined in this datasheet. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in this datasheet.
3. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without the specific consent of EVERLIGHT.