
EVERLIGHT ELECTRONICS CO.,LTD.

Technical Data Sheet
0.56" Dual Digit Displays

ELD-512UBWA/C470



Features :

- Industrial standard size.
- Low power consumption.
- Categorized for luminous intensity.
- Pb free
- The product itself will remain within RoHS compliant version

Descriptions :

- The ELD-512 series is a large 14.22 mm (0.56")high seven segment display designed for viewing distances up to 7 meters.
- These displays provide excellent reliability in bright ambient light.
- These devices are made with white segments and gray surface.

Applications :

- Audio equipment
- Instrument panels
- Digital read out display


PART NO.	Chip	
	Material	Emitted Color
ELD-512UBWA/C470	InGaN/SiC	Blue


BG0308115 50004061

Technical Data Sheet
0.56" Dual Digit Displays


ELD-512UBWA/C470

Package Dimensions





COMMON ANODE
1 CATHODE E D1
2 CATHODE D D1
3 CATHODE C D1
4 CATHODE DP D1
5 CATHODE E D2
6 CATHODE D D2
7 CATHODE G D2
8 CATHODE C D2
9 CATHODE DP D2
10 CATHODE B D2
11 CATHODE A D2
12 CATHODE F D2
13 COMMON ANODE D2
14 COMMON ANODE D1
15 CATHODE B D1
16 CATHODE A D1
17 CATHODE G D1
18 CATHODE F D1



Notes: 1.All dimensions are in millimeters , tolerance is 0.25mm unless otherwise noted.

2.Above specification may be changed without notice.

Supplier will reserve authority on material change for above specification.

Technical Data Sheet

0.56" Dual Digit Displays

ELD-512UBWA/C470

■ Absolute maximum ratings at Ta = 25℃ :

Parameter	Symbol	Rating	Unit
Reverse Voltage	VR	5	V
Forward Current	IF	30	mA
Operating Temperature	Topr	-40 to +85	℃
Storage Temperature	Tstg	-40 to +100	℃
Soldering Temperature *	Tsol	260	℃
Electrostatic Discharge	ESD	1000	V
Power Dissipation	Pd	130	mW

Note: *Soldering time ≦ 5 seconds.


■ Electronic optical characteristics :


Parameter		Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	Per segment	Iv	----	1.0	----	mcd	IF=2mA
			4.0	6.4	----	mcd	IF=10mA
	Per decimal point		----	0.5	----	mcd	IF=2mA
			0.5	1.6	----	mcd	IF=10mA
Peak Wavelength		λ p	----	468	----	mcd	IF=2mA
Dominant Wavelength		λ d	----	470	----	nm	IF=20mA
Spectrum Radiation Bandwidth		△ λ	----	26	----	nm	IF=20mA
Forward Voltage		VF	-----	3.5	4.3	V	IF=20mA
Reverse Current		IR	----	----	100	μA	VR=5V


ELD-512UBWA/C470

■ Typical Electro-Optical Characteristic Curves:

(UB)







Technical Data Sheet
0.56" Dual Digit Displays

ELD-512UBWA/C470

Reliability test items and conditions:

The reliability of products shall be satisfied with items listed below.

Confidence level：97%

LTPD：3%

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Failure Judgment Criteria	Ac/Re
1	Solder Heat	TEMP : 260℃ ± 5 ℃	5 SEC	76 PCS	Iv≦Ivt*0.5 or Vf≧U or Vf≦L	0/1
2	Temperature Cycle	H : +85℃ 30min ∫ 5 min L : -55℃ 30min	50 CYCLE	76 PCS		0/1
3	Thermal Shock	H : +100℃ 5min ∫ 10 sec L : -10℃ 5min	50 CYCLE	76 PCS		0/1
4	High Temperature Storage	TEMP : 100℃	1000 HRS	76 PCS		0/1
5	Low Temperature Storage	TEMP : -55℃	1000 HRS	76 PCS		0/1
6	DC Operating Life	IF = 10 mA	1000 HRS	76 PCS		0/1
7	High Temperature / High Humidity	85℃/85% RH	1000 HRS	76 PCS		0/1

Note： Ivt：The test Iv value of the chip before the reliablility test

Iv：The test value of the chip that has completed the reliablility test

U：Upper Specification Limit

L： Lower Specification Limit


Technical Data Sheet
0.56" Dual Digit Displays

ELD-512UBWA/C470

■ Packing Quantity Specification

1. 20PCS/tube, 54 tubes/box
2. 4Boxes/Carton

Label Form Specification



CPN: Customer's Production Number

P/N : Production Number

QTY: Packing Quantity

CAT: Ranks

HUE: Dominant Wavelength

REF: Reference

LOT No: Lot Number

Reference:Volume label code

Notes :

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
3. These specification sheets include materials protected under copyright of EVERLIGHT corporation. Please don't reproduce or cause anyone to reproduce them without EVERLIGHT' sconsent.

EVERLIGHT ELECTRONICS CO., LTD.
Office: 7c Building ,Lian Hua Port lndustrial District, Lian Hua Shan Bonded Pricessing, Zone Pan Yu, Guang Zhou, China
Tel: (020) 84860913 , 84860914
Fax: (020) 84860600
http://www.everlight.com