

- Package 8 pin DIL
- Frequency range: 20.0 to 50.0kHz; 32.768kHz
- Supply voltage 3.3 or 5.0 Volts
- Frequency stability from ± 1 ppm over -30 to +75°C

DESCRIPTION

EM8T series TCXOs are packaged in a miniature 6 pad ceramic SMD package. With squarewave (CMOS) output, tolerances are available from ± 1.0 ppm over -30° to +75°C. The part has a 0.01 μ F decoupling capacitor built in.

SPECIFICATION

Product Series Code	TCXO: EM8T VCTCXO: VEM8T
Frequency Range:	32.768kHz Standard frequency 20.0kHz to 50.0kHz
Output Waveform:	Squarewave
Initial Calibration Tolerance	
Models with mech. trimmer:	<1.0ppm (at t. 25° $\pm$ 2°C)
Models without trimmer:	<2.0ppm (at t. 25° $\pm$ 2°C)
Operating Temperature Range:	See table
Frequency Stability	
vs. Ageing:	± 1.0 ppm max. first year
vs. Voltage Change:	± 0.3 ppm max. $\pm 5\%$ change
vs. Load Change:	± 0.3 ppm max. $\pm 10\%$ change
vs. Reflow:	± 1 ppm max. for one reflow (Measured after 24 hours)
Supply Voltage:	+3.3 or +5.0Volts (Specify when ordering)
Output Logic Levels:	Logic High: 90% Vdd min. Logic Low: 10% Vdd max.
Rise and Fall Times:	10ns max.
Duty Cycle:	50% $\pm$ 5%
Start-up Time:	2ms typical, 5ms max.
Current Consumption:	See table below
Output Load:	15pF
Storage Temperature:	-55~+125°C

FREQUENCY STABILITY

Frequency Stability (ppm)	± 0.5	± 1.0	± 1.5	± 2.0	± 2.5
Temperature Range (°C)					
0 ~ +50	ASK	✓	✓	✓	✓
-10 ~ +60	x	✓	✓	✓	✓
-20 ~ +70	x	x	✓	✓	✓
-30 ~ +75	x	x	x	✓	✓
-40 ~ +85	x	x	x	x	✓

✓ = available, x = not available, ASK = call Technical Sales


CURRENT CONSUMPTION

Frequency	+3.3 V
32.768kHz	8.0mA
50kHz	12mA

HCMOS 8 pin DIL, kHz Range



EM8T - OUTLINES AND DIMENSIONS



VEM8T VOLTAGE CONTROL SPECIFICATION

Control Voltage:	Standard = +1.5 $\pm$ 1.0Volts for all input voltages. (Contact technical sales if +2.5 $\pm$ 2.0 Volts is required.)
Frequency Deviation:	± 6.0 ppm min.
Slope Polarity:	Positive (increase of control voltage increases output frequency.)
Input Impedance:	10k Ω min.
Modulation Bandwidth:	3.0kHz min. measured at -3dB
Linearity:	10% max.

PART NUMBERING PROCEDURE

Example: **EM8T33-32.768k-2.5/-30+75**

Series Description
TCXO = EM8T
VCTCXO = VEM8T

Supply Voltage
33 = 3.3 VDC
5 = 5.0 VDC

Frequency (kHz)
Stability over OTR ($\pm$ ppm)
Operating Temperature Range (OTR) (°C)
Lower and upper limits.