

MAIN FEATURE

1. High switching current at 16A in small size.
2. 1 N/O contact with a Tungsten pre-make contact.
3. Dielectric Strength up to 5,000VAC.
4. 1 pole 16 A, 1 NO contact
   (W pre-make contact + AgSnO2).
   165 A / 20 ms inrush peak current.
5. Comply with RoHS and REACH regulations.

CONTACT RATING

Load Type	EML (DM)
Rated Load (Resistive)	16A 277VAC
Rated Carrying Current	16A
Max. Allowable Voltage	AC 400V
Max. Allowable Current	16A
Max. Allowable Power Force	4000VA
Contact Material	R (Main) : Ag Alloy, L (Pre-make) : W
Contact Capacity	Tungsten Load: 3000W/230VAC
Contact Form	SPST

APPLICATION

Lamp Control, Audio Equipment, Domestic Appliance and Controlling Equipment…etc.

PERFORMANCE (AT INITIAL VALUE)

- Contact Resistance..... 100 mΩ Max.@1A,6VDC
- Contact Rating(resistive load)
- Operate Time ..... 10 mSec. Max.
- Release Time ..... 5 mSec. Max.
- Dielectric Strength:
  Between Coil & Contact... 5,000VAC at 50/60Hz for one minute
  Between Contacts ..... 1,000VAC at 50/60Hz for one minute
- Surge Strength ..... 10,000V (between coil & contact 1.2x50uSec.)
  Insulation Resistance ..... 100MΩ Min. at 500VDC
- Max. On/Off Switching:
  Electrical ..... 6 Cycles per Minute
  Mechanical ..... 300 Cycles per Minute
- Vibration:
  Destruction ..... 10 to 55 to 10 Hz,0.75 mm single amplitude (1.5mm double amplitude)
  Malfunction ..... 10 to 55 to 10 Hz,0.75 mm single amplitude (1.5mm double amplitude)
- Humidity Range..... 45~85% RH.
- Temperature Range.....-45~+85°C.
- Coil Temperature Rise..... 45°C Max.
- Shock:
  Destruction ..... 1,000 m/S^2
  Malfunction ..... 100 m/S^2
- Life Expectancy:
  Electrical ..... $6x10^4$ Operations at Rated Resistive Load
  $3x10^4$ Operations at Tungsten Load
  Mechanical..... $5x10^6$ Operations at No Load condition
- Weight..... About 12.5 g

ACCESSORIES & SOCKETS

- PI-50BE ..... See Page 171
- PI-50BE/3 ..... See Page 171
- PI-50-0 ..... See Page 173

SAFETY STANDARD & FILE NUMBER

- UL.....E141060

COIL SPECIFICATION (AT 20°C)

Coil Sensitivity	Nominal Voltage (VDC)	Nominal Current (mA)	Coil Resistance (Ω±10%)	Power Consumption (W)	Pull-In Voltage (VDC)	Drop-Out Voltage (VDC)	Maximum Allowable Voltage (VDC)
EML	3	130	23	Abt. 0.40	75% Maximum	10% Minimum	130%
	5	80	63				
	6	67	90				
	9	44	203				
	12	33	360				
	15	27	563				
	18	22	810				
	24	17	1440				
	48	8	5760				
	60	7	9000				

ORDERING INFORMATION

EML - SH - 1 12 D M F

Insulation System:	**Nil:** Standard Class **F:** Class F
Contact Form:	**M:** One Form A
Coil Type:	**D:** Standard DC
Coil Voltage:	**03:** 3V, **05:** 5V, **06:** 6V, **09:** 9V, **12:** 12V, **15:** 15V, **18:** 18V, **24:** 24V, **48:** 48V, **60:** 60V
Number of Pole:	**1:** One Pole
Type of Sealing:	**SS:** RT II Flux Proofed **SH:** RT III Wash Tight
Type:	**EML**

CLASSIFICATION

Model	**EML**
Coil Sensitivity	DC Coil
Contact Form	1A
Flux Proofed	EML-SS-1□□DM
Wash Tight	EML-SH-1□□DM

DIMENSION (≤ 5mm ± 0.2mm, > 5mm ± 0.3mm, the tolerance of PCB thru hole: +0.1mm)

