1-800-383-7323 USA/CAN
www.energizer.com

ENERGIZER EN91

AA



Specifications

NOT INTENDED FOR RETAIL TRADE

Classification:	Alkaline
Chemical System:	Zinc-Manganese Dioxide (Zn/MnO_2) No added mercury or cadmium
Designation:	ANSI-15A, IEC-LR6
Nominal Voltage:	1.5 volts
Nominal IR:	150 to 300 milliohms (fresh)
Operating Temp:	-18°C to 55°C (0°F to 130°F)
Typical Weight:	23.0 grams (0.8 oz.)
Typical Volume:	8.1 cubic centimeters (0.5 cubic inch)
Jacket:	Plastic Label
Shelf Life:	10 years at 21°C
Terminal:	Flat Contact

Industry Standard Dimensions



Milliamp-Hours Capacity

Continuous discharge to 0.8 volts at 21°C



Constant Power Performance

Typical Characteristics (21°C)



Constant Current Performance

Typical Characteristics (21°C)



Important Notice

This data sheet contains typical information specific to products manufactured at the time of its publication.

©Energizer Holdings, Inc. - Contents herein do not constitute a warranty.

Energizer
1-800-383-7323 USA/CAN
www.energizer.com

ENERGIZER EN91

AA

Constant Power Performance

Discharge Characteristics (21°C)



Constant Current Performance

250 mA Discharge (-20°C / 0°C / 21°C)



Industry Standard Tests (21°C)

REMOTE
24 ohm 15 sec/min 8 hrs/day

RADIO
43 ohm 4 hrs/day



PORTABLE LIGHTING
3.3 ohm LIF

TOY
3.9 ohm 1 hr/day



CD/GAMES
250 mA 1 hr/day

TAPE PLAYER
100 mA 1 hr/day



DIGITAL CAMERA
1.5K/.65K mW 2/28 sec - 10x hr

PHOTOFLASH
1K mA 10 sec/min 1 hr/day



Important Notice

This data sheet contains typical information specific to products manufactured at the time of its publication.

©Energizer Holdings, Inc. - Contents herein do not constitute a warranty.