



DESCRIPTION

The ES2AA ~ ES2JA are available in SMA package

FEATURES

- For surface mounted applications
- Low profile package
- Glass Passivated Chip Junction
- Superfast reverse recovery time
- Available in SMA package

ORDERING INFORMATION

Package Type	Part Number
SMA	ES2AA
	ES2BA
	ES2CA
	ES2DA
	ES2EA
	ES2GA
	ES2JA
Note	SPQ: 5,000pcs/Reel
AiT provides all RoHS Compliant Products	

MECHANICAL DATA

Case: SMA

Terminals: Solderable per MIL-STD-750,
Method 2026

Approx. Weight: 0.055g / 0.002oz

PIN DESCRIPTION





ABSOLUTE MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Parameter		Symbol	ES2AA	ES2BA	ES2CA	ES2DA	ES2EA	ES2GA	ES2JA	Unit
Maximum Repetitive Peak Reverse Voltage		V _{RRM}	50	100	150	200	300	400	600	V
Maximum RMS Voltage		V _{RMS}	35	70	105	140	210	280	420	V
Maximum DC Blocking Voltage		V _{DC}	50	100	150	200	300	400	600	V
Maximum Average Forward Rectified Current at T _C =125°C		I _{F(AV)}	2							A
Peak Forward Surge Current 8.3ms Single Half Sine Wave Superimposed on Rated Load		I _{FSM}	50							A
Maximum Forward Voltage at 2A		V _F	1				1.25		1.68	V
Maximum DC Reverse Current at Rated DC Blocking Voltage	T _A =25°C T _A =125°C	I _R	5 100							uA
Typical Junction Capacitance at V _R =4V, f=1MHz		C _J	40							pF
Maximum Reverse Recovery Time ^{NOTE1}		t _{rr}	35							ns
Typical Thermal Resistance ^{NOTE2}		R _{θJA}	60							°C/W
Operating and Storage Temperature Range		T _J , T _{STG}	-55 ~150							°C

NOTE1: Measured with $I_F = 0.5\text{A}$, $I_R = 1\text{A}$, $t_{rr} = 0.25\text{A}$

NOTE2: P.C.B. mounted with 1.0 X 1.0" (2.54 X 2.54 cm) copper pad areas.



TYPICAL CHARACTERISTICS

Figure. 1 Reverse Recovery Time Characteristic and Test Circuit Diagram





Figure. 2 Maximum Average Forward Current Rating




Figure. 3 Typical Reverse Characteristics






Figure. 4 Typical Forward Characteristics




Figure. 5 Typical Junction Capacitance





Figure. 6 Maximum Non-Repetitive Peak Forward Surge Current







PACKAGE INFORMATION

Dimension in SMA(Unit: mm)

Plastic surface mounted package; 2 leads



The recommended mounting pad size



UNIT		A	D	E	H _E	c	e	g	a
mm	Max	2.2	4.5	2.7	5.2	0.31	1.6	1.5	0.3
	Min	1.9	4.0	2.3	4.7	0.15	1.3	0.9	
mil	Max	87	181	106	205	12	63	59	12
	Min	75	157	91	185	3	51	35	



IMPORTANT NOTICE

AiT Semiconductor Inc. (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Semiconductor Inc.'s integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or severe property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Semiconductor Inc. assumes to no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.