Leiditech


# ESD1285WP

1- Line Uni- directional TVS Diode


## Features

- Ultra low leakage: nA level
- Operating voltage: 11V
- Low clamping voltage
- Complies with following standards:
  – IEC 61000-4-2 (ESD) immunity test
    Air discharge: ±20kV
    Contact discharge: ±8kV
  – IEC61000-4-5 (Lightning) 80A (8/20μs)
  RoHS Compliant

## Dimensions DFN1610-2



## Pin Configuration




## Applications

- USB 2.0 power and data line
- Set-top box and digital TV
- Digital video interface (DVI)
- Notebook Computers
- SIM Ports
- 10/100 Ethernet

## Mechanical Characteristics

- Package: DFN1610-2
- Lead Finish: Lead Free
- UL Flammability Classification Rating 94V-0
- Quantity Per Reel:8,000pcs
- Reel Size:7 inch

## Absolute Maximum Ratings(Tamb=25°C unless otherwise specified)

| Parameter | Symbol | Value | Unit |
|---|---|---|---|
| Peak Pulse Power (8/20μs) | Ppp | 1500 | W |
| ESD per IEC 61000−4−2 (Air) | $V_{ESD}$ | ±20 | Kv |
| ESD per IEC 61000−4−2 (Contact) | | ±8 | |
| Operating Temperature Range | $T_J$ | -55 to +125 | ℃ |
| Storage Temperature Range | $T_{STJ}$ | -55 to +150 | ℃ |



Download from alldatasheet.com

## Electrical Characteristics(TA=25°C unless otherwise specified)

| Part Number | Device Marking | $V_{RWM}$ (V) | $V_{BR}$ (V) | $I_T$ (mA) | $V_C$ @10A | Vc | | $I_R$ μA (Max) | C (Pf) (Typ.) |
|---|---|---|---|---|---|---|---|---|---|
| | | | | | | (Max) | (@A) | | |
| ESD1285WP | 72 | 11 | 13.3 | 1 | 18.5 | 25 | 60 | 50 | 250 |

## Characteristic Curves

**Fig1. 8/20μs Pulse Waveform**





**Fig2. ESD Pulse Waveform (according to IEC 61000-4-2)**







**Fig3. Power Derating Curve**







Download from alldatasheet.com

## DFN1610-2 Package Outline Drawing




| SYM | DIMENSIONS | | | | | |
|---|---|---|---|---|---|---|
| | MILLIMETERS | | | INCHES | | |
| | MIN | NOM | MAX | MIN | NOM | MAX |
| A | 0.45 | 0.50 | 0.55 | 0.018 | 0.020 | 0.022 |
| A1 | 0.00 | 0.02 | 0.05 | 0.000 | 0.001 | 0.002 |
| b | 0.75 | 0.80 | 0.85 | 0.030 | 0.032 | 0.034 |
| c | 0.10 | 0.15 | 0.20 | 0.004 | 0.006 | 0.008 |
| D | 1.55 | 1.60 | 1.65 | 0.062 | 0.064 | 0.066 |
| e | 1.10 BSC | | | 0.044 BSC | | |
| E | 0.95 | 1.00 | 1.05 | 0.038 | 0.040 | 0.042 |
| L | 0.35 | 0.40 | 0.45 | 0.014 | 0.016 | 0.018 |
| h | 0.15 | 0.20 | 0.25 | 0.006 | 0.008 | 0.010 |

## Suggested Land Pattern




| SYM | DIMENSIONS | |
|---|---|---|
| | MILLIMETERS | INCHES |
| X | 1.00 | 0.040 |
| Y1 | 0.62 | 0.025 |
| Y2 | 0.60 | 0.024 |
| Y3 | 1.22 | 0.049 |
| Z | 1.85 | 0.074 |

Shanghai Leiditech Electronic Co.,Ltd
Email: sale1@leiditech.com
Tel : +86- 021 50828806
Fax : +86- 021 50477059



Download from alldatasheet.com