

➔ Specifications

Parameter		Specification
Center Wavelength		1310 nm & 1550 nm
Bandwidth		± 40 nm
Attenuation Range		1-30 dB
Attenuation Tolerance		± 10%
Return Loss		≥ 50 dB
Fiber Type		SMF 28e
Operating Temperature		- 40° C ~ + 85° C
Storage Temperature		- 40° C ~ + 85° C
Package Dimensions	Light Duty (B)	3.0 mm (Φ) x 55 mm (L)
	Medium Duty (L)	3.0 mm (Φ) x 60 mm (L)
	Heavy Duty (K, R)	100.0 mm x 12.0 mm x 8.0 mm

Note1: All values specified are without connectors.

Note2: Higher performance specifications available upon request.

➔ Ordering Information

F	A				
					
		Attenuation	Pigtail Length	Pigtail Style (=Package style)	Connector
		XX: xx dB	1: 1 meter	B: bare fiber	0: None 7: LC/UPC
		03: 3 dB	2: 2 meter	L: 900 μm loose tube	1: FC/PC 8: LC/SPC
		10: 10 dB	S: Special	K: 2mm cable	2: FC/APC 9: Special
				R: 3mm cable	3: SC/ PC A: FC/UPC
					4: SC/APC B: SC/UPC
					5: FC/SPC C: ST
					6: SC/SPC