RECTRON
SEMICONDUCTOR
TECHNICAL SPECIFICATION

# FFM101L THRU FFM107L

## SURFACE MOUNT GLASS PASSIVATED FAST RECOVERY SILICON RECTIFIER

### VOLTAGE RANGE 50 to 1000 Volts CURRENT 1.0 Ampere

NEW RELEASE

### FEATURES


* Glass passivated device
* Ideal for surface mounted applications
* Low leakage current
* Metallurgically bonded construction
* Mounting position: Any
* Weight: 0.057 gram

### MECHANICAL DATA

* Epoxy : Device has UL flammability classification 94V-0



SMAL




Dimensions in inches and (millimeters)

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

**MAXIMUM RATINGS** (@ TA=25 °C unless otherwise noted)

| RATINGS | SYMBOL | FFM101L | FFM102L | FFM103L | FFM104L | FFM105L | FFM106L | FFM107L | UNITS |
|---|---|---|---|---|---|---|---|---|---|
| Maximum Recurrent Peak Reverse Voltage | $V_{RRM}$ | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | Volts |
| Maximum RMS Voltage | $V_{RMS}$ | 35 | 70 | 140 | 280 | 420 | 560 | 700 | Volts |
| Maximum DC Blocking Voltage | $V_{DC}$ | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | Volts |
| Maximum Average Forward Rectified Current at $T_A$ = 55°C | $I_O$ | 1.0 | | | | | | | Amps |
| Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC method) | $I_{FSM}$ | 30 | | | | | | | Amps |
| Typical Thermal Resistance (Note 4) | $R_{\theta JA}$ | 70 | | | | | | | °C/W |
| | $R_{\theta JL}$ | 30 | | | | | | | |
| Typical Junction Capacitance (Note 2) | $C_J$ | 15 | | | | | | | pF |
| Operating and Storage Temperature Range | $T_J$, $T_{STG}$ | -55 to + 150 | | | | | | | °C |

**ELECTRICAL CHARACTERISTICS**(@TA=25 °C unless otherwise noted)

| CHARACTERISTICS | | SYMBOL | FFM101L | FFM102L | FFM103L | FFM104L | FFM105L | FFM106L | FFM107L | UNITS |
|---|---|---|---|---|---|---|---|---|---|---|
| Maximum Instantaneous Forward Voltage at 1.0A DC | | $V_F$ | 1.3 | | | | | | | Volts |
| Maximum DC Reverse Current at Rated DC Blocking Voltage | @$T_A$ = 25°C | $I_R$ | 2.0 | | | | | | | µAmps |
| | @$T_A$ = 100°C | | 100 | | | | | | | |
| Maximum Reverse Recovery Time (Note 1) | | trr | 150 | | | | 250 | 500 | | nSec |

NOTES : 1. Reverse Recovery Test Conditions: IF = 0.5A, IR = -1.0A, IRR = -0.25A


2. Measured at 1 MHz and applied reverse voltage of 4.0 volts

3. "Fully ROHS compliant", "100% Sn plating (Pb-free)".

4. Thermal Resistance : Mounted on PCB.

2006-12

# RATING AND CHARACTERISTICS CURVES ( FFM101L THRU FFM107L )




NOTES: 1 Rise Time = 7ns max. Input Impedance = 1 megohm. 22pF.

2. Rise Time = 10ns max. Source Impedance = 50 ohms.

**FIG.1 TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC**





**FIG.2 TYPICAL FORWARD CURRENT DERATING CURVE**





**FIG.3 TYPICAL REVERSE CHARACTERISTICS**

# RATING AND CHARACTERISTICS CURVES ( FFM101L THRU FFM107L )





FIG.4 TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS





FIG.5 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT






FIG.6 TYPICAL JUNCTION CAPACITANCE

## Mounting Pad Layout




Dimensions in inches and (millimeters)

# DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.