


**Is Now Part of**




**ON Semiconductor®**

**To learn more about ON Semiconductor, please visit our website at**
**www.onsemi.com**

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild_questions@onsemi.com.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

May 2014

# FGH40T65SHDF

## 650 V, 40 A Field Stop Trench IGBT

### Features


- Maximum Junction Temperature : $T_J$ = 175°C
- Positive Temperaure Co-efficient for Easy Parallel Operating
- High Current Capability
- Low Saturation Voltage: $V_{CE(sat)}$ = 1.45 V ( Typ.) @ $I_C$ = 40 A
- 100% of the Parts tested for $I_{LM}$(1)
- High Input Impedance
- Fast Switching
- Tighten Parameter Distribution
- RoHS Compliant


### General Description

Using novel field stop IGBT technology, Fairchild's new series of field stop 3rd generation IGBTs offer superior conduction and switching performance and easy parallel operation. This device is well suited for the resonant or soft switching application such as induction heating and MWO.

### Applications

- Induction Heating, MWO




### Absolute Maximum Ratings

| Symbol | Description | | FGH40T65SHDF_F155 | Unit |
|---|---|---|---|---|
| $V_{CES}$ | Collector to Emitter Voltage | | 650 | V |
| $V_{GES}$ | Gate to Emitter Voltage | | ± 20 | V |
| | Transient Gate to Emitter Voltage | | ± 30 | V |
| $I_C$ | Collector Current | @ $T_C$ = 25°C | 80 | A |
| | Collector Current | @ $T_C$ = 100°C | 40 | A |
| $I_{LM}$ (1) | Pulsed Collector Current | @ $T_C$ = 25°C | 120 | A |
| $I_{CM}$ (2) | Pulsed Collector Current | | 120 | A |
| $I_F$ | Diode Forward Current | @ $T_C$ = 25°C | 40 | A |
| | Diode Forward Current | @ $T_C$ = 100°C | 20 | A |
| $I_{FM}$ | Pulsed Diode Maximum Forward Current | | 60 | A |
| $P_D$ | Maximum Power Dissipation | @ $T_C$ = 25°C | 268 | W |
| | Maximum Power Dissipation | @ $T_C$ = 100°C | 134 | W |
| $T_J$ | Operating Junction Temperature | | -55 to +175 | °C |
| $T_{stg}$ | Storage Temperature Range | | -55 to +175 | °C |
| $T_L$ | Maximum Lead Temp. for soldering Purposes, 1/8" from case for 5 seconds | | 300 | °C |

**Notes:**
1. $V_{CC}$ = 400 V, $V_{GE}$ = 15 V, $I_C$ = 120 A, $R_G$ = 30 Ω, Inductive Load
2. Repetitive rating: Pulse width limited by max. junction temperature

©2014 Fairchild Semiconductor Corporation

## Thermal Characteristics

| Symbol | Parameter | FGH40T65SHDF_F155 | Unit |
|---|---|---|---|
| $R_{\theta JC}$ (IGBT) | Thermal Resistance, Junction to Case, Max. | 0.56 | °C/W |
| $R_{\theta JC}$ (Diode) | Thermal Resistance, Junction to Case, Max. | 1.75 | °C/W |
| $R_{\theta JA}$ | Thermal Resistance, Junction to Ambient, Max. | 40 | °C/W |

## Package Marking and Ordering Information

| Device Marking | Device | Package | Reel Size | Tape Width | Qty per Tube |
|---|---|---|---|---|---|
| FGH40T65SHDF | FGH40T65SHDF_F155 | TO-247 G03 | - | - | 30 |

## Electrical Characteristics of the IGBT $T_C$ = 25°C unless otherwise noted

| Symbol | Parameter | Test Conditions | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|---|
| **Off Characteristics** | | | | | | |
| $BV_{CES}$ | Collector to Emitter Breakdown Voltage | $V_{GE}$ = 0 V, $I_C$ = 1 mA | 650 | - | - | V |
| $\frac{\Delta BV_{CES}}{\Delta T_J}$ | Temperature Coefficient of Breakdown Voltage | $V_{GE}$ = 0 V, $I_C$ = 1 mA | - | 0.6 | - | V/°C |
| $I_{CES}$ | Collector Cut-Off Current | $V_{CE}$ = $V_{CES}$, $V_{GE}$ = 0 V | - | - | 250 | μA |
| $I_{GES}$ | G-E Leakage Current | $V_{GE}$ = $V_{GES}$, $V_{CE}$ = 0 V | - | - | ±400 | nA |
| **On Characteristics** | | | | | | |
| $V_{GE(th)}$ | G-E Threshold Voltage | $I_C$ = 40 mA, $V_{CE}$ = $V_{GE}$ | 3.5 | 5.5 | 7.5 | V |
| $V_{CE(sat)}$ | Collector to Emitter Saturation Voltage | $I_C$ = 40 A, $V_{GE}$ = 15 V | - | 1.45 | 1.81 | V |
| | | $I_C$ = 40 A, $V_{GE}$ = 15 V, $T_C$ = 175°C | - | 1.8 | - | V |
| **Dynamic Characteristics** | | | | | | |
| $C_{ies}$ | Input Capacitance | $V_{CE}$ = 30 V, $V_{GE}$ = 0 V, f = 1 MHz | - | 1982 | - | pF |
| $C_{oes}$ | Output Capacitance | | - | 70 | - | pF |
| $C_{res}$ | Reverse Transfer Capacitance | | - | 25 | - | pF |
| **Switching Characteristics** | | | | | | |
| $T_{d(on)}$ | Turn-On Delay Time | $V_{CC}$ = 400 V, $I_C$ = 40 A, $R_G$ = 6 Ω, $V_{GE}$ = 15 V, Inductive Load, $T_C$ = 25°C | - | 18 | - | ns |
| $T_r$ | Rise Time | | - | 27 | - | ns |
| $T_{d(off)}$ | Turn-Off Delay Time | | - | 64 | - | ns |
| $T_f$ | Fall Time | | - | 3 | - | ns |
| $E_{on}$ | Turn-On Switching Loss | | - | 1.22 | - | mJ |
| $E_{off}$ | Turn-Off Switching Loss | | - | 0.44 | - | mJ |
| $E_{ts}$ | Total Switching Loss | | - | 1.66 | - | mJ |
| $T_{d(on)}$ | Turn-On Delay Time | $V_{CC}$ = 400 V, $I_C$ = 40 A, $R_G$ = 6 Ω, $V_{GE}$ = 15 V, Inductive Load, $T_C$ = 175°C | - | 18 | - | ns |
| $T_r$ | Rise Time | | - | 31 | - | ns |
| $T_{d(off)}$ | Turn-Off Delay Time | | - | 70 | - | ns |
| $T_f$ | Fall Time | | - | 56 | - | ns |
| $E_{on}$ | Turn-On Switching Loss | | - | 1.78 | - | mJ |
| $E_{off}$ | Turn-Off Switching Loss | | - | 0.78 | - | mJ |
| $E_{ts}$ | Total Switching Loss | | - | 2.56 | - | mJ |

©2014 Fairchild Semiconductor Corporation

## Electrical Characteristics of the IGBT (Continued)

| Symbol | Parameter | Test Conditions | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|---|
| $Q_g$ | Total Gate Charge | $V_{CE}$ = 400 V, $I_C$ = 40 A, $V_{GE}$ = 15 V | - | 68 | - | nC |
| $Q_{ge}$ | Gate to Emitter Charge | | - | 12 | - | nC |
| $Q_{gc}$ | Gate to Collector Charge | | - | 25 | - | nC |

## Electrical Characteristics of the Diode $T_C$ = 25°C unless otherwise noted

| Symbol | Parameter | Test Conditions | | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|---|---|
| $V_{FM}$ | Diode Forward Voltage | $I_F$ = 20 A | $T_C$ = 25°C | - | 1.5 | 1.95 | V |
| | | | $T_C$ = 175°C | - | 1.37 | - | |
| $E_{rec}$ | Reverse Recovery Energy | $I_F$ = 20 A, $dI_F/dt$ = 200 A/μs | $T_C$ = 175°C | - | 153 | - | μJ |
| $T_{rr}$ | Diode Reverse Recovery Time | | $T_C$ = 25°C | - | 101 | - | ns |
| | | | $T_C$ = 175°C | - | 238 | - | |
| $Q_{rr}$ | Diode Reverse Recovery Charge | | $T_C$ = 25°C | - | 343 | - | nC |
| | | | $T_C$ = 175°C | - | 1493 | - | |

## Typical Performance Characteristics

**Figure 1. Typical Output Characteristics**





**Figure 2. Typical Output Characteristics**





**Figure 3. Typical Saturation Voltage Characteristics**





**Figure 4. Saturation Voltage vs. Case Temperature at Variant Current Level**





**Figure 5. Saturation Voltage vs. $V_{GE}$**






**Figure 6. Saturation Voltage vs. $V_{GE}$**



## Typical Performance Characteristics

**Figure 7. Capacitance Characteristics**





**Figure 8. Gate charge Characteristics**





**Figure 9. Turn-on Characteristics vs. Gate Resistance**





**Figure 10. Turn-off Characteristics vs. Gate Resistance**





**Figure 11. Switching Loss vs. Gate Resistance**






**Figure 12. Turn-on Characteristics vs. Collector Current**



## Typical Performance Characteristics

**Figure 13. Turn-off Characteristics vs. Collector Current**





**Figure 14. Switching Loss vs. Collector Current**





**Figure 15. Load Current Vs. Frequency**





**Figure 16. SOA Characteristics**





**Figure 17. Forward Characteristics**






**Figure 18. Reverse Recovery Current**



## Typical Performance Characteristics

**Figure 19. Reverse Recovery Time**





**Figure 20. Stored Charge**





**Figure 21. Transient Thermal Impedance of IGBT**






**Figure 22. Transient Thermal Impedance of Diode**



## Mechanical Dimensions





**Figure 23. TO-247 3L - TO-247,MOLDED,3 LEADS,JEDEC AB LONG LEADS**

*Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.*

*Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:*

*http://www.fairchildsemi.com/package/packageDetails.html?id=PN_TO247-0A3*

**TRADEMARKS**

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

AccuPower™
AX-CAP®*
BitSiC™
Build it Now™
CorePLUS™
CorePOWER™
*CROSSVOLT*™
CTL™
Current Transfer Logic™
DEUXPEED®
Dual Cool™
EcoSPARK®
EfficentMax™
ESBC™
Fairchild®
Fairchild Semiconductor®
FACT Quiet Series™
FACT®
FAST®
FastvCore™
FETBench™
FPS™
F-PFS™
FRFET®
Global Power Resource℠
GreenBridge™
Green FPS™
Green FPS™ e-Series™
G*max*™
GTO™
IntelliMAX™
ISOPLANAR™
Marking Small Speakers Sound Louder and Better™
MegaBuck™
MICROCOUPLER™
MicroFET™
MicroPak™
MicroPak2™
MillerDrive™
MotionMax™
mWSaver®
OptoHiT™
OPTOLOGIC®
OPTOPLANAR®
PowerTrench®
PowerXS™
Programmable Active Droop™
QFET®
QS™
Quiet Series™
RapidConfigure™
™
Saving our world, 1mW/W/kW at a time™
SignalWise™
SmartMax™
SMART START™
Solutions for Your Success™
SPM®
STEALTH™
SuperFET®
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SupreMOS®
SyncFET™
Sync-Lock™
SYSTEM GENERAL ®*
TinyBoost®
TinyBuck®
TinyCalc™
TinyLogic®
TINYOPTO™
TinyPower™
TinyPWM™
TinyWire™
TranSiC™
TriFault Detect™
TRUECURRENT®*
µSerDes™
UHC®
Ultra FRFET™
UniFET™
VCX™
VisualMax™
VoltagePlus™
XS™

*Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

**DISCLAIMER**

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

**LIFE SUPPORT POLICY**

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used here in:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

**ANTI-COUNTERFEITING POLICY**

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.Fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufactures of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed application, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handing and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address and warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

**PRODUCT STATUS DEFINITIONS**

**Definition of Terms**

| Datasheet Identification | Product Status | Definition |
|---|---|---|
| Advance Information | Formative / In Design | Datasheet contains the design specifications for product development. Specifications may change in any manner without notice. |
| Preliminary | First Production | Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production | Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design. |
| Obsolete | Not In Production | Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only. |

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT**:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
**Phone**: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
**Fax**: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
**Email**: orderlit@onsemi.com

**N. American Technical Support**: 800−282−9855 Toll Free USA/Canada
**Europe, Middle East and Africa Technical Support:**
Phone: 421 33 790 2910
**Japan Customer Focus Center**
Phone: 81−3−5817−1050

**ON Semiconductor Website**: **www.onsemi.com**

**Order Literature**: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative