


**Is Now Part of**




**ON Semiconductor®**

**To learn more about ON Semiconductor, please visit our website at**
**www.onsemi.com**

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild_questions@onsemi.com.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

June 2017

ON Semiconductor®

# FGH40T65SQD

## 650 V, 40 A Field Stop Trench IGBT

### Features


- Maximum Junction Temperature: $T_J$ = 175°C
- Positive Temperature Co-efficient for Easy Parallel Operating
- High Current Capability
- Low Saturation Voltage: $V_{CE(sat)}$ = 1.6 V (Typ.) @ $I_C$ = 40 A
- 100% of the Parts tested for $I_{LM}$(1)
- High Input Impedance
- Fast Switching
- Tighten Parameter Distribution
- RoHS Compliant


### General Description

Using novel field stop IGBT technology, ON semiconductor's new series of field stop 4th generation IGBTs offer the optimum performance for solar inverter, UPS, welder, telecom, ESS and PFC applications where low conduction and switching losses are essential.

### Applications

- Solar Inverter, UPS, Welder, Telecom, ESS, PFC




### Absolute Maximum Ratings

| Symbol | Description | | FGH40T65SQD_F155 (1) | Unit |
|---|---|---|---|---|
| $V_{CES}$ | Collector to Emitter Voltage | | 650 | V |
| $V_{GES}$ | Gate to Emitter Voltage | | ± 20 | V |
| | Transient Gate to Emitter Voltage | | ± 30 | V |
| $I_C$ | Collector Current | @ $T_C$ = 25°C | 80 | A |
| | Collector Current | @ $T_C$ = 100°C | 40 | A |
| $I_{LM}$ (2) | Pulsed Collector Current | @ $T_C$ = 25°C | 160 | A |
| $I_{CM}$ (3) | Pulsed Collector Current | | 160 | A |
| $I_F$ | Diode Forward Current | @ $T_C$ = 25°C | 40 | A |
| | Diode Forward Current | @ $T_C$ = 100°C | 20 | A |
| $I_{FM}$ (3) | Pulsed Diode Maximum Forward Current | | 160 | A |
| $P_D$ | Maximum Power Dissipation | @ $T_C$ = 25°C | 238 | W |
| | Maximum Power Dissipation | @ $T_C$ = 100°C | 119 | W |
| $T_J$ | Operating Junction Temperature | | -55 to +175 | °C |
| $T_{stg}$ | Storage Temperature Range | | -55 to +175 | °C |
| $T_L$ | Maximum Lead Temp. for soldering Purposes, 1/8" from case for 5 seconds | | 300 | °C |

**Notes:**
1. Due to system integration constraints between Fairchild and ON semiconductor, as of November 1, 2017 any product part number with a underscore will be replaced with a dash. This is a notification.
2. $V_{CC}$ = 400 V, $V_{GE}$ = 15 V, $I_C$ = 160 A, $R_G$ = 22 Ω , Inductive Load
3. Repetitive rating: Pulse width limited by max. junction temperature

## Thermal Characteristics

| Symbol | Parameter | FGH40T65SQD_F155 | Unit |
|---|---|---|---|
| $R_{\theta JC}$ (IGBT) | Thermal Resistance, Junction to Case, Max. | 0.63 | °C/W |
| $R_{\theta JC}$ (Diode) | Thermal Resistance, Junction to Case, Max. | 1.71 | °C/W |
| $R_{\theta JA}$ | Thermal Resistance, Junction to Ambient, Max. | 40 | °C/W |

## Package Marking and Ordering Information

| Device Marking | Device | Package | Reel Size | Tape Width | Qty per Tube |
|---|---|---|---|---|---|
| FGH40T65SQD | FGH40T65SQD_F155 | TO-247 G03 | - | - | 30 |

## Electrical Characteristics of the IGBT $T_C$ = 25°C unless otherwise noted

| Symbol | Parameter | Test Conditions | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|---|
| **Off Characteristics** | | | | | | |
| $BV_{CES}$ | Collector to Emitter Breakdown Voltage | $V_{GE}$ = 0 V, $I_C$ = 1 mA | 650 | - | - | V |
| $\Delta BV_{CES} / \Delta T_J$ | Temperature Coefficient of Breakdown Voltage | $V_{GE}$ = 0 V, $I_C$ = 1 mA | - | 0.6 | - | V/°C |
| $I_{CES}$ | Collector Cut-Off Current | $V_{CE}$ = $V_{CES}$, $V_{GE}$ = 0 V | - | - | 250 | μA |
| $I_{GES}$ | G-E Leakage Current | $V_{GE}$ = $V_{GES}$, $V_{CE}$ = 0 V | - | - | ±400 | nA |
| **On Characteristics** | | | | | | |
| $V_{GE(th)}$ | G-E Threshold Voltage | $I_C$ = 40 mA, $V_{CE}$ = $V_{GE}$ | 2.6 | 4.5 | 6.4 | V |
| $V_{CE(sat)}$ | Collector to Emitter Saturation Voltage | $I_C$ = 40 A, $V_{GE}$ = 15 V | - | 1.6 | 2.1 | V |
| | | $I_C$ = 40 A, $V_{GE}$ = 15 V, $T_C$ = 175°C | - | 1.92 | - | V |
| **Dynamic Characteristics** | | | | | | |
| $C_{ies}$ | Input Capacitance | $V_{CE}$ = 30 V, $V_{GE}$ = 0 V, f = 1 MHz | - | 2620 | - | pF |
| $C_{oes}$ | Output Capacitance | | - | 60 | - | pF |
| $C_{res}$ | Reverse Transfer Capacitance | | - | 9 | - | pF |
| **Switching Characteristics** | | | | | | |
| $T_{d(on)}$ | Turn-On Delay Time | $V_{CC}$ = 400 V, $I_C$ = 10 A, $R_G$ = 6 Ω, $V_{GE}$ = 15 V, Inductive Load, $T_C$ = 25°C | - | 16.4 | - | ns |
| $T_r$ | Rise Time | | - | 4.8 | - | ns |
| $T_{d(off)}$ | Turn-Off Delay Time | | - | 86.4 | - | ns |
| $T_f$ | Fall Time | | - | 8.8 | - | ns |
| $E_{on}$ | Turn-On Switching Loss | | - | 138 | - | μJ |
| $E_{off}$ | Turn-Off Switching Loss | | - | 52 | - | μJ |
| $E_{ts}$ | Total Switching Loss | | - | 190 | - | μJ |
| $T_{d(on)}$ | Turn-On Delay Time | $V_{CC}$ = 400 V, $I_C$ = 20 A, $R_G$ = 6 Ω, $V_{GE}$ = 15 V, Inductive Load, $T_C$ = 25°C | - | 17.6 | - | ns |
| $T_r$ | Rise Time | | - | 9.6 | - | ns |
| $T_{d(off)}$ | Turn-Off Delay Time | | - | 80 | - | ns |
| $T_f$ | Fall Time | | - | 8.8 | - | ns |
| $E_{on}$ | Turn-On Switching Loss | | - | 329 | - | μJ |
| $E_{off}$ | Turn-Off Switching Loss | | - | 84 | - | μJ |
| $E_{ts}$ | Total Switching Loss | | - | 413 | - | μJ |

## Electrical Characteristics of the IGBT (Continued)


| Symbol | Parameter | Test Conditions | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|---|
| $T_{d(on)}$ | Turn-On Delay Time | $V_{CC}$ = 400 V, $I_C$ = 10 A, $R_G$ = 6 Ω, $V_{GE}$ = 15 V, Inductive Load, $T_C$ = 175°C | - | 14.4 | - | ns |
| $T_r$ | Rise Time | | - | 6.4 | - | ns |
| $T_{d(off)}$ | Turn-Off Delay Time | | - | 99.2 | - | ns |
| $T_f$ | Fall Time | | - | 8 | - | ns |
| $E_{on}$ | Turn-On Switching Loss | | - | 269 | - | μJ |
| $E_{off}$ | Turn-Off Switching Loss | | - | 132 | - | μJ |
| $E_{ts}$ | Total Switching Loss | | - | 401 | - | μJ |
| $T_{d(on)}$ | Turn-On Delay Time | $V_{CC}$ = 400 V, $I_C$ = 20 A, $R_G$ = 6 Ω, $V_{GE}$ = 15 V, Inductive Load, $T_C$ = 175°C | - | 16 | - | ns |
| $T_r$ | Rise Time | | - | 11.2 | - | ns |
| $T_{d(off)}$ | Turn-Off Delay Time | | - | 91.2 | - | ns |
| $T_f$ | Fall Time | | - | 8 | - | ns |
| $E_{on}$ | Turn-On Switching Loss | | - | 581 | - | μJ |
| $E_{off}$ | Turn-Off Switching Loss | | - | 237 | - | μJ |
| $E_{ts}$ | Total Switching Loss | | - | 818 | - | μJ |
| $Q_g$ | Total Gate Charge | $V_{CE}$ = 400 V, $I_C$ = 40 A, $V_{GE}$ = 15 V | - | 80 | - | nC |
| $Q_{ge}$ | Gate to Emitter Charge | | - | 15 | - | nC |
| $Q_{gc}$ | Gate to Collector Charge | | - | 20 | - | nC |

## Electrical Characteristics of the Diode $T_C$ = 25°C unless otherwise noted


| Symbol | Parameter | Test Conditions | | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|---|---|
| $V_{FM}$ | Diode Forward Voltage | $I_F$ = 20 A | $T_C$ = 25°C | - | 2.2 | 2.8 | V |
| | | | $T_C$ = 175°C | - | 1.94 | - | |
| $E_{rec}$ | Reverse Recovery Energy | $I_F$ = 20 A, $dI_F/dt$ = 200 A/μs | $T_C$ = 175°C | - | 50 | - | μJ |
| $T_{rr}$ | Diode Reverse Recovery Time | | $T_C$ = 25°C | - | 31.8 | - | ns |
| | | | $T_C$ = 175°C | - | 192 | - | |
| $Q_{rr}$ | Diode Reverse Recovery Charge | | $T_C$ = 25°C | - | 50.6 | - | nC |
| | | | $T_C$ = 175°C | - | 699 | - | |

## Typical Performance Characteristics


### Figure 1. Typical Output Characteristics





### Figure 2. Typical Output Characteristics





### Figure 3. Typical Saturation Voltage Characteristics





### Figure 4. Saturation Voltage vs. Case Temperature at Variant Current Level




### Figure 5. Saturation Voltage vs. $V_{GE}$





### Figure 6. Saturation Voltage vs. $V_{GE}$




## Typical Performance Characteristics


### Figure 7. Capacitance Characteristics





### Figure 8. Gate charge Characteristics





### Figure 9. Turn-on Characteristics vs. Gate Resistance





### Figure 10. Turn-off Characteristics vs. Gate Resistance




### Figure 11. Switching Loss vs. Gate Resistance




### Figure 12. Turn-on Characteristics vs. Collector Current



## Typical Performance Characteristics

**Figure 13. Turn-off Characteristics vs. Collector Current**





**Figure 14. Switching Loss vs. Collector Current**





**Figure 15. Load Current Vs. Frequency**





**Figure 16. SOA Characteristics**





**Figure 17. Forward Characteristics**






**Figure 18. Reverse Recovery Current**



## Typical Performance Characteristics

**Figure 19. Reverse Recovery Time**





**Figure 20. Stored Charge**





**Figure 21.Transient Thermal Impedance of IGBT**







**Figure 22.Transient Thermal Impedance of Diode**



## Mechanical Dimensions




NOTES: UNLESS OTHERWISE SPECIFIED.

A. PACKAGE REFERENCE: JEDEC TO-247, ISSUE E, VARIATION AB, DATED JUNE, 2004.
B. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
C. ALL DIMENSIONS ARE IN MILLIMETERS.
D. DRAWING CONFORMS TO ASME Y14.5 - 1994

E. DOES NOT COMPLY JEDEC STANDARD VALUE
F. DRAWING FILENAME: MKT-TO247G03_REV02

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**

Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
**Phone**: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
**Email**: orderlit@onsemi.com

**N. American Technical Support**: 800-282-9855 Toll Free USA/Canada.
**Europe, Middle East and Africa Technical Support**:
Phone: 421 33 790 2910
**Japan Customer Focus Center**
Phone: 81-3-5817-1050

**ON Semiconductor Website**: www.onsemi.com

**Order Literature**: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT**:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
**Phone**: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
**Fax**: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
**Email**: orderlit@onsemi.com

**N. American Technical Support**: 800−282−9855 Toll Free USA/Canada
**Europe, Middle East and Africa Technical Support:**
Phone: 421 33 790 2910
**Japan Customer Focus Center**
Phone: 81−3−5817−1050

**ON Semiconductor Website**: **www.onsemi.com**

**Order Literature**: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative