FAIRCHILD SEMICONDUCTOR®

February 2012

FODM121 Series, FODM124, FODM2701, FODM2705
4-Pin Full Pitch Mini-Flat Package Transistor Output Optocouplers

Features

- More than 5mm creepage/clearance
- Compact 4-pin surface mount package (2.4mm maximum standoff height)
- Current Transfer Ratio in selected groups
  DC Input:
  FODM121: 50–600%
  FODM121A: 100–300%
  FODM121B: 50–150%
  FODM121C: 100–200%
  FODM2701: 50–300%
  FODM124: 100% MIN
  AC Input:
  FODM2705: 50–300%
- Available in tape and reel quantities of 2500
- Applicable to Infrared Ray reflow (260°C max, 10 sec.)
- C-UL, UL and VDE* certifications

*option 'V' required


Applications


- Digital logic inputs
- Microprocessor inputs
- Power supply monitor
- Twisted pair line receiver
- Telephone line receiver


Description

The FODM124, FODM121 series, and FODM2701 consists of a gallium arsenide infrared emitting diode driving a phototransistor in a compact 4-pin mini-flat package. The lead pitch is 2.54mm. The FODM2705 consists of two gallium arsenide infrared emitting diodes connected in inverse parallel for AC operation.


Package Dimensions







Equivalent Circuit
FODM121, FODM124, FODM2701



Equivalent Circuit
FODM2705

Note:
All dimensions are in millimeters.

©2006 Fairchild Semiconductor Corporation

Absolute Maximum Ratings (T_A = 25°C unless otherwise specified)

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Symbol	Parameter		Value	Units
TOTAL PACKAGE				
T_{STG}	Storage Temperature		-40 to +125	°C
T_{OPR}	Operating Temperature		-40 to +110	°C
EMITTER				
$I_{F\ (avg)}$	Continuous Forward Current		50	mA
$I_{F\ (pk)}$	Peak Forward Current (1µs pulse, 300 pps.)		1	A
V_R	Reverse Input Voltage		6	V
P_D	Power Dissipation		70	mW
	Derate linearly (above 25°C)		0.65	mW/°C
DETECTOR				
	Continuous Collector Current		80	mA
P_D	Power Dissipation		150	mW
	Derate linearly (above 25°C)		2.0	mW/°C
V_{CEO}	Collector-Emitter Voltage	FODM2701, FODM2705	40	V
		FODM121 Series, FODM124	80	
V_{ECO}	Emitter-Collector Voltage		7	V

Electrical Characteristics (T_A = 25°C)

Individual Component Characteristics

Symbol	Parameter	Test Conditions	Device	Min.	Typ.*	Max.	Unit
EMITTER							
V_F	Forward Voltage	I_F = 10mA	FODM121 Series, FODM124	1.0		1.3	V
		I_F = 5mA	FODM2701			1.4	
		I_F = ±5mA	FODM2705				
I_R	Reverse Current	V_R = 5V	FODM2701			5	µA
			FODM121 Series				
			FODM124				
DETECTOR							
BV_{CEO}	Breakdown Voltage Collector to Emitter	I_C = 1mA, I_F = 0	FODM121 Series, FODM124	80			V
			FODM2701, FODM2705	40			
BV_{ECO}	Emitter to Collector	I_E = 100µA, I_F = 0	All	7			V
I_{CEO}	Collector Dark Current	V_{CE} = 40V, I_F = 0	All			100	nA
C_{CE}	Capacitance	V_{CE} = 0V, f = 1MHz	All		10		pF

©2006 Fairchild Semiconductor Corporation

Electrical Characteristics (Continued) (T_A = 25°C)

Transfer Characteristics

Symbol	Characteristic	Test Conditions	Device	Min.	Typ.*	Max.	Unit
CTR	DC Current Transfer Ratio	I_F = ±5mA, V_{CE} = 5V	FODM2705	50		300	%
		I_F = 5mA, V_{CE} = 5V	FODM2701	50		300	
		I_F = 5mA, V_{CE} = 5V	FODM121	50		600	
			FODM121A	100		300	
			FODM121B	50		150	
			FODM121C	100		200	
		I_F = 1mA, V_{CE} = 0.5V	FODM124	100		1200	
		I_F = 0.5mA, V_{CE} = 1.5V		50			
	CTR Symmetry	I_F = ±5mA, V_{CE} = 5V	FODM2705	0.3		3.0	
$V_{CE\ (SAT)}$	Saturation Voltage	I_F = ±10mA, I_C = 2mA	FODM2705			0.3	V
		I_F = 10mA, I_C = 2mA	FODM2701			0.3	
		I_F = 8mA, I_C = 2.4mA	FODM121 Series			0.4	
		I_F = 1mA, I_C = 0.5mA	FODM124			0.4	
t_r	Rise Time (Non-Saturated)	I_C = 2mA, V_{CE} = 5V, R_L = 100Ω	All		3		µs
t_f	Fall Time (Non-Saturated)	I_C = 2mA, V_{CE} = 5V, R_L = 100Ω	All		3		µs

Isolation Characteristics

Characteristic	Test Conditions	Symbol	Device	Min.	Typ.*	Max.	Unit
Steady State Isolation Voltage[1]	1 Minute	V_{ISO}	All	3750			VRMS

*All typicals at T_A = 25°C

Note:

1. Steady state isolation voltage, V_{ISO}, is an internal device dielectric breakdown rating. For this test, pins 1 and 2 are common, and pins 3 and 4 are common.

©2006 Fairchild Semiconductor Corporation

Typical Performance Curves

Fig. 1 Forward Current vs. Forward Voltage




Fig. 2 Collector-Emitter Saturation Voltage vs. Ambient Temperature (FODM121/2701/2705)




Fig. 3 Current Transfer Ratio vs. Forward Current (FODM121/2701/2705)




Fig. 4 Collector Current vs. Forward Current (FODM121/2701/2705)




Fig. 5 Collector Current vs. Ambient Temperature (FODM121/2701/2705)





Fig. 6 Collector Current vs. Collector-Emitter Voltage (FODM121/2701/2705)



©2006 Fairchild Semiconductor Corporation

Fig 7. Collector Dark Current vs. Ambient Temperature (FODM121/2701/2705)




Fig. 8 Normalized Current Transfer Ratio vs. Ambient Temperature (FODM121/2701/2705)




Fig. 9 Switching Time vs. Load Resistance (FODM121/2701/2705)




Fig. 10 Collector-Emitter Saturation Voltage vs. Ambient Temperature (FODM124)




Fig. 11 Current Transfer Ratio vs. Forward Current (FODM124)





Fig 12. Collector Current vs. Forward Current (FODM124)



©2006 Fairchild Semiconductor Corporation

Fig 13. Collector Current vs. Ambient Temperature (FODM124)




Fig. 14 Collector Current vs. Collector-Emitter Voltage (FODM124)




Fig. 15 Collector Dark Current vs. Ambient Temperature (FODM124)




Fig. 16 Normalized Current Transfer Ratio vs. Ambient Temperature (FODM124)






Fig. 17 Switching Time vs. Load Resistance (FODM124)



Ordering Information


Option	Description
V	VDE Approved
R2	Tape and Reel (2500 units)
R2V	Tape and Reel (2500 units) and VDE Approved

Marking Information




Definitions	
1	Fairchild logo
2	Device number
3	VDE mark (Note: Only appears on parts ordered with VDE option – See order entry table)
4	One digit year code
5	Two digit work week ranging from ‘01’ to ‘53’
6	Assembly package code

Carrier Tape Specifications




Description	Symbol	2.54 Pitch Dimensions
Tape Width	W	12.00±0.4
Tape Thickness	t	0.35±0.02
Sprocket Hole Pitch	P_0	4.00±0.20
Sprocket Hole Dia.	D_0	1.55±0.20
Sprocket Hole Location	E	1.75±0.20
Pocket Location	F	5.50±0.20
	P_2	2.00±0.20
Pocket Pitch	P	8.00±0.20
Pocket Dimension	A_0	4.75±0.20
	B_0	7.30±0.20
	K_0	2.30±0.20
Pocket Hole Dia.	D_1	1.55±0.20
Cover Tape Width	W_1	9.20
Cover Tape Thickness	d	0.065±0.02
Max. Component Rotation or Tilt		20° max
Devices Per Reel		2500
Reel Diameter		330 mm (13")

Footprint Drawing for PCB Layout



Note:
All dimensions are in mm.

Reflow Profile



Profile Feature	Pb-Free Assembly Profile
Temperature Min. (Tsmin)	150°C
Temperature Max. (Tsmax)	200°C
Time (t_S) from (Tsmin to Tsmax)	60–120 seconds
Ramp-up Rate (t_L to t_P)	3°C/second max.
Liquidous Temperature (T_L)	217°C
Time (t_L) Maintained Above (T_L)	60–150 seconds
Peak Body Package Temperature	260°C +0°C / –5°C
Time (t_P) within 5°C of 260°C	30 seconds
Ramp-down Rate (T_P to T_L)	6°C/second max.
Time 25°C to Peak Temperature	8 minutes max.

FAIRCHILD SEMICONDUCTOR®

TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

2Cool™
AccuPower™
AX-CAP™*
BitSiC™
Build it Now™
CorePLUS™
CorePOWER™
CROSSVOLT™
CTL™
Current Transfer Logic™
DEUXPEED®
Dual Cool™
EcoSPARK®
EfficientMax™
ESBC™
F®
Fairchild®
Fairchild Semiconductor®
FACT Quiet Series™
FACT®
FAST®
FastvCore™
FETBench™
FlashWriter®*
FPS™
F-PFS™
FRFET®
Global Power Resource℠
GreenBridge™
Green FPS™
Green FPS™ e-Series™
G*max*™
GTO™
IntelliMAX™
ISOPLANAR™
Making Small Speakers Sound Louder and Better™
MegaBuck™
MICROCOUPLER™
MicroFET™
MicroPak™
MicroPak2™
MillerDrive™
MotionMax™
Motion-SPM™
mWSaver™
OptoHiT™
OPTOLOGIC®
OPTOPLANAR®
®
PowerTrench®
PowerXS™
Programmable Active Droop™
QFET®
QS™
Quiet Series™
RapidConfigure™
™
Saving our world, 1mW/W/kW at a time™
SignalWise™
SmartMax™
SMART START™
Solutions for Your Success™
SPM®
STEALTH™
SuperFET®
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SupreMOS®
SyncFET™
Sync-Lock™
SYSTEM GENERAL®*
The Power Franchise®
the power franchise
TinyBoost™
TinyBuck™
TinyCalc™
TinyLogic®
TINYOPTO™
TinyPower™
TinyPWM™
TinyWire™
TranSiC™
TriFault Detect™
TRUECURRENT®*
μSerDes™
SerDes
UHC®
Ultra FRFET™
UniFET™
VCX™
VisualMax™
VoltagePlus™
XS™

* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.

Rev. I61

©2006 Fairchild Semiconductor Corporation