

FQB020ADC-007-S_{New}
Product



Sales Region	Worldwide (except Japan)
Power Supply	DC
Series	FQB
Status	Production
Features	MIL-STD-461 MIL-STD-1275 MIL-STD-704 RTCA DO-160
Option	Flanged baseplate Standard screening
Option Lineup	Please refer to here.
Accessories	
Brand	TDK-Lambda



Electrical Characteristics	
Rated Current	20A
Rated Voltage [AC]	
Rated Voltage [DC]	40V
Withstanding Voltage	DC2250V, 60s [terminals - case]
Insulation Resistance (Min.)	
Leakage Current (Max.)	
DC Resistance (Max.)	25mΩ
Common Mode Attenuation (Min.)	30dB
Differential Mode Attenuation (Min.)	50dB

Package Type & Size	
Package / Mounting	Low profile PCB
Length(L)	60.6mm Nom. (2.39in Nom.)
Width(W)	55.9mm Nom. (2.20in Nom.)
Height(H)	12.7mm Nom. (0.50in Nom.)
Weight	100g Typ.

Other	
Terminals	Pin
Operating Temp. Range	-40 to 115°C
Performance	Wide range high attenuation
Function	

Safety Standard

UL60950-1
CSA60950-1
IEC60950-1

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.