


FR201 – FR207P

2A 快速二极管

2A FAST RECOVERY DIODES

型 号 TYPE	最大反向 峰值电压 Maximum Peak Reverse Voltage	最大平均正向电流 Maximum Average Rectified Current @ Half-Wave Resistive Load 60Hz		最大正向浪涌电流 Maximum Forward Peak Surge Current @ 8.3ms Superimposed	最大反向漏电流 Maximum Reverse Current @ PRV @ T _A =25°C	最大正向电压 Maximum Forward Voltage @ T _A =25°C		最大反向 恢复时间 Maximum Reverse Recovery Time	外型尺寸 Package Dimensions
	PRV	I _O @ T _L		I _{FM} (Surge)	I _R	I _{FM}	V _{FM}	T _{rr}	
	V _{PK}	A _{AV}	°C	A _{PK}	μA _{dc}	A _{PK}	V _{PK}	ns	
FR201	50	2.0	75	70	5.0	2.0	1.3	150	DO - 15
FR202	100							150	
FR203	200							150	
FR204	400							150	
FR205	600							250	
FR206	800							500	
FR207	1000							500	
FR207P	1000							250	

 Trr测试条件: I_F = 0.5A, I_R = 1.0A, I_{RR} = 0.25A

 Trr Test Conditions: I_F = 0.5A, I_R = 1.0A, I_{RR} = 0.25A



DO – 15

FR201 – FR207P

2A 快速二极管额定值与特性曲线

RATING & CHARACTERISTIC CURVES OF 2A FAST DIODES

FIG.1–TEST CIRCUIT DIAGRAM AND
REVERSE RECOVERY TIME CHARACTERISTIC



NOTES:1.Rise Time=7ns max.
Input Impedance=1megohm.22pF.
2.Rise Time=10ns max.
Source Impedance=50 ohms.




FIG. 2 – TYPICAL FORWARD
CURRENT DERATING CURVE




FIG. 3 – TYPICAL INSTANTANEOUS
FORWARD CHARACTERISTICS




FIG. 4 – MAXIMUM NON-REPETITIVE
FORWARD SURGE CURRENT




FIG. 5 – TYPICAL JUNCTION CAPACITANCE

