



**Is Now Part of**



**ON Semiconductor®**

**To learn more about ON Semiconductor, please visit our website at**  
**[www.onsemi.com](http://www.onsemi.com)**

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (\_), the underscore (\_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (\_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at [www.onsemi.com](http://www.onsemi.com). Please email any questions regarding the system integration to [Fairchild\\_questions@onsemi.com](mailto:Fairchild_questions@onsemi.com).

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

# FSA266 • NC7WB66

## Low Voltage Dual SPST

## Normally Open Analog Switch or 2-Bit Bus Switch

### General Description

The FSA266 or NC7WB66 is an ultra high-speed (UHS) dual single-pole/single-throw (SPST) analog switch or 2-bit bus switch. The device is fabricated with advanced sub-micron CMOS technology to achieve high speed enable and disable times and low On Resistance over a broad  $V_{CC}$  range. The device is specified to operate over the 1.65 to 5.5V  $V_{CC}$  operating range. The device is organized as a dual switch with independent CMOS compatible switch enable (OE) controls. When OE is HIGH, the switch is ON and Port A is connected to Port B. When OE is LOW, the switch is OPEN and a high-impedance state exists between the two ports. The enable inputs tolerate voltages up to 5.5V independent of the  $V_{CC}$  operating range.

### Features

- Useful in both analog and digital applications
- Space saving US8 surface mount package
- MicroPak™ Pb-Free leadless package
- Typical  $7\Omega$  On Resistance @ 5V  $V_{CC}$
- Broad  $V_{CC}$  operating range: 1.65V to 5.5V
- Rail-to-Rail signal handling
- Power down high impedance control inputs
- Control inputs are overvoltage tolerant
- Control inputs are CMOS compatible
- >300 MHz –3dB bandwidth


### Ordering Code:

| Order Number | Package Number | Product Code Top Mark | Package Description                               | Supplied As               |
|--------------|----------------|-----------------------|---------------------------------------------------|---------------------------|
| FSA266K8X    | MAB08A         | WB66                  | 8-Lead US8, JEDEC MO-187, Variation CA 3.1mm Wide | 3K Units on Tape and Reel |
| FSA266L8X    | MAC08A         | P4                    | Pb-Free 8-Lead MicroPak, 1.6 mm Wide              | 5K Units on Tape and Reel |
| NC7WB66K8X   | MAB08A         | WB66                  | 8-Lead US8, JEDEC MO-187, Variation CA 3.1mm Wide | 3K Units on Tape and Reel |
| NC7WB66L8X   | MAC08A         | P4                    | Pb-Free 8-Lead MicroPak, 1.6 mm Wide              | 5K Units on Tape and Reel |


Pb-Free package per JEDEC J-STD-020B.

MicroPak™ is a trademark of Fairchild Semiconductor Corporation.

Logic Symbol



Analog Symbol



Pin Descriptions



| Pin Names | Description   |
|-----------|---------------|
| A         | Switch Port A |
| B         | Switch Port B |
| OE        | Control Input |

Function Table

| Switch Enable Input (OE) | Function         |
|--------------------------|------------------|
| L                        | Disconnect       |
| H                        | B Connected to A |

H = HIGH Logic Level  
L = LOW Logic Level

Connection Diagrams



**Absolute Maximum Ratings**(Note 1)

|                                                                |                          |
|----------------------------------------------------------------|--------------------------|
| Supply Voltage ( $V_{CC}$ )                                    | -0.5V to +7.0V           |
| DC Switch Voltage ( $V_S$ )                                    | -0.5V to $V_{CC} + 0.5V$ |
| DC Input Voltage ( $V_{IN}$ ) (Note 2)                         | -0.5V to +7.0V           |
| DC Input Diode Current<br>@ ( $I_{IK}$ ) $V_{IN} < 0V$         | -50 mA                   |
| DC Switch Output Current ( $I_{OUT}$ )                         | ±128 mA                  |
| DC $V_{CC}$ or Ground Current ( $I_{CC}/I_{GND}$ )             | ±100 mA                  |
| Storage Temperature Range ( $T_{STG}$ )                        | -65°C to +150°C          |
| Junction Lead Temperature<br>under Bias ( $T_J$ )              | +150°C                   |
| Junction Lead Temperature ( $T_L$ )<br>(Soldering, 10 Seconds) | +260°C                   |
| Power Dissipation ( $P_D$ ) @ +85°C<br>SC70-6                  | 250 mW                   |

**Recommended Operating Conditions** (Note 3)

|                                         |                   |
|-----------------------------------------|-------------------|
| Supply Voltage ( $V_{CC}$ )             | 1.65V to 5.5V     |
| Control Input Voltage ( $V_{IN}$ )      | 0V to 5.5V        |
| Switch Input Voltage ( $V_{IN}$ )       | 0V to $V_{CC}$    |
| Switch Output Voltage ( $V_{OUT}$ )     | 0V to $V_{CC}$    |
| Operating Temperature ( $T_A$ )         | -40°C to +85°C    |
| Input Rise and Fall Time ( $t_r, t_f$ ) |                   |
| Control Input $V_{CC} = 1.65V-2.7V$     | 0 ns/V to 20 ns/V |
| Control Input $V_{CC} = 3.0V-3.6V$      | 0 ns/V to 10 ns/V |
| Control Input $V_{CC} = 4.5V-5.5V$      | 0 ns/V to 5 ns/V  |
| Thermal Resistance ( $\theta_{JA}$ )    | 250°C/W           |

**Note 1:** The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the Electrical Characteristics tables are not guaranteed at the absolute maximum ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

**Note 2:** The input and output negative voltage ratings may be exceeded if the input and output diode current ratings are observed.

**Note 3:** Unused inputs must be held HIGH or LOW. They may not float.

**DC Electrical Characteristics**

| Symbol            | Parameter                                                   | V <sub>CC</sub><br>(V) | T <sub>A</sub> = +25°C                             |     |                 | T <sub>A</sub> = −40°C to +85°C |     | Units           | Conditions                                                    |
|-------------------|-------------------------------------------------------------|------------------------|----------------------------------------------------|-----|-----------------|---------------------------------|-----|-----------------|---------------------------------------------------------------|
|                   |                                                             |                        | Min                                                | Typ | Max             | Min                             | Max |                 |                                                               |
| V <sub>IH</sub>   | HIGH Level Input Voltage                                    | 1.65 to 1.95           | 0.75 V <sub>CC</sub>                               |     |                 | 0.75 V <sub>CC</sub>            |     | V               |                                                               |
|                   |                                                             | 2.3 to 5.5             | 0.7 V <sub>CC</sub>                                |     |                 | 0.7 V <sub>CC</sub>             |     |                 |                                                               |
| V <sub>IL</sub>   | LOW Level Input Voltage                                     | 1.65 to 1.95           | 0.25 V <sub>CC</sub>                               |     |                 | 0.25V <sub>CC</sub>             |     | V               |                                                               |
|                   |                                                             | 2.3 to 5.5             | 0.3 V <sub>CC</sub>                                |     |                 | 0.3 V <sub>CC</sub>             |     |                 |                                                               |
| I <sub>IN</sub>   | Input Leakage Current                                       | 0 to 5.5               | ±0.1                                               |     |                 | ±1.0                            |     | µA              | 0 ≤ V <sub>IN</sub> ≤ 5.5V                                    |
| I <sub>OFF</sub>  | Switch OFF Leakage Current                                  | 1.65 to 5.5            | ±0.1                                               |     |                 | ±1.0                            |     | µA              | 0 ≤ A, B ≤ V <sub>CC</sub>                                    |
| R <sub>ON</sub>   | Switch On Resistance<br>(Note 4)                            | 4.5                    | 6.0                                                |     | 10.0            | 10.0                            |     | Ω               | V <sub>I</sub> = 0V, I <sub>O</sub> = 30 mA                   |
|                   |                                                             |                        | 7.0                                                |     | 13.5            | 13.5                            |     |                 | V <sub>I</sub> = 2.4V, I <sub>O</sub> = −30 mA                |
|                   |                                                             |                        | 6.0                                                |     | 10.0            | 10.0                            |     |                 | V <sub>I</sub> = 4.5V, I <sub>O</sub> = −30 mA                |
|                   |                                                             | 3.0                    | 7.5                                                |     | 15.0            | 15.0                            |     | Ω               | V <sub>I</sub> = 0V, I <sub>O</sub> = 24 mA                   |
|                   |                                                             |                        | 8.5                                                |     | 15.0            | 15.0                            |     |                 | V <sub>I</sub> = 3V, I <sub>O</sub> = −24 mA                  |
|                   |                                                             | 2.3                    | 9.0                                                |     | 20.0            | 20.0                            |     | Ω               | V <sub>I</sub> = 0V, I <sub>O</sub> = 8 mA                    |
|                   |                                                             |                        | 10.5                                               |     | 20.0            | 20.0                            |     |                 | V <sub>I</sub> = 2.3V, I <sub>O</sub> = −8 mA                 |
|                   |                                                             | 1.65                   | 12.5                                               |     | 30.0            | 30.0                            |     | Ω               | V <sub>I</sub> = 0V, I <sub>O</sub> = 4 mA                    |
|                   |                                                             |                        | 17.0                                               |     | 30.0            | 30.0                            |     |                 | V <sub>I</sub> = 1.65V, I <sub>O</sub> = −4 mA                |
|                   |                                                             | I <sub>CC</sub>        | Quiescent Supply Current<br>All Channels ON or OFF | 5.5 | 1.0             |                                 |     | 10.0            |                                                               |
|                   | Analog Signal Range                                         | V <sub>CC</sub>        | 0                                                  |     | V <sub>CC</sub> | 0                               |     | V <sub>CC</sub> | V                                                             |
| RRange            | On Resistance Over<br>Signal Range<br>(Note 4)(Note 5)      | 4.5                    | 8.0                                                |     | 15.0            | 15.0                            |     | Ω               | I <sub>O</sub> = −30 mA, 0 ≤ V <sub>I</sub> ≤ V <sub>CC</sub> |
|                   |                                                             | 3.0                    | 15.0                                               |     | 30.0            | 30.0                            |     |                 | I <sub>O</sub> = −24 mA, 0 ≤ V <sub>I</sub> ≤ V <sub>CC</sub> |
|                   |                                                             | 2.3                    | 45.0                                               |     | 75.0            | 75.0                            |     |                 | I <sub>O</sub> = −8 mA, 0 ≤ V <sub>I</sub> ≤ V <sub>CC</sub>  |
|                   |                                                             | 1.65                   | 150                                                |     | 275             | 275                             |     |                 | I <sub>O</sub> = −4 mA, 0 ≤ V <sub>I</sub> ≤ V <sub>CC</sub>  |
| ΔR <sub>ON</sub>  | On Resistance Match<br>Between Channels<br>(Note 4)(Note 7) | 4.5                    | 0.2                                                |     |                 |                                 |     | Ω               | I <sub>O</sub> = −30 mA, V <sub>I</sub> = 3.15                |
|                   |                                                             | 3.0                    | 0.2                                                |     |                 |                                 |     |                 | I <sub>O</sub> = −24 mA, V <sub>I</sub> = 2.1                 |
|                   |                                                             | 2.3                    | 0.5                                                |     |                 |                                 |     |                 | I <sub>O</sub> = −8 mA, V <sub>I</sub> = 1.6                  |
|                   |                                                             | 1.65                   | 0.6                                                |     |                 |                                 |     |                 | I <sub>O</sub> = −4 mA, V <sub>I</sub> = 1.15                 |
| R <sub>flat</sub> | On Resistance Flatness<br>(Note 4)(Note 5)(Note 6)          | 4.5                    | 2.5                                                |     | 6.0             | 6.0                             |     |                 | I <sub>O</sub> = −30 mA, 0 ≤ V <sub>I</sub> ≤ V <sub>CC</sub> |
|                   |                                                             | 3.0                    | 8.0                                                |     | 17.5            | 17.5                            |     |                 | I <sub>O</sub> = −24 mA, 0 ≤ V <sub>I</sub> ≤ V <sub>CC</sub> |
|                   |                                                             | 2.3                    | 33.0                                               |     | 60.0            | 60.0                            |     |                 | I <sub>O</sub> = −8 mA, 0 ≤ V <sub>I</sub> ≤ V <sub>CC</sub>  |
|                   |                                                             | 1.65                   | 135                                                |     | 250             | 250                             |     |                 | I <sub>O</sub> = −4 mA, 0 ≤ V <sub>I</sub> ≤ V <sub>CC</sub>  |

**Note 4:** Measured by the voltage drop between A and B pins at the indicated current through the switch. On Resistance is determined by the lower of the voltages on the two (A or B) pins.

**Note 5:** Guaranteed by design.

**Note 6:** Flatness is defined as the difference between the minimum and maximum value of ON Resistance over the specified range of conditions.

## DC Electrical Characteristics (Continued)

Note 7:  $\Delta R_{ON} = R_{ON\ max} - R_{ON\ min}$  measured at identical  $V_{CC}$ , temperature and voltage levels.

## AC Electrical Characteristics

| Symbol             | Parameter                                | $V_{CC}$<br>(V) | $T_A = -40^{\circ}\text{C to } +85^{\circ}\text{C}$ |       |      | Units | Conditions                                                                                                              | Figure Number   |
|--------------------|------------------------------------------|-----------------|-----------------------------------------------------|-------|------|-------|-------------------------------------------------------------------------------------------------------------------------|-----------------|
|                    |                                          |                 | Min                                                 | Typ   | Max  |       |                                                                                                                         |                 |
| $t_{PHL}, t_{PLH}$ | Propagation Delay Bus-to-Bus<br>(Note 8) | 4.5 to 5.5      |                                                     | 0.35  | 1.0  | ns    | $V_I = \text{OPEN}$<br>$C_L = 50\text{ pF}, R_U = R_D = 500\Omega$                                                      | Figures<br>1, 2 |
|                    |                                          | 3.0 to 3.6      |                                                     | 0.7   | 1.5  |       |                                                                                                                         |                 |
|                    |                                          | 2.3 to 2.7      |                                                     | 1.1   | 2.5  |       |                                                                                                                         |                 |
|                    |                                          | 1.65 to 1.95    |                                                     | 2.0   | 4.0  |       |                                                                                                                         |                 |
| $t_{PZL}, t_{PZH}$ | Output Enable Time<br>Turn on Time       | 4.5 to 5.5      | 0.8                                                 | 2.0   | 3.2  | ns    | $V_I = 0\text{V}$ for $t_{PZH}$<br>$V_I = 2 \times V_{CC}$ for $t_{PZL}$<br>$C_L = 50\text{ pF}, R_U = R_D = 500\Omega$ | Figures<br>1, 2 |
|                    |                                          | 3.0 to 3.6      | 1.2                                                 | 2.5   | 3.9  |       |                                                                                                                         |                 |
|                    |                                          | 2.3 to 2.7      | 1.5                                                 | 3.2   | 5.6  |       |                                                                                                                         |                 |
|                    |                                          | 1.65 to 1.95    | 2.5                                                 | 5.7   | 10.0 |       |                                                                                                                         |                 |
| $t_{PLZ}, t_{PHZ}$ | Output Disable Time<br>Turn Off Time     | 4.5 to 5.5      | 0.8                                                 | 2.6   | 4.1  | ns    | $V_I = 0\text{V}$ for $t_{PHZ}$<br>$V_I = 2 \times V_{CC}$ for $t_{PLZ}$<br>$C_L = 50\text{ pF}, R_U = R_D = 500\Omega$ | Figures<br>1, 2 |
|                    |                                          | 3.0 to 3.6      | 1.5                                                 | 3.4   | 5.0  |       |                                                                                                                         |                 |
|                    |                                          | 2.3 to 2.7      | 2.0                                                 | 4.2   | 6.9  |       |                                                                                                                         |                 |
|                    |                                          | 1.65 to 1.95    | 3.0                                                 | 6.2   | 10.5 |       |                                                                                                                         |                 |
| Q                  | Charge Injection (Note 9)                | 1.65 to 5.5     |                                                     |       |      | pC    | $C_L = 0.1\text{ nF}, V_{GEN} = 0\text{V},$<br>$R_{GEN} = 0\Omega, f = 1\text{ MHz}$                                    | Figure 3        |
| OIRR               | Off Isolation (Note 10)                  | 1.65 to 5.5     |                                                     | -55.0 |      | dB    | $R_L = 50\Omega, C_L = 5\text{ pF},$<br>$f = 10\text{ MHz}$                                                             | Figure 4        |
| Xtalk              | Crosstalk                                | 1.65 to 5.5     |                                                     | -70.0 |      | dB    | $R_L = 50\Omega, C_L = 5\text{ pF},$<br>$f = 10\text{ MHz}$                                                             | Figure 5        |
| BW                 | -3dB Bandwidth                           | 1.65 to 5.5     |                                                     | >300  |      | MHz   | $R_L = 50\Omega$                                                                                                        | Figure 8        |
| THD                | Total Harmonic Distortion<br>(Note 9)    | 5               |                                                     | .016  |      | %     | $R_L = 600\Omega$<br>$0.5\text{ V}_{P-P}$<br>$f = 600\text{ Hz to } 20\text{ KHz}$                                      |                 |

Note 8: This parameter is guaranteed by design. The switch contributes no propagation delay other than the RC delay of the On Resistance of the switch and the 50 pF load capacitance.


Note 9: Guaranteed by design.

Note 10: Off Isolation =  $20 \log_{10} [V_A/V_{Bn}]$

## Capacitance

| Symbol                  | Parameter                                      | Typ  | Max | Units | Conditions             | Figures  |
|-------------------------|------------------------------------------------|------|-----|-------|------------------------|----------|
| $C_{IN}$                | Control Pin Input Capacitance                  | 2.5  |     | pF    | $V_{CC} = 0\text{V}$   |          |
| $C_{I/O} \text{ (OFF)}$ | Switch Port Off Capacitance                    | 5.0  |     | pF    | $V_{CC} = 5.0\text{V}$ | Figure 6 |
| $C_{I/O} \text{ (ON)}$  | Switch Port Capacitance when Switch is Enabled | 10.0 |     | pF    | $V_{CC} = 5.0\text{V}$ | Figure 7 |

## AC Loading and Waveforms



Input driven by  $50\Omega$  source terminated in  $50\Omega$

$C_L$  includes load and stray capacitance.

Input PRR = 1.0 MHz;  $t_W = 500$  ns

FIGURE 1. AC Test Circuit




FIGURE 2. AC Waveforms





FIGURE 3. Charge Injection Test

## AC Loading and Waveforms (Continued)




FIGURE 4. Off Isolation




FIGURE 5. Crosstalk




FIGURE 6. Channel Off Capacitance




FIGURE 7. Channel On Capacitance





FIGURE 8. Bandwidth

## Tape and Reel Specification

## TAPE FORMAT for US8


| Package Designator | Tape Section       | Number Cavities | Cavity Status | Cover Tape Status |
|--------------------|--------------------|-----------------|---------------|-------------------|
| K8X                | Leader (Start End) | 125 (typ)       | Empty         | Sealed            |
|                    | Carrier            | 250             | Filled        | Sealed            |
|                    | Trailer (Hub End)  | 75 (typ)        | Empty         | Sealed            |

**TAPE DIMENSIONS** inches (millimeters)




## TAPE FORMAT for MicroPak

| Package Designator | Tape Section       | Number Cavities | Cavity Status | Cover Tape Status |
|--------------------|--------------------|-----------------|---------------|-------------------|
| L8X                | Leader (Start End) | 125 (typ)       | Empty         | Sealed            |
|                    | Carrier            | 250             | Filled        | Sealed            |
|                    | Trailer (Hub End)  | 75 (typ)        | Empty         | Sealed            |



**TAPE DIMENSIONS** inches (millimeters)

## REEL DIMENSIONS inches (millimeters)






| Tape Size | A              | B               | C                | D                | N                | W1                                            | W2               | W3                                       |
|-----------|----------------|-----------------|------------------|------------------|------------------|-----------------------------------------------|------------------|------------------------------------------|
| 8 mm      | 7.0<br>(177.8) | 0.059<br>(1.50) | 0.512<br>(13.00) | 0.795<br>(20.20) | 2.165<br>(55.00) | $0.331 + 0.059/-0.000$<br>(8.40 + 1.50/-0.00) | 0.567<br>(14.40) | $W1 + 0.078/-0.039$<br>(W1 + 2.00/-1.00) |

# Physical Dimensions inches (millimeters) unless otherwise noted



## LAND PATTERN RECOMMENDATION



## DETAIL A


## NOTES:

- A. CONFORMS TO JEDEC REGISTRATION MO-187
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
- D. DIMENSIONS AND TOLERANCES PER ANSI Y14.5M, 1982.

MAB08AREVC

8-Lead US8, JEDEC MO-187, Variation CA 3.1mm Wide  
Package Number MAB08A

# Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



## Notes:

1. PACKAGE CONFORMS TO JEDEC MO-255 VARIATION UAAD
2. DIMENSIONS ARE IN MILLIMETERS
3. DRAWING CONFORMS TO ASME Y.14M-1994
4. PIN 1 FLAG, END OF PACKAGE OFFSET.

MAC08AREVC

**Pb-Free 8-Lead MicroPak, 1.6 mm Wide**  
**Package Number MAC08A**

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use

provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

Definition of terms

| Datasheet Identification | Product Status         | Definition                                                                                                                                                                                                            |
|--------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                                    |
| Preliminary              | First Production       | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.                                                       |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild Semiconductor. The datasheet is printed for reference information only.                                                   |

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910

**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative