

Is Now Part of



ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at
www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild_questions@onsemi.com.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

May 2018

FSA644 — 2:1 MIPI D-PHY (1.5Gbps) 4-Data Lane Switch

Features

Switch Type	SPDT (10x)
Signal Types	**MIPI, D-PHY**
V_{CC}	1.65 to 4.5 V
Input Signals	0 to V_{CC}
R_{ON}	6 Ω Typical HS MIPI 8 Ω Typical LP MIPI
ΔR_{ON}	0.6 Ω Typical HS & LP MIPI
R_{ON_FLAT}	0.3 Ω Typical
I_{CCZ}	0.5 µA Maximum
I_{CC}	32 µA Maximum
O_{IRR}	-40 dB Typical
X_{TALK}	-25 dB Typical
Bandwidth	1100 MHz Minimum
Channel-to-Channel Skew	6 ps Typical
C_{ON}	5.2 pF
Operating Temperature	-40 to +85°C
Package	36-Ball WLCSP
FSA644UCX Top Mark	M7
Ordering Information	FSA644UCX
FSA644BUCX Top Mark	KM
Ordering Information	FSA644BUCX

Description

The FSA644 is a four-data-lane, MIPI, D-PHY switch. This single-pole, double-throw (SPDT) switch is optimized for switching between two high-speed or low-power MIPI sources. The FSA644 is designed for the MIPI specification and allows connection to a CSI or DSI module.

Applications

- Cellular Phones, Smart Phones
- Displays

Related Resources

- FSA644 Demonstration Board

Typical Application




Figure 1. Mobile Phone Example

© 2011 Fairchild Semiconductor Corporation

Pin Descriptions




Figure 2. Analog Symbol

Pin Name	Description		
$CLK_{P/N}$	Common Clock Path		
$D1_{P/N}$	Common Data Path 1		
$D2_{P/N}$	Common Data Path 2		
$D3_{P/N}$	Common Data Path 3		
$D4_{P/N}$	Common Data Path 4		
$CLKA_{P/N}$	A-Side Clock Path		
$DA1_{P/N}$	A-Side Data Path 1		
$DA2_{P/N}$	A-Side Data Path 2		
$DA3_{P/N}$	A-Side Data Path 3		
$DA4_{P/N}$	A-Side Data Path 4		
$CLKB_{P/N}$	B-Side Clock Path		
$DB1_{P/N}$	B-Side Data Path 1		
$DB2_{P/N}$	B-Side Data Path 2		
$DB3_{P/N}$	B-Side Data Path 3		
$DB4_{P/N}$	B-Side Data Path 4		
SEL	Control Pin	SEL=0	CLKP=CLKAP, CLKN=CLKAN, Dn(P/N)=DAn(P/N)
		SEL=1	CLKP=CLKBP, CLKN=CLKBN, Dn(P/N)=DBn(P/N)
/OE	Output Enable		
V_{CC}	Power		
GND	Ground		
NC	No Connect		

© 2011 Fairchild Semiconductor Corporation

Pin Definitions




Figure 3. Top Through View

Table 1. Ball-to-Pin Mappings

Ball	Pin Name
A1	CLK_N
A2	CLK_P
A3	$CLKA_P$
A4	$DA1_P$
A5	$DA2_P$
A6	$DA2_N$
B1	$D1_N$
B2	$D1_P$
B3	$CLKA_N$
B4	$DA1_N$
B5	$DA3_P$
B6	$DA3_N$
C1	$D2_N$
C2	$D2_P$
C3	NC
C4	V_{CC}
C5	$DA4_P$
C6	$DA4_N$
D1	$D3_N$
D2	$D3_P$
D3	GND
D4	NC
D5	$CLKB_N$
D6	$CLKB_P$
E1	$D4_N$
E2	$D4_P$
E3	$DB4_P$
E4	$DB3_P$
E5	$DB1_N$
E6	$DB1_P$
F1	/OE
F2	SEL
F3	$DB4_N$
F4	$DB3_N$
F5	$DB2_N$
F6	$DB2_P$

Truth Table

SEL	/OE	Function
LOW	LOW	CLK_P=$CLKA_P$, CLK_N=$CLKA_N$, Dn(P/N)=DAn(P/N)
HIGH	LOW	CLK_P=$CLKB_P$, CLK_N=$CLKB_N$, Dn(P/N)=DBn(P/N)
X	HIGH	DAn(P/N), DBn(P/N) Data Ports High Impedance

© 2011 Fairchild Semiconductor Corporation

Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Symbol	Parameter		Min.	Max.	Unit
V_{CC}	Supply Voltage		-0.50	+5.25	V
V_{CNTRL}	DC Input Voltage (/OE)[1]		-0.5	V_{CC}	V
V_{SW}	DC Switch I/O Voltage[1]		-0.50	5.25	V
I_{IK}	DC Input Diode Current		-50		mA
I_{OUT}	DC Output Current			50	mA
T_{STG}	Storage Temperature		-65	+150	°C
ESD	Human Body Model, JEDEC: JESD22-A114	All Pins		3.5	kV
		I/O to GND		3.5	
		Power to GND		8.0	
	Charged Device Model, JEDEC: JESD22-C101			1.5	
	IEC 61000-4-2 System	Contact		8.0	
		Air Gap		15.0	

Note:

1. The input and output negative ratings may be exceeded if the input and output diode current ratings are observed.

Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to Absolute Maximum Ratings.

Symbol	Parameter		Min.	Max.	Unit
V_{CC}	Supply Voltage		1.65	4.50	V
V_{CNTRL}	Control Input Voltage (S, /OE)[2]		0	V_{CC}	V
V_{SW}	Switch I/O Voltage (CLKn, CLKAn, CLKBn, Dn, DAn, DBn)	HS Mode	0.1	0.3	V
		LP Mode	0	1.2	
T_A	Operating Temperature		-40	+85	°C

Note:

2. The control input must be held HIGH or LOW; it must not float.

© 2011 Fairchild Semiconductor Corporation

DC Electrical Characteristics

All typical values are at T_A=25°C unless otherwise specified.

Symbol	Parameter	Conditions	V_{CC} (V)	T_A=- 40ºC to +85ºC			Unit
				Min.	Typ.	Max.	
V_{IK}	Clamp Diode Voltage	I_{IN}=-18 mA	2.8			-1.2	V
V_{IH}	Input Voltage High		1.65 to 4.50	1.0			V
V_{IL}	Input Voltage Low		1.65 to 4.50			0.4	V
I_{IN}	Control Input Leakage (SEL,/OE)	V_{SW}=0 to V_{CC}	1.65 to 4.50	-100		100	nA
$I_{NO(OFF)}$, $I_{NC(OFF)}$	Off Leakage Current of Port CLKAn, DAn, CLKBn, DBn	CLKn, Dn=0.3 V; V_{CC}-0.3 V; CLKAn, DAn, or CLKBn; DBn= V_{CC}-0.3 V, 0.3 V, or Floating; /OE=0 V	1.65 to 4.50	-100		100	nA
$I_{A(ON)}$	On Leakage Current of Common Ports (CLKn, Dn)	CLKn, Dn = 0.3 V; V_{CC}-0.3 V; CLKAn, DAn, or CLKBn; DBn=V_{CC}-0.3 V, 0.3 V, or Floating; /OE=0 V	1.65 to 4.50	-100		100	nA
I_{OFF}	Power-Off Leakage Current	CLKn, Dn, or CLKAn; DAn or CLKBn, DBn; V_{IN}=0 V to 4.5 V; V_{CC}=0 V	0	-100		100	nA
I_{OZ}	Off-State Leakage	0 ≤ CLKn, Dn, CLKAn, CLKBn, DAn, DBn ≤ 3.6 V, /OE=High	4.5	-100		100	nA
$R_{ON_MIPI_HS}$	Switch On Resistance for HS MIPI Applications(3)	I_{ON}=-10 mA, /OE=0 V, SEL=V_{CC} or 0V, $CLK_{A, B}$, DBn or DAn=0.1, 0.2, 0.3	1.8		7	12	Ω
			2.5		6	9	
			3.6		6	9	
			4.5		6	9	
$R_{ON_MIPI_LP}$	Switch On Resistance for LP MIPI Applications(3)	I_{ON}=-10 mA, /OE=0 V, SEL=V_{CC} or 0V, $CLK_{A, B}$, DBn or DAn=0, 0.6, 1.2 V	1.8		6.7	12.0	Ω
			2.5		6.4	9.0	
			3.6		6.2	9.0	
			4.5		6.0	9.0	
$\Delta R_{ON_MIPI_HS}$	On Resistance Matching Between HS MIPI Channels(4)	I_{ON}=-10 mA, /OE=0 V, SEL=V_{CC} or 0 V, $CLK_{A, B}$, DBn or DAn=0.1, 0.2, 0.3	1.8		0.8		Ω
			2.5		0.6		
			3.6		0.5		
			4.5		0.5		
$\Delta R_{ON_MIPI_LP}$	On Resistance Matching Between LP MIPI Channels(4)	I_{ON}=-10 mA, /OE=0 V, SEL=V_{CC} or 0 V, $CLK_{A,B}$, DBn or DAn= 0.0, 0.6, 1.2 V	1.8		0.8		Ω
			2.5		0.6		
			3.6		0.5		
			4.5		0.5		
$R_{ON_FLAT_MIPI_HS}$	On Resistance Flatness for HS MIPI Signals(4)	I_{ON}=-10 mA, /OE=0 V, SEL=V_{CC} or 0 V, $CLK_{A, B}$, DBn or DAn=0.1, 0.2, 0.3	1.8		1.5		Ω
			2.5		0.5		
			3.6		0.3		
			4.5		0.2		
$R_{ON_FLAT_MIPI_LP}$	On Resistance Flatness for LP MIPI Signals(4)	I_{ON}=-10 mA, /OE=0 V, SEL=V_{CC} or 0 V, $CLK_{A, B}$, DB_n or DAn=0.0, 0.6, 1.2 V	1.8		3.5		Ω
			2.5		2		
			3.6		1		
			4.5		0.5		

Continued on the following page…

© 2011 Fairchild Semiconductor Corporation

DC Electrical Characteristics

All typical values are at T_A=25°C unless otherwise specified.

Symbol	Parameter	Conditions	V_{CC} (V)	T_A=- 40ºC to +85ºC			Unit
				Min.	Typ.	Max.	
I_{CCZ}	Quiescent Hi-Z Supply Current	V_{IN}=0 or V_{CC}, I_{OUT}=0	4.5			0.5	µA
I_{CC}	Quiescent Supply Current	V_{IN}=0 or V_{CC}, I_{OUT}=0	2.5 to 4.5			32	µA
			1.8			22	
I_{CCT}	Increase in I_{CC} Current Per Control Voltage and V_{CC}	$V_{SEL,/OE}$=1.65 V	4.5			4	µA
			2.5			0.1	

Notes:

3. Measured by the voltage drop between A and B pins at the indicated current through the switch. On resistance is determined by the lower of the voltage on the two (A or B ports).
4. Guaranteed by characterization.

AC Electrical Characteristics

All typical values are for V_{CC}=3.3V at T_A=25°C unless otherwise specified.

Symbol	Parameter	Conditions	V_{CC} (V)	T_A=- 40ºC to +85ºC			Unit
				Min.	Typ.	Max.	
t_{INIT}	Initalization Time V_{CC} to Output (5)	R_L=50 Ω, C_L=5 pF, V_{SW}=1.2 V	2.5 to 4.5			100	µs
			1.8			150	
t_{EN}	Enable Turn-On Time, /OE to Output	R_L=50 Ω, C_L=5 pF, V_{SW}=1.2 V	2.5 to 4.5		120	200	ns
			1.8		250	500	
t_{DIS}	Disable Turn-Off Time, /OE to Output	R_L=50 Ω, C_L=5 pF, V_{SW}=1.2 V	2.5 to 4.5		25	50	ns
			1.8		50	90	
t_{ON}	Turn-On Time, SEL to Output	R_L=50 Ω, C_L=5 pF, V_{SW}=1.2 V	2.5 to 4.5		50	100	ns
			1.8		75	125	
t_{OFF}	Turn-Off Time SEL to Output	R_L=50 Ω, C_L=5 pF, V_{SW}=1.2 V	2.5 to 4.5		50	200	ns
			1.8		200	325	
t_{BBM}	Break-Before-Make Time	R_L=50 Ω, C_L=5 pF, V_{SW}=1.2 V		10	50		ns
O_{IRR}	Off Isolation for MIPI(5)	R_L=50 Ω, f=750 MHz, /OE=V_{CC} V_{SW}=-1 dBm (200 mV_{PP})	1.65 to 4.5		-18		dB
X_{TALK}	Crosstalk for MIPI(5)	R_L=50 Ω, f=750 MHz, V_{SW}=-1 dBm (200 mV_{PP})	1.65 to 4.5		-25		dB
BW	-3db Bandwidth(5)	R_L=50 Ω, C_L=0 pF	3.0	1100	1600		MHz
S_{DD21}	Differential Data Rate	Inter-operability Data Rate	3.0		1.5		Gbps

Note:

5. Guaranteed by characterization.

© 2011 Fairchild Semiconductor Corporation

High-Speed-Related AC Electrical Characteristics

Symbol	Parameter	Conditions	V_{CC} (V)	T_A=- 40ºC to +85ºC			Unit
				Min.	Typ.	Max.	
$t_{SK(O)}$	Channel-to-Channel Single-Ended Skew[6]	TDR-Based Method (V_{SW}=0.2 V_{PP}, C_L=C_{ON})	3.3		6	20	ps
$t_{SK(P)}$	Skew of Opposite Transitions of the Same Output[6]	TDR-Based Method (V_{SW}=0.2 V_{PP}, C_L=C_{ON})	3.3		6	20	ps

Note:

6. Guaranteed by characterization.


Capacitance

Symbol	Parameter	Conditions	T_A=- 40ºC to +85ºC			Unit
			Min.	Typ.	Max.	
C_{IN}	Control Pin Input Capacitance	V_{CC}=0 V, f=1 MHz		2.1		pF
C_{ON}	Out On Capacitance	V_{CC}=3.3 V, /OE=0 V, f=1 MHz		5.2		
C_{OFF}	Out Off Capacitance	V_{CC} and /OE=3.3 V, f=1 MHz		2.0		


Ordering Information

Part Number	Top Mark	Package	D	E	X	Y
FSA644UCX	M7	36-Ball WLCSP, Non-JEDEC 2.36 mm x 2.36 mm, 0.4 mm Pitch	2.36 mm	2.36 mm	0.18 mm	0.18 mm
FSA644BUCX	KM	36-Ball WLCSP, Non-JEDEC 2.415 mm x 2.415 mm, 0.4 mm Pitch	2.415 mm	2.415 mm	0.208 mm	0.208 mm


© 2011 Fairchild Semiconductor Corporation




TOP VIEW




RECOMMENDED LAND PATTERN
(NSMD PAD TYPE)





SIDE VIEWS



BOTTOM VIEW

NOTES

A. NO JEDEC REGISTRATION APPLIES.

B. DIMENSIONS ARE IN MILLIMETERS.


C. DIMENSIONS AND TOLERANCE PER ASMEY14.5M, 1994.

D. DATUM C IS DEFINED BY THE SPHERICAL CROWNS OF THE BALLS.


E. PACKAGE NOMINAL HEIGHT IS 500 ± 39 MICRONS (461-539 MICRONS).

F. FOR DIMENSIONS D, E, X, AND Y SEE PRODUCT DATASHEET.


G. DRAWING FILNAME: MKT-UC036AArev1.




TOP VIEW




RECOMMENDED LAND PATTERN
(NSMD PAD TYPE)





SIDE VIEWS



BOTTOM VIEW

NOTES

A. NO JEDEC REGISTRATION APPLIES.

B. DIMENSIONS ARE IN MILLIMETERS.

C. DIMENSIONS AND TOLERANCE PER ASMEY14.5M, 2009.

D. DATUM C IS DEFINED BY THE SPHERICAL CROWNS OF THE BALLS.

E. PACKAGE NOMINAL HEIGHT IS 495 ± 39 MICRONS (456-534 MICRONS).

F. FOR DIMENSIONS D, E, X, AND Y SEE PRODUCT DATASHEET.

G. DRAWING FILNAME: MKT-UC036AB REV1.

FAIRCHILD™

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative