HEYCO



Heyco® Thick Panel Rubber Grommets

For Panels .250˝ (6,4 mm) to .375˝ (9,5 mm) Thick

MOUNTING HOLE DIAMETER		PART NO.	DESCRIPTION	PART DIMENSIONS A Inside Diameter		B Head Diameter		C Overall Height	
in.	mm.	Black		in.	mm.	in.	mm.	in.	mm.
For .250˝ (6,4 mm) Thick Panels									
.312	7,9	**G1023**	RG 312-6-8	.188	4,8	.437	11,1	.375	9,5
.437	11,1	**G1058***	RG 437-8-8	.250	6,4	.625	15,9		
.500	12,7	**G1086***	RG 500-10-8	.313	8,0	.625	15,9	.625	15,9
		G1095	RG 500-12-8	.375	9,5	.750	19,1	.500	12,7
.562	14,3	**G1117***	RG 562-10-8	.313	8,0	.812	20,6	.500	12,7
.625	15,9	**G1134**	RG 625-12-8	.375	9,5	.875	22,2		
.687	17,5	**G1154**	RG 687-14-8	.438	11,1	.937	23,8		
.812	20,6	**G1195**	RG 812-16-8	.500	12,7	1.062	27,0	.500	12,7
		G1200	RG 812-18-8	.562	14,3				
.875	22,2	**G1220**	RG 875-20-8	.625	15,9	1.125	28,6	.500	12,7
1.000	25,4	**G1257**	RG 1000-22-8	.687	17,5	1.312	33,3	.562	14,3
		G1264	RG 1000-28-8	.875	22,2	1.250	31,8	.625	15,9
1.062	27,0	**G1273**	RG 1062-24-8	.750	19,1	1.375	34,9	.562	14,3
1.250	31,8	**G1301**	RG 1250-24-8	.750	19,1	1.625	41,3	.438	11,1
		G1307	RG 1250-28-8	.875	22,2	1.625	41,3	.625	15,9
1.375	34,9	**G1324**	RG 1375-32-8	1.000	25,4	1.750	44,5	.625	15,9
1.500	38,1	**G1353**	RG 1500-40-8	1.250	31,8	1.750	44,5	.500	12,7
		G1354	RG 1500-40-8A	1.250	31,8	2.000	50,8	.516	13,1
1.750	44,5	**G1373**	RG 1750-48-8	1.500	38,1	2.000	50,8	.500	12,7
		G1374	RG 1750-48-8A	1.500	38,1	2.125	54,0	.625	15,9
2.000	50,8	**G1393**	RG 2000-56-8	1.750	44,5	2.500	63,5	.531	13,5
		G1394*	RG 2000-56-8A	1.750	44,5	2.500	63,5	.560	14,2
2.500	63,5	**G1421**	RG 2.5-64-8	2.000	50,8	3.000	76,2	.562	14,3
		G1425	RG 2.5-72-8	2.250	57,2	3.000	76,2	.625	15,9
For .375˝ (9,5 mm) Thick Panels									
.375	9,5	**G1043**	RG 375-10-12	.313	8,0	.562	14,3	.500	12,7
.500	12,7	**G1096**	RG 500-12-12	.375	9,5	.625	15,9	.625	15,9
.562	14,3	**G1121**	RG 562-12-12	.375	9,5	.750	19,1	.750	19,1
.625	15,9	**G1136**	RG 625-13-12	.406	10,3	.812	20,6	.625	15,9
.750	19,1	**G1182**	RG 750-16-12	.500	12,7	1.000	25,4		
.875	22,2	**G1214**	RG 875-18-12	.562	14,3	1.062	27,0		
1.000	25,4	**G1249**	RG 1000-18-12	.562	14,3	1.250	31,8		
1.125	28,6	**G1278**	RG 1125-24-12	.750	19,1	1.625	41,3	1.125	28,6
1.250	31,8	**G1308****	RG 1250-28-12	.875	22,2	1.750	44,5	.750	19,1
		G1314	RG 1250-32-12	1.000	25,4	1.500	38,1	.625	15,9
1.375	34,9	**G1326**	RG 1375-32-12	1.000	25,4	1.750	44,5	.750	19,1
1.750	44,5	**G1375**	RG 1750-48-12	1.500	38,1	2.125	54,0		
2.000	50,8	**G1395**	RG 2000-56-12	1.750	44,5	2.500	63,5	.625	15,9
2.500	63,5	**G1427**	RG 2.5-72-12	2.250	57,2	3.000	76,2	.750	19,1

Standard color black. *Nitrile **Neoprene

- Used to protect through holes. Help eliminate sharp edges so your wires are protected and add aesthetic value to your application.
- 38 sizes available that accommodate mounting holes ranging from .312˝ (7,9 mm) to holes as large as 2.50˝ (63,5 mm) in diameter and panel thicknesses of .250˝ (6,4 mm) and .375˝ (9,5 mm).
- Rubber grommets are constructed of SBR (unless otherwise noted) with an operating temperature range of -40°F (-40°C) to 221°F (105°C).
- SBR grommets have good water resistant characteristics and are suitable for most moderate chemicals and wet or dry organic acids.
- Provides vibration dampening.



Material	**SBR (Styrene Butadiene)**
Temperature Rating	**-40°F (-40°C) to 221°F (105°C)**

Quick Specs

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Heyco:

G1023 G1278 G1257 G1195 G1395 G1134 G1394 G1273 G1393 G1136 G1117 G1043 G1154 G1421 G1214 G1220 G1308 G1324 G1264 G1374 G1307 G1427 G1425 G1314 G1200 G1301 G1375 G1354 G1086 G1096 G1121 G1182 G1095 G1353 G1058 G1326 G1249 G1373