G2402

N-CHANNEL ENHANCEMENT MODE POWER MOSFET

BV_{DSS}	20V
$R_{DS(ON)}$	250mΩ
I_D	3.2A

Description

The G2402 provides the designer with the best combination of fast switching, low on-resistance and cost-effectiveness.

Features

- Ultra Low On-Resistance
- Fast Switching

Applications

- Power Management in Notebook Computer
- Portable Equipment
- Battery Powered System.

Package Dimensions







REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	2.70	3.10	G	1.90	REF.
B	2.40	2.80	H	1.00	1.30
C	1.40	1.60	K	0.10	0.20
D	0.35	0.50	J	0.40	-
E	0	0.10	L	0.85	1.15
F	0.45	0.55	M	0°	10°

Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	V_{DS}	20	V
Gate-Source Voltage	V_{GS}	±12	V
Continuous Drain Current[3], V_{GS}@4.5V	I_D @TA =25℃	3.2	A
Continuous Drain Current[3], V_{GS}@4.5V	I_D @TA =70℃	2.6	A
Pulsed Drain Current[1,2]	I_{DM}	7.4	A
Power Dissipation	P_D @TA =25℃	1.38	W
Linear Derating Factor		0.01	W/℃
Operating Junction and Storage Temperature Range	Tj, Tstg	-55 ~ +150	℃

Thermal Data

Parameter	Symbol	Ratings	Unit
Thermal Resistance Junction-ambient[3] Max.	Rthj-a	90	℃/W

Electrical Characteristics(Tj = 25℃ Unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Drain-Source Breakdown Voltage	BV_{DSS}	20	-	-	V	V_{GS}=0, I_D=250uA
Breakdown Voltage Temperature Coefficient	$\triangle BV_{DSS}/\triangle Tj$	-	0.1	-	V/℃	Reference to 25℃, I_D=1mA
Gate Threshold Voltage	$V_{GS(th)}$	0.7	-	1.2	V	V_{DS}= V_{GS}, I_D=250uA
Forward Transconductance	gfs	-	6	-	S	V_{DS}=10V, I_D=0.47A
Gate-Source Leakage Current	I_{GSS}	-	-	±100	nA	V_{GS}= ±12V
Drain-Source Leakage Current(Tj=25℃)	I_{DSS}	-	-	1.0	uA	V_{DS}=20V, V_{GS}=0
Drain-Source Leakage Current(Tj=70℃)		-	-	10	uA	V_{DS}=20V, V_{GS}=0
Static Drain-Source On-Resistance[2]	$R_{DS(ON)}$	-	-	250	mΩ	I_D=0.93A, V_{GS}=4.5V
		-	-	350		I_D=0.47A, V_{GS}=2.7V
Total Gate Charge[2]	Q_g	-	4.4	-	nC	I_D=3.6A
Gate-Source Charge	Q_{gs}	-	0.6	-		V_{DS}=10V
Gate-Drain ("Miller") Change	Q_{gd}	-	1.9	-		V_{GS}=4.5V
Turn-on Delay Time[2]	$T_{d(on)}$	-	5.2	-	ns	V_{DS}=10V I_D=3.6A R_G=6Ω V_{GS}=5v R_D=2.8Ω
Rise Time	T_r	-	37	-		
Turn-off Delay Time	$T_{d(off)}$	-	15	-		
Fall Time	T_f	-	5.7	-		
Input Capacitance	C_{iss}	-	145	-	pF	V_{GS}=0V V_{DS}=10V f=1.0MHz
Output Capacitance	C_{oss}	-	100	-		
Reverse Transfer Capacitance	C_{rss}	-	50	-		

Source-Drain Diode

Forward On Voltage[2]	V_{SD}	-	-	1.2	V	I_S=1.6A, V_{GS}=0 Tj=25℃
Continuous Source Current(Body Diode)	Is	-	-	1	A	V_D= V_G=0V, V_S=1.2V
Pulsed Source Current (Body Diode)[1]	Ism	-	-	7.4	A	

Notes: 1. Pulse width limited by Max. junction temperature.
2. Pulse width≦300us, duty cycle≦2%.
3. Surface mounted on 1 in^2 copper pad of FR4 board;270℃/w when mounted on min. copper pad.

Characteristics Curve



Fig 1. Typical Output Characteristics



Fig 2. Typical Output Characteristics



Fig 3. On-Resistance v.s. Gate Voltage



Fig 4. Normalized On-Resistance



Fig 5. Forward Characteristic of Reverse Diode



Fig 6. Gate Threshold Voltage v.s. Junction Temperature



Fig 7. Gate Charge Characteristics



Fig 8. Typical Capacitance Characteristics



Fig 9. Maximum Safe Operating Area



Fig10. Effective Transient Thermal Impedance



Fig 11. Switching Time Waveform



Fig 12. Gate Charge Waveform

Important Notice:
- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:
- **Taiwan**: No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
  TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China**: (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
  TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165