


GES-1651 Version: 1



16-Port Web Smart Gigabit Ethernet Switch, 2 x SFP/RJ45 Combo

LevelOne GES-1651 is a powerful, high-performance Gigabit Ethernet switch with 16 10/100/1000Mbps ports shared 2 SFP(mini GBIC) ports, providing you a cost-effective, space-saving solution for expanding your network. The gigabit ports can lead you to a real gigabit connection, making you be able to transfer high bandwidth-needed files larger and faster in an easy way. And the two gigabit SFP ports allow you to add fiber-optic connectivities for connecting to other network switches to obtain long-distance communication. This GES-1651 device provides the easy management function, the network administrator can configure the status and the port function setting of the device through the Web-Based UI. When installing the auto-discovery management tool helps network managers to search and access those switches on LAN easily. Therefore, network managers can access switches that support autodiscovery on LAN without memorizing IP address.



Key Features

- 16 Gigabit Ethernet ports with 2 shared SFP slots
- 10/100/1000Mbps wire speed transmission and reception
- IEEE 802.1d/w/s Spanning Tree Protocol (STP) and port mirroring
- IEEE 802.1p QoS with 4 priority queues
- Supports port-based VLAN, IEEE 802.1Q VLAN Tagging
- IP Multicast Filtering through IGMP Snooping V1 / V2 / V3
- 10K jumbo frames to increase data transfer rates
- Supports 8K MAC address auto-learning and auto-aging
- 19-inch metal housing
-

Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet
IEEE 802.3u 100-BASE-TX, Fast Ethernet
IEEE 802.3ab 1000BASE-T, Gigabit Ethernet
IEEE 802.1p Quality of Service (QoS)
IEEE 802.1Q Virtual LANs (VLANs)
IEEE 802.1D MAC Bridges
IEEE 802.1d Standard Spanning Tree Protocol (STP)
IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
IEEE 802.3x Flow Control (full-duplex flow control)

Buffer Memory:

4086KB

Connectors and Cabling:

16 x 10/100/1000BASE-T RJ-45 ports
2 x 100/1000Base-X SFP Slots (2 shared)

Button:

Reset Button

Indicator:

Power, System, Link/Active, 1000Mbps

Transmission Method:

Store-and-Forward

Power:

Power Consumption: 14.7W
Power Input: 100-240V AC, 50-60 Hz, Internal Power Supply

Features

General:

Quality of Service (QoS):
4 hardware Priority Queues per port
Traffic classification based on IEEE 802.1p CoS, DSCP, Supports WRR, Strict scheduling, or hybrid mode
Rate Limiting - Ingress resolution; Egress resolution

Spanning Tree:

IEEE 802.1D MAC Bridges
IEEE 802.1d Spanning Tree Protocol (STP)
IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
Loop/Root Guard, TC-BPDU Guard, BPDU Guard/Filter

Virtual Local Area Network (VLAN):

802.1Q tag-based VLAN - up to 4096 VLAN IDs

Security:

Storm Control:

Prevents traffic on a LAN from being disrupted by a broadcast, multicast, or unicast storm on a port

Access Control:

HTTPS; Manage VLAN assignment

Port security: access control port-based

Filtering: Port-/MAC-/IP-based security

Management:

Diagnosis:
syslog

Network:

RMON (groups 1, 2, 3 and 9) Management; SNMP v1, v2c, v3; DNS client, proxy; HTTPs

Ease of Use:

Firmware and Configuration: upgrade/downgrade via HTTP

Performance**Backplane (Gbps):**

32Gbps

MAC Address Table:

8K

Data Transfer Rate:

10/100/1000Mbps

Packet Forwarding Rate:

1000Mbps port - 1,488,000pps

100Mbps port - 148,000pps

10Mbps port - 14,880pps

Jumbo Frame (K):

10K

Environment**Temperature (°C):**

Operating: 0°C ~ 40°C

Storage: -40°C ~ 70°C

Humidity (Non-condensing):

Storage: 5% ~ 90%

Operating: 10 ~ 90%

Deployment:

19-inch rack-mountable

Physical Specifications**Dimensions (W x D x H mm):**

440 x 180 x 44 mm

Weight (g):

2000 g


Reliability**MTBF:**

107949 hour

Others**Approval and Compliance:**

FCC Part 15 Class A, CE, RoHS

Diagram



Order Information

GES-1651

Package Contents

GES-1651
Power Cord
19" Rackmount Kit
Rubber Feet
Quick Installation Guide
Resource CD (User Manual)

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.