GP1600FSM18

Hi-Reliability Single Switch IGBT Module

Replaces May 2000 version, DS5361-1.1

DS5361-2.3 January 2001

FEATURES

- High Thermal Cycling Capability
- 1600A Per Module
- Non Punch Through Silicon
- Isolated MMC Base with AlN Substrates

APPLICATIONS

- High Reliability Inverters
- Motor Controllers
- Traction Drives
- Resonant Converters

The Powerline range of high power modules includes dual and single switch configurations covering voltages from 1200V to 3300V and currents up to 4800A.

The GP1600FSM18 is a single switch 1800V, n channel enhancement mode, insulated gate bipolar transistor (IGBT) module. The IGBT has a wide reverse bias safe operating area (RBSOA) ensuring reliability in demanding applications. This device is optimised for traction drives and other applications requiring high thermal cycling capability or very high reliability.

The module incorporates an electrically isolated base plate and low inductance construction enabling circuit designers to optimise circuit layouts and utilise earthed heat sinks for safety.

ORDERING INFORMATION

Order As:

GP1600FSM18

Note: When ordering, please use the whole part number.

KEY PARAMETERS

V_{CES}		1800V
$V_{CE(sat)}$	(typ)	3.5V
I_C	(max)	1600A
$I_{C(PK)}$	(max)	3200A



Fig. 1 Single switch circuit diagram



Outline type code: F

(See package details for further information)

Fig. 2 Electrical connections - (not to scale)

ABSOLUTE MAXIMUM RATINGS

Stresses above those listed under 'Absolute Maximum Ratings' may cause permanent damage to the device. In extreme conditions, as with all semiconductors, this may include potentially hazardous rupture of the package. Appropriate safety precautions should always be followed. Exposure to Absolute Maximum Ratings may affect device reliability.

T_{case} = 25˚C unless stated otherwise

Symbol	Parameter	Test Conditions	Max.	Units
V_{CES}	Collector-emitter voltage	V_{GE} = 0V	1800	V
V_{GES}	Gate-emitter voltage	-	±20	V
I_C	Continuous collector current	T_{case} = 65˚C for T_j = 125˚C	1600	A
$I_{C(PK)}$	Peak collector current	1ms, T_{case} = 110˚C	2400	A
P_{max}	Max. transistor power dissipation	T_{case} = 25˚C, T_j = 150˚C	13.9	kW
V_{isol}	Isolation voltage	Commoned terminals to base plate. AC RMS, 1 min, 50Hz	4000	V

THERMAL AND MECHANICAL RATINGS

Symbol	Parameter	Test Conditions	Min.	Max.	Units
$R_{th(j-c)}$	Thermal resistance - transistor	Continuous dissipation - junction to case	-	9	˚C/kW
$R_{th(j-c)}$	Thermal resistance - diode	Continuous dissipation - junction to case	-	20	˚C/kW
$R_{th(c-h)}$	Thermal resistance - case to heatsink (per module)	Mounting torque 5Nm (with mounting grease)	-	8	˚C/kW
T_j	Junction temperature	Transistor	-	150	˚C
		Diode	-	125	˚C
T_{stg}	Storage temperature range	-	–40	125	˚C
-	Screw torque	Mounting - M6	-	5	Nm
		Electrical connections - M4	-	2	Nm
		Electrical connections - M8	-	10	Nm

Caution: This device is sensitive to electrostatic discharge. Users should follow ESD handling procedures.

ELECTRICAL CHARACTERISTICS

T_{case} = 25˚C unless stated otherwise.

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
I_{CES}	Collector cut-off current	V_{GE} = 0V, V_{CE} = V_{CES}	-	-	2	mA
		V_{GE} = 0V, V_{CE} = V_{CES}, T_{case} = 125˚C	-	-	50	mA
I_{GES}	Gate leakage current	V_{GE} = ±20V, V_{CE} = 0V	-	-	8	µA
$V_{GE(TH)}$	Gate threshold voltage	I_C = 80mA, V_{GE} = V_{CE}	4.5	5.5	6.5	V
$V_{CE(sat)}$	Collector-emitter saturation voltage	V_{GE} = 15V, I_C = 1600A	-	3.5	4	V
		V_{GE} = 15V, I_C = 1600A, T_{case} = 125˚C	-	4.3	5	V
I_F	Diode forward current	DC	-	-	1600	A
I_{FM}	Diode maximum forward current	t_p = 1ms	-	-	3200	A
V_F	Diode forward voltage	I_F = 1600A	-	2.2	2.5	V
		I_F = 1600A, T_{case} = 125˚C	-	2.3	2.6	V
C_{ies}	Input capacitance	V_{CE} = 25V, V_{GE} = 0V, f = 1MHz	-	180	-	nF
L_M	Module inductance	-	-	15	-	nH

ELECTRICAL CHARACTERISTICS

T_{case} = 25°C unless stated otherwise

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$t_{d(off)}$	Turn-off delay time	I_C = 1600A	-	1500	1650	ns
t_f	Fall time	V_{GE} = ±15V	-	200	300	ns
E_{OFF}	Turn-off energy loss	V_{CE} = 900V	-	500	650	mJ
$t_{d(on)}$	Turn-on delay time	$R_{G(ON)}$ = $R_{G(OFF)}$ = 2.2Ω	-	400	550	ns
t_r	Rise time	L ~ 50nH	-	300	450	ns
E_{ON}	Turn-on energy loss		-	450	650	mJ
Q_{rr}	Diode reverse recovery charge	I_F = 1600A, V_R = 50% V_{CES},	-	300	400	µC
I_{rr}	Diode reverse current	dI_F/dt = 6000A/µs	-	750	-	A
E_{REC}	Diode reverse recovery energy		-	200	-	mJ

T_{case} = 125°C unless stated otherwise

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$t_{d(off)}$	Turn-off delay time	I_C = 1600A	-	1700	1900	ns
t_f	Fall time	V_{GE} = ±15V	-	200	330	ns
E_{OFF}	Turn-off energy loss	V_{CE} = 900V	-	650	800	mJ
$t_{d(on)}$	Turn-on delay time	$R_{G(ON)}$ = $R_{G(OFF)}$ = 2.2Ω	-	500	700	ns
t_r	Rise time	L ~ 50nH	-	350	500	ns
E_{ON}	Turn-on energy loss		-	600	800	mJ
Q_{rr}	Diode reverse recovery charge	I_F = 1600A, V_R = 50% V_{CES},	-	550	650	µC
I_{rr}	Diode reverse current	dI_F/dt = 5000A/µs	-	850	-	A
E_{REC}	Diode reverse recovery energy		-	320	-	mJ

Caution: This device is sensitive to electrostatic discharge. Users should follow ESD handling procedures.

TYPICAL CHARACTERISTICS



Fig. 3 Typical output characteristics



Fig. 4 Typical output characteristics



Fig. 5 Typical switching energy vs collector current



Fig. 6 Typical switching energy vs gate resistance



Fig. 7 Diode typical forward characteristics



Fig. 8 Reverse bias safe operating area



Fig. 9 Forward bias safe operating area



Fig. 10 Transient thermal impedance

Caution: This device is sensitive to electrostatic discharge. Users should follow ESD handling procedures.

PACKAGE DETAILS

For further package information, please visit our website or contact your nearest Customer Service Centre. All dimensions in mm, unless stated otherwise. DO NOT SCALE.



Nominal weight: 1600g

Module outline type code: F

ASSOCIATED PUBLICATIONS

Title	Application Note Number
Electrostatic handling precautions	AN4502
An introduction to IGBTs	AN4503
IGBT ratings and characteristics	AN4504
Heatsink requirements for IGBT modules	AN4505
Calculating the junction temperature of power semiconductors	AN4506
Gate drive considerations to maximise IGBT efficiency	AN4507
Parallel operation of IGBTs – punch through vs non-punch through characteristics	AN4508
Guidance notes for formulating technical enquiries	AN4869
Principle of rating parallel connected IGBT modules	AN5000
Short circuit withstand capability in IGBTs	AN5167
Driving Dynex Semincoductor IGBT modules with Concept gate drivers	AN5384

POWER ASSEMBLY CAPABILITY

The Power Assembly group was set up to provide a support service for those customers requiring more than the basic semiconductor, and has developed a flexible range of heatsink and clamping systems in line with advances in device voltages and current capability of our semiconductors.

We offer an extensive range of air and liquid cooled assemblies covering the full range of circuit designs in general use today. The Assembly group continues to offer high quality engineering support dedicated to designing new units to satisfy the growing needs of our customers.

Using the latest CAD methods our team of design and applications engineers aim to provide the Power Assembly Complete Solution (PACs).

HEATSINKS

The Power Assembly group has its own proprietary range of extruded aluminium heatsinks. They have been designed to optimise the performance of Dynex semiconductors. Data with respect to air natural, forced air and liquid cooling (with flow rates) is available on request.

For further information on device clamps, heatsinks and assemblies, please contact your nearest sales representative or customer service office.

Caution: This device is sensitive to electrostatic discharge. Users should follow ESD handling procedures.

http://www.dynexsemi.com

e-mail: power_solutions@dynexsemi.com

HEADQUARTERS OPERATIONS
DYNEX SEMICONDUCTOR LTD
Doddington Road, Lincoln.
Lincolnshire. LN6 3LF. United Kingdom.
Tel: 00-44-(0)1522-500500
Fax: 00-44-(0)1522-500550

DYNEX POWER INC.
99 Bank Street, Suite 410,
Ottawa, Ontarion, Canada, K1P 6B9
Tel: 613.723.7035
Fax: 613.723.1518
Toll Free: 1.888.33.DYNEX (39639)

CUSTOMER SERVICE CENTRES
Central Europe Tel: +33 (0)1 58 04 91 00. Fax: +33 (0)1 46 38 51 33
North America Tel: 011-800-5554-5554. Fax: 011-800-5444-5444
UK, Scandinavia & Rest Of World Tel: +44 (0)1522 500500. Fax: +44 (0)1522 500020

SALES OFFICES
Central Europe Tel: +33 (0)1 58 04 91 00. Fax: +33 (0)1 46 38 51 33
North America Tel: (613) 723-7035. Fax: (613) 723-1518. Toll Free: 1.888.33.DYNEX (39639) /
Tel: (949) 733-3005. Fax: (949) 733-2986.
UK, Scandinavia & Rest Of World Tel: +44 (0)1522 500500. Fax: +44 (0)1522 500020

These offices are supported by Representatives and Distributors in many countries world-wide.
© Dynex Semiconductor 2001 Publication No. DS5261-2 Issue No. 2.2 January 2001
TECHNICAL DOCUMENTATION – NOT FOR RESALE. PRINTED IN UNITED KINGDOM

Datasheet Annotations:

Dynex Semiconductor annotate datasheets in the top right hard corner of the front page, to indicate product status. The annotations are as follows:-

Target Information: This is the most tentative form of information and represents a very preliminary specification. No actual design work on the product has been started.

Preliminary Information: The product is in design and development. The datasheet represents the product as it is understood but details may change.

Advance Information: The product design is complete and final characterisation for volume production is well in hand.

No Annotation: The product parameters are fixed and the product is available to datasheet specification.

This publication is issued to provide information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose nor form part of any order or contract nor to be regarded as a representation relating to the products or services concerned. No warranty or guarantee express or implied is made regarding the capability, performance or suitability of any product or service. The Company reserves the right to alter without prior notice the specification, design or price of any product or service. Information concerning possible methods of use is provided as a guide only and does not constitute any guarantee that such methods of use will be satisfactory in a specific piece of equipment. It is the user's responsibility to fully determine the performance and suitability of any equipment using such information and to ensure that any publication or data used is up to date and has not been superseded. These products are not suitable for use in any medical products whose failure to perform may result in significant injury or death to the user. All products and materials are sold and services provided subject to the Company's conditions of sale, which are available on request.

All brand names and product names used in this publication are trademarks, registered trademarks or trade names of their respective owners.