WON-TOP ELECTRONICS


HD5000 – HD5006

50A GLASS PASSIVATED HITACHI TYPE PRESS-FIT DIODE

RoHS Pb

Features

- Glass Passivated Die Construction
- Low Leakage
- Low Cost
- High Surge Current Capability
- Typical I_R less than 5.0μA
- C-Band Terminal Construction



12mm Hitachi		
Dim	**Min**	**Max**
A	11.80	12.00
B	3.65	3.85
C	1.35	1.55
D (+)*	18.00	22.00
D (-)*	20.00	24.00
All Dimensions in mm		

(+)*: Standard Polarity
(-)*: Reverse Polarity

Mechanical Data

- Case: 12mm Hitachi Type Press-Fit
- Terminals: Contact Areas Readily Solderable
- Polarity: Cathode to Case (Reverse Units Are Available Upon Request and Are Designated By A "R" Suffix, i.e. HD5002R or HD5004R)
- Polarity: White Color Equals Standard, Black Color Equals Reverse Polarity
- Mounting Position: Any
- **Lead Free: For RoHS / Lead Free Version, Add "-LF" Suffix to Part Number, See Page 2**

Maximum Ratings and Electrical Characteristics @T_A=25°C unless otherwise specified

Single Phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

Characteristic	Symbol	HD5000	HD5001	HD5002	HD5003	HD5004	HD5005	HD5006	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	50	100	200	300	400	500	600	V
RMS Reverse Voltage	$V_{R(RMS)}$	35	70	140	210	280	350	420	V
Average Rectified Output Current @T_C = 120°C	I_O	50							A
Non-Repetitive Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed on Rated Load (JEDEC Method)	I_{FSM}	500							A
Forward Voltage @I_F = 50A	V_{FM}	1.0							V
Peak Reverse Current @T_A = 25°C At Rated DC Blocking Voltage @T_A = 100°C	I_{RM}	5.0 500							μA
Typical Junction Capacitance (Note 1)	C_J	300							pF
Typical Thermal Resistance (Note 2)	$R_{\theta JC}$	1.2							°C/W
Operating and Storage Temperature Range	T_J, T_{STG}	-65 to +175							°C

Note: 1. Measured at 1.0 MHz and applied reverse voltage of 4.0V D.C.
2. Thermal Resistance: Junction to case, single side cooled.

© Won-Top Electronics Co., Ltd.

WON-TOP ELECTRONICS

ORDERING INFORMATION

Product No.	Package Type	Shipping Quantity
HD5000	12mm Hitachi Press-Fit	500 Units/Box
HD5001	12mm Hitachi Press-Fit	500 Units/Box
HD5002	12mm Hitachi Press-Fit	500 Units/Box
HD5003	12mm Hitachi Press-Fit	500 Units/Box
HD5004	12mm Hitachi Press-Fit	500 Units/Box
HD5005	12mm Hitachi Press-Fit	500 Units/Box
HD5006	12mm Hitachi Press-Fit	500 Units/Box

1. Shipping quantity given is for minimum packing quantity only. For minimum order quantity, please consult the Sales Department.
2. **To order Lead Free version (with Lead Free finish), add "-LF" suffix to part number above. For example, HD5000-LF.**

WON-TOP ELECTRONICS and are registered trademarks of Won-Top Electronics Co., Ltd (WTE). WTE has checked all information carefully and believes it to be correct and accurate. However, WTE cannot assume any responsibility for inaccuracies. Furthermore, this information does not give the purchaser of semiconductor devices any license under patent rights to manufacturer. WTE reserves the right to change any or all information herein without further notice.

WARNING: DO NOT USE IN LIFE SUPPORT EQUIPMENT. WTE power semiconductor products are not authorized for use as critical components in life support devices or systems without the express written approval.

Won-Top Electronics Co., Ltd.
No. 44 Yu Kang North 3rd Road,
Chine Chen Dist., Kaohsiung 806, Taiwan
Phone: 886-7-822-5408 or 886-7-822-5410
Fax: 886-7-822-5417
Email: sales@wontop.com
Internet: http://www.wontop.com

We power your everyday.

© Won-Top Electronics Co., Ltd.