HD SHOULDER 好达

规格书编号

SPEC NO :

产品规格书
SPECIFICATION

CUSTOMER 客 户：

PRODUCT 产 品：SAW FILTER

MODEL NO 型 号：HDF865C SMD-4

MARKING 印 字：HDF4864

PREPARED 编 制： CHECKED 审 核：


APPROVED 批 准： D A T E 日 期：2011-6-13

客户确认 CUSTOMER RECEIVED:		
审核 CHECKED	批准 APPROVED	日期 DATE

无锡市好达电子有限公司

Shoulder Electronics Limited

1. Package Dimension



3.Performance

3.1Application

Low-Loss SAW Filter of cordless system.

Center Frequency:865MHz


3.2Maximum Rating


Operation Temperature Range	-40℃ to +85℃
Storage Temperature Range	-45℃to +85℃
DC. Permissive Voltage	10 V DC
Maximum Input Power	10 dBm


3.3 Electronic Characteristics(-10~60℃)


	Unit	Minimum	Typical	Maximum
Center Frequency	MHz	-	865	-
Insertion Loss (860 MHz ~870 MHz)	dB		2.5	4.0
Amplitude Ripple (860 MHz ~870 MHz)	dB		1.0	2.5
Relative Attenuation 0.3 MHz ~ 850 MHz 900 MHz ~ 1200MHz	dB	 38 40	 42 45	-
Input/Output Impedance	Ohms		50	

3.4 Frequency Characteristics










3.5 Test Circuit



4. ENVIRONMENTAL CHARACTERISTICS

4-1 High temperature exposure

Subject the device to +85℃ for 16 hours. Then release the filter into the room conditions for 24 hours prior to the measurement. It shall fulfill the specifications in 3.3.

4-2 Low temperature exposure

Subject the device to -40℃ for 16 hours. Then release the device into the room conditions for 24 hours prior to the measurement. It shall fulfill the specifications in 3.3.

4-3 Temperature cycling

Subject the device to a low temperature of -40℃ for 30 minutes. Following by a high temperature of +85℃ for 30 Minutes. Then release the device into the room conditions for 24 hours prior to the measurement. It shall meet the specifications in 3.3.

4-4 Resistance to solder heat

Dip the device terminals no closer than 1.5mm into the solder bath at 260℃ ±10℃ for 10±1 sec. Then release the device into the room conditions for 4 hours. The device shall meet the specifications in 3.3.

4-5 Solderability

Subject the device terminals into the solder bath at 245℃ ±5℃ for 5s, More than 95% area of the terminals must be covered with new solder. It shall meet the specifications in 3.3.

4-6 Mechanical shock

Drop the device randomly onto the concrete floor from the height of 1m 3 times. the device shall fulfill the specifications in 3.3.

4-7 Vibration

Subject the device to the vibration for 1 hour each in x,y and z axes with the amplitude of 1.5 mm at 10 to 55 Hz. The device shall fulfill the specifications in 3.3.

5. REMARK

5.1 Static voltage

Static voltage between signal load & ground may cause deterioration &destruction of the component. Please avoid static voltage.

5.2 Ultrasonic cleaning

Ultrasonic vibration may cause deterioration & destruction of the component. Please avoid ultrasonic cleaning

5.3 Soldering

Only leads of component may be soldered . Please avoid soldering another part of component.

6. Packing

6.1 Dimensions

(1) Carrier Tape: Figure 1

(2) Reel: Figure 2

(3) The product shall be packed properly not to be damaged during transportation and storage.


6.2 Reeling Quantity

1000 pcs/reel 7”

3000 pcs/reel 13”

6.3 Taping Structure


(1) The tape shall be wound around the reel in the direction shown below.



(2) Label

Device Name	
User Product Name	
Quantity	
Lot No.	

(3) Leader part and vacant position specifications.




7. TAPE SPECIFICATIONS


7.1 Tensile Strength of Carrier Tape: 4.4N/mm width

7.2 Top Cover Tape Adhesion (See the below figure)

(1) pull off angle: 0~15°
(2) speed: 300mm/min.
(3) force: 20~70g



[Figure 1] Carrier Tape Dimensions




[Unit:mm]

W	F	E	P0	P1	P2	D0	D1	t1	t2	A	B

12.00 ±0.30	5.50 ±0.10	1.75 ±0.10	4.00 ±0.10	4.00 ±0.10	2.00 ±0.10	Ø1.50	Ø1.5 ±0.25	0.31 ±0.05	1.30 ±0.10	3.4 MAX.	3.4 MAX

[Figure 2]

[Unit:mm]



A	B	C	D	E	W	t	r
Ø330 ±1.0	Ø100 ±0.5	Ø13 ±0.5	Ø21 ±0.8	2 ±0.5	13 ±0.3	3 max.	1.0 max.