
PROGRAMMABLE HIGH-STABILITY HIGH-FREQUENCY CRYSTAL OSCILLATOR

HG-8002JA/DC series



Product number (please refer to page 2)

Q3502JAxxxxxx00
Q3402DCxxxxxx00

- Wide frequency output by PLL technology.
- Low current consumption by output enable function (OE) or standby function (ST)
- Pin compatible with half-size oscillator SG-531.
- Package and pin compatible with SG-615.
- Low current consumption due to CMOS technology.
- Excellent environmental capability.

Specifications (characteristics)


Item		Symbol	Specifications *2 PT/ST	PH/SH	PC/SC	Remarks
Output frequency range		f_0	1.0000 MHz to 125.0000 MHz			Refer to page 33. "Frequency range"
Power source voltage	Max. supply voltage	V_{DD}-GND	-0.5 V to +7.0 V			
	Operating voltage	V_{DD}	5.0 V ±0.25 V		3.3 V ±0.165 V	
Temperature range	Storage temperature	T_{STG}	-55 °C to +125 °C			Stored as bare product after unpacking
	Operating temperature	T_{OPR}	-20 °C to +70 °C (-40 °C to +85 °C)			Refer to page 33."Frequency range"
Frequency stability		$\Delta f/f_0$	AV: ±20 x 10^{-6} BV: ±25 x 10^{-6} CX: ± 30 x 10^{-6}			AV,BV: -20 °C to +70 °C, CX: -40 °C to +85 °C
Current consumption		Iop	45 mA Max.		28 mA Max.	No load condition, Max. frequency range
Output disable current		I_{OE}	30 mA Max.		16 mA Max.	OE=GND(PT, PH, PC)
Standby current		I_{ST}	50 μA Max.			$\overline{ST}$=GND(ST, SH, SC)
Duty *1		t_w/ t	—	40 % to 60 %		CMOS load: 1/2V_{DD} level, Max. load condition
			40 % to 60 %	—		TTL load: 1.4 V level, Max. load condition
High output voltage		V_{OH}	V_{DD} -0.4 V Min.			I_{OH}=-16 mA(PT/ST, PH/SH),-8 mA(PC/SC)
Low output voltage		V_{OL}	0.4 V Max.			I_{OL}= 16 mA(PT/ST, PH/SH), 8 mA(PC/SC)
Output load condition (fan out) *1	TTL	N	2 TTL Max.	—		Max. frequency and Max. operating voltage range
	CMOS	C_L	15 pF Max.			
Output enable/disable input voltage		V_{IH}	2.0 V Min.		0.7 x V_{DD} Min.	$\overline{ST}$, OE terminal
		V_{IL}	0.8 V Max.		0.2 x V_{DD} Max.	
Output rise time *1	CMOS level	t_{TLH}	—	3 ns Max.		CMOS load: 20 %→80 % V_{DD} level
	TTL level		4 ns Max.	—		TTL load: 0.4 V→2.4 V level
Output fall time *1	CMOS level	t_{THL}	—	3 ns Max.		CMOS load: 80 %→20 % V_{DD} level
	TTL level		4 ns Max.	—		TTL load: 2.4 V→0.4 V level
Oscillation start up time		t_{OSC}	10 ms Max.			Time at minimum operating voltage to be 0 s
Aging		fa	±2 x 10^{-6}/year Max.			Ta= +25 °C, V_{DD} = 5.0 V/3.3 V(PC/SC)
Shock resistance		S.R.	±2 x 10^{-6} Max.			Three drops on a hard board from 750 mm or excitation test with 29400 m/s² x 0.3 ms x 1/2sine wave in 3 directions

*1 Operating temperature(-40 °C to +85 °C), the available frequency, duty and output load conditions, please refer to page 33.
*2 PLL - PLL connection & Jitter specification, please refer to page 53, 54.
Checking possible by the Frequency Checking Program.

External dimensions


(Unit: mm)

● HG-8002JA series



No.	Pin terminal
1	OE or $\overline{ST}$
2	GND
3	OUT
4	V_{DD}

● HG-8002DC series



No.	Pin terminal
1	OE or $\overline{ST}$
2	GND
3	OUT
4	V_{DD}

Note.
OE Pin (PT, PH, PC)
OE pin - "H" or "open" : Specified frequency output.
OE pin - "L" : Output is high impedance.

ST pin (ST, SH, SC)
ST pin - "H" or "open" : Specified frequency output.
ST pin - "L" : Output is low level (weak pull - down), oscillation stops.

Recommended soldering pattern

(Unit: mm)

● HG-8002JA series

