Product data sheet
Characteristics

HR6IMA16C1
Surge Protect - IMA - HR - 160kA - 240VAC delta - 3P3W - T1

Product availability : Non-Stock - Not normally stocked in distribution facility

Price** : 11,616.00 USD



Main

Product	Surge protection device
Range	Surgelogic
Device Short Name	IMA
Type	HR

Complementary

Surge Current	160 kA
Voltage Rating	240 V delta AC
Number of Phases	3 phase
Wiring Configuration	3-wire
Connection	I-Line line Lugs ground AWG 6 copper 35.40 lbf.in (4 N.m) Lugs neutral AWG 6 copper 35.40 lbf.in (4 N.m)
MCOV	320 V
Max Number of Poles	3
Rated Current	60 A
Breaking Capacity	100 kA
Trip Unit Technology	Electronic
SCCR	200 kA
Local Signalling	Status LED green per phase normal operation Status LED red per phase fault
Provided Equipment	Alarm enable/disable switch Surge counter Circuit breaker
Mounting Support	Panel mounting
Height	12.16 in (308.9 mm)
Width	13.46 in (341.9 mm)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Depth	5.59 in (142.1 mm)
Cable length	19.02 in (483 mm)

Environment

Enclosure Rating	NEMA 1
Standards	UL 1449:ed. 3 CSA C22.2 No 8:1986 UL 96A:ed. 12 UL 489:ed. 11 CSA C22.2 No 5-09

Ordering and shipping details

Category	08460 - SURGE PROTECTION I-LINE
Discount Schedule	DE1B
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.