HS-7260

Intel® Core™ 2 Duo/Celeron® M processor PCI-ISA Bus SBC w/CF, Mini PCIe, DVI-I/CRT/LVDS, Dual Gigabit Ethernet, Audio, 2 COM, 4 USB

PCI-ISA Bus



Features

- **» Intel® Core™ 2 Duo/Celeron® M processor**
- **» 1 x SO-DIMM up to 2GB DDR2 SDRAM**
- **» Intel® 945GME/ICH7-M system chipset**
- **» 18-bit dual-channel LVDS**
- **» Dual Gigabit Ethernet**
- **» ALC202A Codec**
- **» Hardware Monitor function**
- **» Option for DVI-I display**

System

CPU
Socket M for Intel® Core™ 2 Duo/Celeron® M processor
Bus Interface
PCI-ISA Bus (no 3.3V output through Golden Finger)
FSB
667/533MHz FSB
BIOS
Award PnP Flash BIOS
System Chipset
Intel® 945GME/ICH7-M
I/O Chipset
Winbond W83627EHG
System Memory
1 x 200-pin SO-DIMM, DDR2 667MHz, Max. 2GB
Storage
1 x Type II CF socket
Expansion Interface
1 x mini PCIe socket (option)
GPIO
8-bit general purpose input/output port
Watchdog Timer
Software programmable time-out intervals from 1~255 sec. or 1~255 min.
H/W Status Monitor
Monitoring temperatures, voltages, and cooling fan status
Power Function
AT/ATX power mode support
Operating Temperature
0~60ºC
Operating Humidity
0~95%, non-condensing
Board Size (LxW)
186 x 122 mm

I/O Interface

I/O Port
1 x RS-232
1 x RS-232/422/485
4 x USB2.0
1 x IDE
1 x FDD
2 x SATA
1 x Parallel
1 x PS/2 for KB/MS
1 x 6-pin connector for PS/2 KB/MS

Display

Chipset
Intel® 945GME integrated Intel® GMA950
Display Memory
DVMT3.0 up to 224MB video memory
LVDS
18-bit single/dual-channel
DVI
Chrontel CH7307 (option)
Resolution
VGA Mode: 2048 x 1536

Audio

Chipset
RealTek ALC202A
Audio Interface
MIC In, Line Out

Ethernet

Chipset
Dual RealTek RTL8111C Gigabit Ethernet
Ethernet Interface
2 x RJ-45

Ordering Information

HS-7260
PCI-ISA Bus SBC w/CF, CRT, Dual Gigabit Ethernet, Audio
HS-7260/DVI-I
PCI-ISA Bus SBC w/CF, DVI-I, Dual Gigabit Ethernet, Audio

Accessory Options
IDE Cable, FDD Cable, SATA Cable, USB Cable, H=23mm Cooler

All specifications and photos are subject to change without notice. #201104