Product data sheet
Characteristics

HU362SS
Safety switch, heavy duty, non fusible, 60A, 3 poles, 60 hp, 600 VAC/600 NDC, NEMA 4, 4X, 5, 316 steel,

Product availability : Stock - Normally stocked in distribution facility

Price* : 3,444.00 USD



Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device application	Heavy application
Disconnect Type	Non-fusible disconnect
Factory Installed Neutral	None
Phase	3 phase
Number of Poles	3
Current Rating	60 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 4/4X/5 stainless steel 316
Maximum Horse Power Rating	50 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 60 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 30 hp 600 V at DC

Complementary

Short Circuit Current Rating	200 kA maximum
Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	3-wire
Wire Size	AWG 14...AWG 3 copper AWG 12...AWG 3 aluminium
Tightening torque	50 lbf.in (5.65 N.m) AWG 3) 45 lbf.in (5.08 N.m) AWG 6...AWG 4) 40 lbf.in (4.52 N.m) 0.01 in² (8.367 mm²) AWG 8) 50 lbf.in (5.65 N.m) 0.00…0.01 in² (2.06…5.261 mm²) AWG 14...AWG 10)

* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Depth	6.97 in (177.04 mm)
Width	10.81 in (274.57 mm)
Height	16.87 in (428.50 mm)

Environment

Certifications	UL listed file E2875

Ordering and shipping details

Category	00010 - H&HU SW,2&3P,N4,SS,30-200A
Discount Schedule	DE1
GTIN	00785901706670
Nbr. of units in pkg.	1
Package weight(Lbs)	19.45 lb(US) (8.82 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.60 in (19.304 cm)
Package 1 width	11.20 in (28.448 cm)
Package 1 Length	19.30 in (49.022 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months