Technical Data Sheet
1.6mm round Subminiature Side Looking Infrared LED

IR26-51C/L110/TR8



Features

- Small double-end package
- Low forward voltage
- Good spectral matching to Si photo detector
- Package in 8mm tape on 7″ diameter reel.
- Pb free
- The product itself will remain within RoHS compliant version.

Descriptions

- IR26-51C/L110/TR8 is an infrared emitting diode in miniature SMD package which is molded in a water clear plastic with spherical top view lens. The device is spectrally matched with silicon photodiode and phototransistor


Applications

- PCB mounted infrared sensor
- Infrared emitting for miniature light barrier
- Floppy disk drive
- Optoelectronic switch
- Smoke detector

Device Selection Guide

LED Part No.	Chip Material	Lens Color
IR	GaAlAs	Water Clear

Package Dimensions



Notes: 1.All dimensions are in millimeters
2.Tolerances unless dimensions ±0.1mm

Absolute Maximum Ratings (Ta=25℃)

Parameter	Symbol	Rating	Units
Continuous Forward Current	I_F	65	mA
Reverse Voltage	V_R	5	V
Operating Temperature	T_{opr}	-25 ~ +85	℃
Storage Temperature	T_{stg}	-40 ~ +100	℃
Soldering Temperature *1	T_{sol}	260	℃
Power Dissipation at(or below) 25℃ Free Air Temperature	P_d	130	mW

Notes: *1:Soldering time≦5 seconds.

Electro-Optical Characteristics (Ta=25℃)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Units
Radiant Intensity	Ie	I_F=20mA	1.0	3.5	--	mW /sr
		I_F=100mA Pulse Width≦100 μs ,Duty≦1%	--	15	--	
Peak Wavelength	λp	I_F=20mA	--	940	--	nm
Spectral Bandwidth	Δλ	I_F=20mA	--	45	--	nm
Forward Voltage	V_F	I_F=20mA	--	1.2	1.5	V
		I_F=100mA Pulse Width≦100 μs ,Duty≦1%	--	1.5	1.8	
		I_F=1A Pulse Width≦100 μs ,Duty≦1%	--	2.6	4.0	
Reverse Current	I_R	V_R=5V	--	--	10	μA
View Angle	2θ1/2	I_F=20mA	--	20	--	deg

Typical Electro-Optical Characteristics Curves

Fig.1 Forward Current vs. Ambient Temperature




Fig.2 Spectral Distribution




Fig.3 Peak Emission Wavelength Ambient Temperature





Fig.4 Forward Current vs. Forward Voltage



Typical Electro-Optical Characteristics Curves

Fig.5 Relative Intensity vs. Forward Current





Fig.6 Relative Radiant Intensity vs. Angular Displacement



Precautions For Use

1. Over-current-proof

Customer must apply resistors for protection , otherwise slight voltage shift will cause big current change (Burn out will happen).

2. Storage

2.1 Do not open moisture proof bag before the products are ready to use.

2.2 Before opening the package, the LEDs should be kept at 30℃ or less and 90%RH or less.

2.3 The LEDs should be used within a year.


2.4 After opening the package, the LEDs should be kept at 30℃ or less and 70%RH or less.

2.5 The LEDs should be used within 168 hours (7 days) after opening the package.

2.6 If the moisture absorbent material (silica gel) has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the following conditions.
Baking treatment : 60±5℃ for 24 hours.

3. Soldering Condition

3.1 Pb-free solder temperature profile



3.2 Reflow soldering should not be done more than two times.

3.3 When soldering, do not put stress on the LEDs during heating.


3.4 After soldering, do not warp the circuit board.

4.Soldering Iron

Each terminal is to go to the tip of soldering iron temperature less than 280℃ for 3 seconds within once in less than the soldering iron capacity 25W. Leave two seconds and more intervals, and do soldering of each terminal. Be careful because the damage of the product is often started at the time of the hand solder.

5.Repairing

Repair should not be done after the LEDs have been soldered. When repairing is unavoidable, a double-head soldering iron should be used (as below figure). It should be confirmed beforehand whether the characteristics of the LEDs will or will not be damaged by repairing.




Reliability Test Item And Condition

The reliability of products shall be satisfied with items listed below.
Confidence level：90%
LTPD：10%


NO.	Item	Test Conditions	Test Hours/ Cycles	Sample Sizes	Failure Judgement Criteria	Ac/Re
1	REFLOW Soldering	TEMP.：260℃±5℃ 10secs	6Mins	22pcs	$I_R \geqq U \times 2$ $Ie \leqq L \times 0.8$ $V_F \geqq U \times 1.2$ U：Upper Specification Limit L：Lower Specification Limit	0/1
2	Temperature Cycle	H：+100℃ 15mins ↕ 5mins L：-40℃ 15mins	50Cycles	22pcs		0/1
3	Thermal Shock	H：+100℃ 5mins ↕ 10secs L：-10℃ 5mins	50Cycles	22pcs		0/1
4	High Temperature Storage	TEMP.：+100℃	1000hrs	22pcs		0/1
5	Low Temperature Storage	TEMP.：-40℃	1000hrs	22pcs		0/1
6	DC Operating Life	I_F=20mA	1000hrs	22pcs		0/1
7	High Temperature/ High Humidity	85℃ / 85% R.H	1000hrs	22pcs		0/1

Package Dimensions



Taping Dimensions

Unit:mm



Packing Quantity Specification

1.1500Pcs/1Volume，1Volume/1Bag

2.10Boxes/1Carton

Label Form Specification



CPN: Customer's Production Number
P/N : Production Number
QTY: Packing Quantity
CAT: Ranks
HUE: Peak Wavelength
REF: Reference
LOT No: Lot Number
MADE IN TAIWAN: Production Place

Notes

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
3. These specification sheets include materials protected under copyright of EVERLIGHT corporation. Please don't reproduce or cause anyone to reproduce them without EVERLIGHT's consent.

EVERLIGHT ELECTRONICS CO., LTD.
Office: No 25, Lane 76, Sec 3, Chung Yang Rd, Tucheng, Taipei 236, Taiwan, R.O.C
Tel: 886-2-2267-2000, 2267-9936
Fax: 886-2267-6244, 2267-6189, 2267-6306
http:\\www.everlight.com