PD 91453B

International
IOR Rectifier

IRG4BC30UD

INSULATED GATE BIPOLAR TRANSISTOR WITH ULTRAFAST SOFT RECOVERY DIODE

UltraFast CoPack IGBT

Features

- UltraFast: Optimized for high operating frequencies 8-40 kHz in hard switching, >200 kHz in resonant mode
- Generation 4 IGBT design provides tighter parameter distribution and higher efficiency than Generation 3
- IGBT co-packaged with HEXFRED™ ultrafast, ultra-soft-recovery anti-parallel diodes for use in bridge configurations
- Industry standard TO-220AB package



n-channel

V_{CES} = 600V

$V_{CE(on)\ typ.}$ = 1.95V

@V_{GE} = 15V, I_C = 12A



TO-220AB

Benefits

- Generation -4 IGBT's offer highest efficiencies available
- IGBTs optimized for specific application conditions
- HEXFRED diodes optimized for performance with IGBTs . Minimized recovery characteristics require less/no snubbing
- Designed to be a "drop-in" replacement for equivalent industry-standard Generation 3 IR IGBTs

Absolute Maximum Ratings

	Parameter	Max.	Units
V_{CES}	Collector-to-Emitter Voltage	600	V
I_C @ T_C = 25°C	Continuous Collector Current	23	A
I_C @ T_C = 100°C	Continuous Collector Current	12	
I_{CM}	Pulsed Collector Current ①	92	
I_{LM}	Clamped Inductive Load Current ②	92	
I_F @ T_C = 100°C	Diode Continuous Forward Current	12	
I_{FM}	Diode Maximum Forward Current	92	
V_{GE}	Gate-to-Emitter Voltage	± 20	V
P_D @ T_C = 25°C	Maximum Power Dissipation	100	W
P_D @ T_C = 100°C	Maximum Power Dissipation	42	
T_J	Operating Junction and	-55 to +150	°C
T_{STG}	Storage Temperature Range		
	Soldering Temperature, for 10 sec.	300 (0.063 in. (1.6mm) from case)	
	Mounting Torque, 6-32 or M3 Screw.	10 lbf•in (1.1 N•m)	

Thermal Resistance

	Parameter	Min.	Typ.	Max.	Units
$R_{\theta JC}$	Junction-to-Case - IGBT	------	------	1.2	°C/W
$R_{\theta JC}$	Junction-to-Case - Diode	------	------	2.5	
$R_{\theta CS}$	Case-to-Sink, flat, greased surface	------	0.50	------	
$R_{\theta JA}$	Junction-to-Ambient, typical socket mount	-----	-----	80	
Wt	Weight	------	2 (0.07)	------	g (oz)

4/17/00

Electrical Characteristics @ T_J = 25°C (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
$V_{(BR)CES}$	Collector-to-Emitter Breakdown Voltage③	600	----	----	V	V_{GE} = 0V, I_C = 250µA
$\Delta V_{(BR)CES}/\Delta T_J$	Temperature Coeff. of Breakdown Voltage	----	0.63	----	V/°C	V_{GE} = 0V, I_C = 1.0mA
$V_{CE(on)}$	Collector-to-Emitter Saturation Voltage	----	1.95	2.1	V	I_C = 12A V_{GE} = 15V
		----	2.52	----		I_C = 23A See Fig. 2, 5
		----	2.09	----		I_C = 12A, T_J = 150°C
$V_{GE(th)}$	Gate Threshold Voltage	3.0	----	6.0		V_{CE} = V_{GE}, I_C = 250µA
$\Delta V_{GE(th)}/\Delta T_J$	Temperature Coeff. of Threshold Voltage	----	-11	----	mV/°C	V_{CE} = V_{GE}, I_C = 250µA
g_{fe}	Forward Transconductance ④	3.1	8.6	----	S	V_{CE} = 100V, I_C = 12A
I_{CES}	Zero Gate Voltage Collector Current	----	----	250	µA	V_{GE} = 0V, V_{CE} = 600V
		----	----	2500		V_{GE} = 0V, V_{CE} = 600V, T_J = 150°C
V_{FM}	Diode Forward Voltage Drop	----	1.4	1.7	V	I_C = 12A See Fig. 13
		----	1.3	1.6		I_C = 12A, T_J = 150°C
I_{GES}	Gate-to-Emitter Leakage Current	----	----	±100	nA	V_{GE} = ±20V

Switching Characteristics @ T_J = 25°C (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
Q_g	Total Gate Charge (turn-on)	----	50	75	nC	I_C = 12A
Qge	Gate - Emitter Charge (turn-on)	----	8.1	12		V_{CC} = 400V See Fig. 8
Q_{gc}	Gate - Collector Charge (turn-on)	----	18	27		V_{GE} = 15V
$t_{d(on)}$	Turn-On Delay Time	----	40	----	ns	T_J = 25°C
t_r	Rise Time	----	21	----		I_C = 12A, V_{CC} = 480V
$t_{d(off)}$	Turn-Off Delay Time	----	91	140		V_{GE} = 15V, R_G = 23Ω
t_f	Fall Time	----	80	130		Energy losses include "tail" and
E_{on}	Turn-On Switching Loss	----	0.38	----	mJ	diode reverse recovery.
E_{off}	Turn-Off Switching Loss	----	0.16	----		See Fig. 9, 10, 11, 18
E_{ts}	Total Switching Loss	----	0.54	0.9		
$t_{d(on)}$	Turn-On Delay Time	----	40	----	ns	T_J = 150°C, See Fig. 9, 10, 11, 18
t_r	Rise Time	----	22	----		I_C = 12A, V_{CC} = 480V
$t_{d(off)}$	Turn-Off Delay Time	----	120	----		V_{GE} = 15V, R_G = 23Ω
t_f	Fall Time	----	180	----		Energy losses include "tail" and
E_{ts}	Total Switching Loss	----	0.89	----	mJ	diode reverse recovery.
L_E	Internal Emitter Inductance	----	7.5	----	nH	Measured 5mm from package
C_{ies}	Input Capacitance	----	1100	----	pF	V_{GE} = 0V
C_{oes}	Output Capacitance	----	73	----		V_{CC} = 30V See Fig. 7
C_{res}	Reverse Transfer Capacitance	----	14	----		f = 1.0MHz
t_{rr}	Diode Reverse Recovery Time	----	42	60	ns	T_J = 25°C See Fig.
		----	80	120		T_J = 125°C 14 I_F = 12A
I_{rr}	Diode Peak Reverse Recovery Current	----	3.5	6.0	A	T_J = 25°C See Fig.
		----	5.6	10		T_J = 125°C 15 V_R = 200V
Q_{rr}	Diode Reverse Recovery Charge	----	80	180	nC	T_J = 25°C See Fig.
		----	220	600		T_J = 125°C 16 di/dt 200A/µs
$di_{(rec)M}/dt$	Diode Peak Rate of Fall of Recovery	----	180	----	A/µs	T_J = 25°C See Fig.
	During t_b	----	120	----		T_J = 125°C 17



Fig. 1 - Typical Load Current vs. Frequency
(Load Current = I_{RMS} of fundamental)



Fig. 2 - Typical Output Characteristics



Fig. 3 - Typical Transfer Characteristics



Fig. 4 - Maximum Collector Current vs. Case Temperature



Fig. 5 - Typical Collector-to-Emitter Voltage vs. Junction Temperature



Fig. 6 - Maximum IGBT Effective Transient Thermal Impedance, Junction-to-Case



Fig. 7 - Typical Capacitance vs. Collector-to-Emitter Voltage



Fig. 8 - Typical Gate Charge vs. Gate-to-Emitter Voltage



Fig. 9 - Typical Switching Losses vs. Gate Resistance



Fig. 10 - Typical Switching Losses vs. Junction Temperature



Fig. 11 - Typical Switching Losses vs. Collector-to-Emitter Current



Fig. 12 - Turn-Off SOA



Fig. 13 - Maximum Forward Voltage Drop vs. Instantaneous Forward Current



Fig. 14 - Typical Reverse Recovery vs. di_f/dt



Fig. 15 - Typical Recovery Current vs. di_f/dt



Fig. 16 - Typical Stored Charge vs. di_f/dt



Fig. 17 - Typical $di_{(rec)M}/dt$ vs. di_f/dt



Fig. 18a - Test Circuit for Measurement of I_{LM}, E_{on}, $E_{off(diode)}$, t_{rr}, Q_{rr}, I_{rr}, $t_{d(on)}$, t_r, $t_{d(off)}$, t_f



Fig. 18b - Test Waveforms for Circuit of Fig. 18a, Defining E_{off}, $t_{d(off)}$, t_f



Fig. 18c - Test Waveforms for Circuit of Fig. 18a, Defining E_{on}, $t_{d(on)}$, t_r



Fig. 18d - Test Waveforms for Circuit of Fig. 18a, Defining E_{rec}, t_{rr}, Q_{rr}, I_{rr}



Figure 18e. Macro Waveforms for Figure 18a's Test Circuit



Figure 19. Clamped Inductive Load Test Circuit



Figure 20. Pulsed Collector Current Test Circuit

Notes:

① Repetitive rating: V_{GE}=20V; pulse width limited by maximum junction temperature (figure 20)

② V_{CC}=80%(V_{CES}), V_{GE}=20V, L=10µH, R_G = 23Ω (figure 19)

③ Pulse width ≤ 80µs; duty factor ≤ 0.1%.

④ Pulse width 5.0µs, single shot.

Case Outline — TO-220AB



CONFORMS TO JEDEC OUTLINE TO-220AB
Dimensions in Millimeters and (Inches)

International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
IR EUROPEAN REGIONAL CENTRE: 439/445 Godstone Rd, Whyteleafe, Surrey CR3 OBL, UK Tel: ++ 44 (0)20 8645 8000
IR CANADA: 15 Lincoln Court, Brampton, Ontario L6T3Z2, Tel: (905) 453 2200
IR GERMANY: Saalburgstrasse 157, 61350 Bad Homburg Tel: ++ 49 (0) 6172 96590
IR ITALY: Via Liguria 49, 10071 Borgaro, Torino Tel: ++ 39 011 451 0111
IR JAPAN: K&H Bldg., 2F, 30-4 Nishi-Ikebukuro 3-Chome, Toshima-Ku, Tokyo 171 Tel: 81 (0)3 3983 0086
IR SOUTHEAST ASIA: 1 Kim Seng Promenade, Great World City West Tower, 13-11, Singapore 237994 Tel: ++ 65 (0)838 4630
IR TAIWAN:16 Fl. Suite D. 207, Sec. 2, Tun Haw South Road, Taipei, 10673 Tel: 886-(0)2 2377 9936
Data and specifications subject to change without notice. 4/00