
IXYS

HiPerFET™ Power MOSFETs Single Die MOSFET

IXFN 340N07

V_{DSS} = 70 V
I_{D25} = 340 A
$R_{DS(on)}$ = 4 mΩ
t_{rr} ≤ 200 ns


N-Channel Enhancement Mode
Avalanche Rated, High dv/dt, Low t_{rr}



Symbol	Test Conditions	Maximum Ratings	
V_{DSS}	T_J = 25°C to 150°C	70	V
V_{DGR}	T_J = 25°C to 150°C; R_{GS} = 1 MΩ	70	V
V_{GS}	Continuous	±20	V
V_{GSM}	Transient	±30	V
I_{D25}	T_C = 25°C, Chip capability	340	A
$I_{L(RMS)}$	Terminal current limit	100	A
I_{DM}	T_C = 25°C, pulse width limited by T_{JM}	1360	A
I_{AR}	T_C = 25°C	200	A
E_{AR}	T_C = 25°C	64	mJ
E_{AS}	T_C = 25°C	4	J
dv/dt	$I_S \le I_{DM}$, di/dt ≤ 100 A/µs, $V_{DD} \le V_{DSS}$, $T_J \le 150°C$, R_G = 2 Ω	10	V/ns
P_D	T_C = 25°C	700	W
T_J		-55 ... +150	°C
T_{JM}		150	°C
T_{stg}		-55 ... +150	°C
V_{ISOL}	50/60 Hz, RMS t = 1 min $I_{ISOL} \le$ 1 mA t = 1 s	2500 3000	V~ V~
M_d	Mounting torque Terminal connection torque	1.5/13 1.5/13	Nm/lb.in. Nm/lb.in.
Weight		30	g

Symbol	Test Conditions		Characteristic Values (T_J = 25°C, unless otherwise specified) min.	typ.	max.	
V_{DSS}	V_{GS} = 0 V, I_D = 3 mA		70			V
$V_{GH(th)}$	$V_{DS} = V_{GS}$, I_D = 8 mA		2.0		4.0	V
I_{GSS}	V_{GS} = ±20 V_{DC}, V_{DS} = 0				±200	nA
I_{DSS}	$V_{DS} = V_{DSS}$ V_{GS} = 0 V	T_J = 25°C T_J = 125°C			100 2	µA mA
$R_{DS(on)}$	V_{GS} = 10 V, I_D = 100A Pulse test, t ≤ 300 µs, duty cycle d ≤ 2 %				4	mΩ

miniBLOC, SOT-227 B (IXFN)
E153432



G = Gate D = Drain
S = Source

Either Source terminal at miniBLOC can be used as Main or Kelvin Source

Features

- International standard package
- miniBLOC, with Aluminium nitride isolation
- Low $R_{DS\ (on)}$ HDMOS™ process
- Rugged polysilicon gate cell structure
- Unclamped Inductive Switching (UIS) rated
- Low package inductance
- Fast intrinsic Rectifier

Applications

- DC-DC converters
- Battery chargers
- Switched-mode and resonant-mode power supplies
- DC choppers
- Temperature and lighting controls
- Linear current regulators


Advantages

- Easy to mount
- Space savings
- High power density

© 2004 IXYS All rights reserved

Symbol	Test Conditions	Characteristic Values (T_J = 25°C, unless otherwise specified) min.	typ.	max.	
g_{fs}	V_{DS} = 10 V; I_D = 60A, pulse test	80	98		S
C_{iss}	V_{GS} = 0 V, V_{DS} = 25 V, f = 1 MHz		12200		pF
C_{oss}			7100		pF
C_{rss}			3340		pF
$t_{d(on)}$	V_{GS} = 10 V, V_{DS} = 0.5 • V_{DSS}, I_D = 100A R_G = 1 Ω (External)		100		ns
t_r			95		ns
$t_{d(off)}$			200		ns
t_f			33		ns
$Q_{g(on)}$	V_{GS} = 10 V, V_{DS} = 50 V, I_D = 100A		490		nC
Q_{gs}			72		nC
Q_{gd}			266		nC
R_{thJC}				0.18	K/W
R_{thCK}			0.05		K/W

miniBLOC, SOT-227 B



M4 screws (4x) supplied

Dim.	Millimeter Min.	Max.	Inches Min.	Max.
A	31.50	31.88	1.240	1.255
B	7.80	8.20	0.307	0.323
C	4.09	4.29	0.161	0.169
D	4.09	4.29	0.161	0.169
E	4.09	4.29	0.161	0.169
F	14.91	15.11	0.587	0.595
G	30.12	30.30	1.186	1.193
H	38.00	38.23	1.496	1.505
J	11.68	12.22	0.460	0.481
K	8.92	9.60	0.351	0.378
L	0.76	0.84	0.030	0.033
M	12.60	12.85	0.496	0.506
N	25.15	25.42	0.990	1.001
O	1.98	2.13	0.078	0.084
P	4.95	5.97	0.195	0.235
Q	26.54	26.90	1.045	1.059
R	3.94	4.42	0.155	0.174
S	4.72	4.85	0.186	0.191
T	24.59	25.07	0.968	0.987
U	-0.05	0.1	-0.002	0.004

Source-Drain Diode

Symbol	Test Conditions	Characteristic Values (T_J = 25°C, unless otherwise specified) min.	typ.	max.	
I_S	V_{GS} = 0 V			340	A
I_{SM}	Repetitive; pulse width limited by T_{JM}			1360	A
V_{SD}	I_F = 100A, V_{GS} = 0 V, Pulse test, t ≤ 300 µs, duty cycle d ≤ 2 %			1.2	V
t_{rr}	I_F = 50A, -di/dt = 100 A/µs, V_R = 50V T_J = 25°C		100	200	ns
Q_{RM}			1.4		µC
I_{RM}			8		A

IXYS reserves the right to change limits, test conditions, and dimensions.

IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: 4,835,592 4,881,106 5,017,508 5,049,961 5,187,117 5,381,025 6,162,665 6,306,728 B1 6,534,343 6,683,344 4,850,072 4,931,844 5,034,796 5,063,307 5,237,481 5,486,715 6,259,123 B1 6,404,065 B1 6,583,505 6,710,405B2

Fig. 1. Output Characteristics @ 25 Deg. C




Fig. 2. Output Characteristics @ 125 Deg. C




Fig. 3. Temperature Dependence of $R_{DS(ON)}$




Fig. 4. $R_{DS(ON)}$ Normalized to $I_{L(RMS)}$ Value vs. Junction Temperature




Fig. 5. $R_{DS(ON)}$ Normalized to $I_{L(RMS)}$ Value vs. I_D





Fig. 6. Temperature dependence of Breakdown & Threshold Voltage



© 2004 IXYS All rights reserved

Fig. 7. Input Admittance




Fig. 8. Transconductance




Fig. 9. Source Current vs. Source-To-Drain Voltage




Fig. 10. Gate Charge




Fig. 11. Capacitance






Fig. 12. Transient Thermal Resistance



IXYS reserves the right to change limits, test conditions, and dimensions.

Fig. 13. Forward-Bias Safe Operating Area



© 2004 IXYS All rights reserved



Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications.Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.