


# HiPerFAST™ IGBT


IXGH 50N60B  
IXGK 50N60B  
IXGT 50N60B  
IXGJ 50N60B

$V_{CES} = 600 \text{ V}$   
 $I_{C25} = 75 \text{ A}$   
 $V_{CE(sat)} = 2.3 \text{ V}$   
 $t_{fi(typ)} = 120 \text{ ns}$




| Symbol                                                                          | Test Conditions                                                                                  | Maximum Ratings                                 |                   |
|---------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|-------------------------------------------------|-------------------|
| V <sub>CES</sub>                                                                | T <sub>J</sub> = 25°C to 150°C                                                                   | 600                                             | V                 |
| V <sub>CGR</sub>                                                                | T <sub>J</sub> = 25°C to 150°C; R <sub>GE</sub> = 1 MΩ                                           | 600                                             | V                 |
| V <sub>GES</sub>                                                                | Continuous                                                                                       | ±20                                             | V                 |
| V <sub>GEM</sub>                                                                | Transient                                                                                        | ±30                                             | V                 |
| I <sub>C25</sub>                                                                | T <sub>C</sub> = 25°C                                                                            | 75                                              | A                 |
| I <sub>C90</sub>                                                                | T <sub>C</sub> = 90°C                                                                            | 50                                              | A                 |
| I <sub>CM</sub>                                                                 | T <sub>C</sub> = 25°C, 1 ms                                                                      | 200                                             | A                 |
| SSOA<br>(RBSOA)                                                                 | V <sub>GE</sub> = 15 V, T <sub>VJ</sub> = 125°C, R <sub>G</sub> = 10 Ω<br>Clamped inductive load | I <sub>CM</sub> = 100<br>@ 0.8 V <sub>CES</sub> | A                 |
| P <sub>C</sub>                                                                  | T <sub>C</sub> = 25°C                                                                            | 300                                             | W                 |
| T <sub>J</sub>                                                                  |                                                                                                  | -55 ... +150                                    | °C                |
| T <sub>JM</sub>                                                                 |                                                                                                  | 150                                             | °C                |
| T <sub>stg</sub>                                                                |                                                                                                  | -55 ... +150                                    | °C                |
| M <sub>d</sub>                                                                  | Mounting torque                                                                                  | TO-247AD                                        | 1.13/10 Nm/lb.in. |
|                                                                                 |                                                                                                  | TO-264                                          | 0.9/6 Nm/lb.in.   |
| Maximum lead temperature for soldering<br>1.6 mm (0.062 in.) from case for 10 s |                                                                                                  | 300                                             | °C                |
| Weight                                                                          | TO-247                                                                                           | 6                                               | g                 |
|                                                                                 | TO-264                                                                                           | 10                                              | g                 |
|                                                                                 | TO-268                                                                                           | 4                                               | g                 |


TO-247 AD (IXGH)




TO-268 (D3) (IXGT)



TO-268 Leaded (IXGJ)



TO-264 AA (IXGK)



G = Gate  
E = Emitter  
D = Drain  
TAB = Collector

## Features

- International standard packages
- High frequency IGBT
- Latest generation HDMOS™ process
- High current handling capability
- MOS Gate turn-on - drive simplicity

## Applications

- AC motor speed control
- DC servo and robot drives
- DC choppers
- Uninterruptible power supplies (UPS)
- Switch-mode and resonant-mode power supplies


## Advantages

- Easy to mount with 1 screw (insulated mounting screw hole)
- Switching speed for high frequency applications
- High power density

| Symbol        | Test Conditions                                        | Characteristic Values<br>( $T_J = 25^\circ\text{C}$ , unless otherwise specified) |      |                           |
|---------------|--------------------------------------------------------|-----------------------------------------------------------------------------------|------|---------------------------|
|               |                                                        | Min.                                                                              | Typ. | Max.                      |
| $BV_{CES}$    | $I_C = 250 \mu\text{A}, V_{GE} = 0 \text{ V}$          | 600                                                                               |      | V                         |
| $V_{GE(th)}$  | $I_C = 250 \mu\text{A}, V_{CE} = V_{GE}$               | 2.5                                                                               |      | 5.0 V                     |
| $I_{CES}$     | $V_{CE} = 0.8 \cdot V_{CES}$<br>$V_{GE} = 0 \text{ V}$ |                                                                                   |      | 200 $\mu\text{A}$<br>1 mA |
| $I_{GES}$     | $V_{CE} = 0 \text{ V}, V_{GE} = \pm 20 \text{ V}$      |                                                                                   |      | $\pm 100 \text{ nA}$      |
| $V_{CE(sat)}$ | $I_C = I_{C90}, V_{GE} = 15 \text{ V}$                 |                                                                                   |      | 2.3 V                     |


| Symbol                    | Test Conditions                                                                                                                                                                                                                                                                                                                                            | Characteristic Values<br>(T <sub>j</sub> = 25°C, unless otherwise specified) |      |      |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|------|------|
|                           |                                                                                                                                                                                                                                                                                                                                                            | min.                                                                         | typ. | max. |
| <b>g<sub>fs</sub></b>     | I <sub>C</sub> = I <sub>C90</sub> ; V <sub>CE</sub> = 10 V,<br>Pulse test, t ≤ 300 μs, duty cycle ≤ 2 %                                                                                                                                                                                                                                                    | 25                                                                           | 42   | S    |
| <b>C<sub>ies</sub></b>    | V <sub>CE</sub> = 25 V, V <sub>GE</sub> = 0 V, f = 1 MHz                                                                                                                                                                                                                                                                                                   |                                                                              | 4100 | pF   |
| <b>C<sub>oes</sub></b>    |                                                                                                                                                                                                                                                                                                                                                            |                                                                              | 310  | pF   |
| <b>C<sub>res</sub></b>    |                                                                                                                                                                                                                                                                                                                                                            |                                                                              | 95   | pF   |
| <b>Q<sub>G</sub></b>      | I <sub>C</sub> = I <sub>C90</sub> ; V <sub>GE</sub> = 15 V, V <sub>CE</sub> = 0.5 V <sub>CES</sub>                                                                                                                                                                                                                                                         |                                                                              | 160  | nC   |
| <b>Q<sub>GE</sub></b>     |                                                                                                                                                                                                                                                                                                                                                            |                                                                              | 30   | nC   |
| <b>Q<sub>GC</sub></b>     |                                                                                                                                                                                                                                                                                                                                                            |                                                                              | 55   | nC   |
| <b>t<sub>d(on)</sub></b>  | <b>Inductive load, T<sub>j</sub> = 25°C</b><br>I <sub>C</sub> = I <sub>C90</sub> ; V <sub>GE</sub> = 15 V<br>V <sub>CE</sub> = 0.8 • V <sub>CES</sub> ; R <sub>G</sub> = R <sub>off</sub> = 2.7 Ω<br>Remarks: Switching times may increase<br>for V <sub>CE</sub> (Clamp) > 0.8 • V <sub>CES</sub> ; higher T <sub>j</sub> or<br>increased R <sub>G</sub>  |                                                                              | 50   | ns   |
| <b>t<sub>ri</sub></b>     |                                                                                                                                                                                                                                                                                                                                                            |                                                                              | 50   | ns   |
| <b>t<sub>d(off)</sub></b> |                                                                                                                                                                                                                                                                                                                                                            |                                                                              | 150  | ns   |
| <b>t<sub>fi</sub></b>     |                                                                                                                                                                                                                                                                                                                                                            |                                                                              | 120  | ns   |
| <b>E<sub>off</sub></b>    |                                                                                                                                                                                                                                                                                                                                                            |                                                                              | 3.0  | mJ   |
| <b>t<sub>d(on)</sub></b>  | <b>Inductive load, T<sub>j</sub> = 125°C</b><br>I <sub>C</sub> = I <sub>C90</sub> ; V <sub>GE</sub> = 15 V<br>V <sub>CE</sub> = 0.8 • V <sub>CES</sub> ; R <sub>G</sub> = R <sub>off</sub> = 2.7 Ω<br>Remarks: Switching times may increase<br>for V <sub>CE</sub> (Clamp) > 0.8 • V <sub>CES</sub> ; higher T <sub>j</sub> or<br>increased R <sub>G</sub> |                                                                              | 50   | ns   |
| <b>t<sub>ri</sub></b>     |                                                                                                                                                                                                                                                                                                                                                            |                                                                              | 50   | ns   |
| <b>E<sub>on</sub></b>     |                                                                                                                                                                                                                                                                                                                                                            |                                                                              | 3    | mJ   |
| <b>t<sub>d(off)</sub></b> |                                                                                                                                                                                                                                                                                                                                                            |                                                                              | 200  | ns   |
| <b>t<sub>fi</sub></b>     |                                                                                                                                                                                                                                                                                                                                                            |                                                                              | 250  | ns   |
| <b>E<sub>off</sub></b>    |                                                                                                                                                                                                                                                                                                                                                            |                                                                              | 4.2  | mJ   |
| <b>R<sub>thJC</sub></b>   |                                                                                                                                                                                                                                                                                                                                                            |                                                                              | 0.42 | K/W  |
| <b>R<sub>thCK</sub></b>   | TO-247 & TO-268 leaded packages                                                                                                                                                                                                                                                                                                                            | 0.25                                                                         |      | K/W  |
|                           | TO-264 package                                                                                                                                                                                                                                                                                                                                             | 0.15                                                                         |      | K/W  |

### TO-247 AD (IXGH) Outline




| Dim.           | Millimeter |       | Inches |       |
|----------------|------------|-------|--------|-------|
|                | Min.       | Max.  | Min.   | Max.  |
| A              | 4.7        | 5.3   | .185   | .209  |
| A <sub>1</sub> | 2.2        | 2.54  | .087   | .102  |
| A <sub>2</sub> | 2.2        | 2.6   | .059   | .098  |
| b              | 1.0        | 1.4   | .040   | .055  |
| b <sub>1</sub> | 1.65       | 2.13  | .065   | .084  |
| b <sub>2</sub> | 2.87       | 3.12  | .113   | .123  |
| C              | .4         | .8    | .016   | .031  |
| D              | 20.80      | 21.46 | .819   | .845  |
| E              | 15.75      | 16.26 | .610   | .640  |
| e              | 5.20       | 5.72  | 0.205  | 0.225 |
| L              | 19.81      | 20.32 | .780   | .800  |
| L <sub>1</sub> |            | 4.50  |        | .177  |
| ØP             | 3.55       | 3.65  | .140   | .144  |
| Q              | 5.89       | 6.40  | 0.232  | 0.252 |
| R              | 4.32       | 5.49  | .170   | .216  |
| S              | 6.15       | BSC   | .242   | BSC   |

### TO-264 AA (IXGK) Outline



| Dim.           | Millimeter |       | Inches   |       |
|----------------|------------|-------|----------|-------|
|                | Min.       | Max.  | Min.     | Max.  |
| A              | 4.82       | 5.13  | .190     | .202  |
| A <sub>1</sub> | 2.54       | 2.89  | .100     | .114  |
| A <sub>2</sub> | 2.00       | 2.10  | .079     | .083  |
| b              | 1.12       | 1.42  | .044     | .056  |
| b <sub>1</sub> | 2.39       | 2.69  | .094     | .106  |
| b <sub>2</sub> | 2.90       | 3.09  | .114     | .122  |
| c              | 0.53       | 0.83  | .021     | .033  |
| D              | 25.91      | 26.16 | 1.020    | 1.030 |
| E              | 19.81      | 19.96 | .780     | .786  |
| e              | 5.46 BSC   |       | .215 BSC |       |
| J              | 0.00       | 0.25  | .000     | .010  |
| K              | 0.00       | 0.25  | .000     | .010  |
| L              | 20.32      | 20.83 | .800     | .820  |
| L <sub>1</sub> | 2.29       | 2.59  | .090     | .102  |
| P              | 3.17       | 3.66  | .125     | .144  |
| Q              | 6.07       | 6.27  | .239     | .247  |
| Q <sub>1</sub> | 8.38       | 8.69  | .330     | .342  |
| R              | 3.81       | 4.32  | .150     | .170  |
| R <sub>1</sub> | 1.78       | 2.29  | .070     | .090  |
| S              | 6.04       | 6.30  | .238     | .248  |
| T              | 1.57       | 1.83  | .062     | .072  |


### TO-268 (IXGT) Outline



| SYM            | INCHES   |      | MILLIMETERS |       |
|----------------|----------|------|-------------|-------|
|                | MIN      | MAX  | MIN         | MAX   |
| A              | .193     | .201 | 4.90        | 5.10  |
| A <sub>1</sub> | .106     | .114 | 2.70        | 2.90  |
| A <sub>2</sub> | .001     | .010 | 0.02        | 0.25  |
| b              | .045     | .057 | 1.15        | 1.45  |
| b <sub>1</sub> | .075     | .083 | 1.90        | 2.10  |
| C              | .016     | .026 | 0.40        | 0.65  |
| C <sub>2</sub> | .057     | .063 | 1.45        | 1.60  |
| D              | .543     | .551 | 13.80       | 14.00 |
| D <sub>1</sub> | .488     | .500 | 12.40       | 12.70 |
| E              | .624     | .632 | 15.85       | 16.05 |
| E <sub>1</sub> | .524     | .535 | 13.30       | 13.60 |
| e              | .215 BSC |      | 5.45 BSC    |       |
| H              | .736     | .752 | 18.70       | 19.10 |
| L              | .094     | .106 | 2.40        | 2.70  |
| L <sub>1</sub> | .047     | .055 | 1.20        | 1.40  |
| L <sub>2</sub> | .039     | .045 | 1.00        | 1.15  |
| L <sub>3</sub> | .010 BSC |      | 0.25 BSC    |       |
| L <sub>4</sub> | .150     | .161 | 3.80        | 4.10  |

Terminals:  
1 - Gate  
2 - Collector

### TO-268 (IXGJ) Leaded Outline



| SYM            | INCHES   |       | MILLIMETERS |       |
|----------------|----------|-------|-------------|-------|
|                | MIN      | MAX   | MIN         | MAX   |
| A              | .193     | .201  | 4.90        | 5.10  |
| A <sub>1</sub> | .106     | .114  | 2.70        | 2.90  |
| b              | .045     | .057  | 1.15        | 1.45  |
| b <sub>1</sub> | .075     | .083  | 1.90        | 2.10  |
| C              | .016     | .026  | 0.40        | 0.65  |
| C <sub>2</sub> | .057     | .063  | 1.45        | 1.60  |
| D              | .543     | .551  | 13.80       | 14.00 |
| D <sub>1</sub> | .488     | .500  | 12.40       | 12.70 |
| E              | .624     | .632  | 15.85       | 16.05 |
| E <sub>1</sub> | .524     | .535  | 13.30       | 13.60 |
| e              | .215 BSC |       | 5.45 BSC    |       |
| H              | 1.365    | 1.395 | 34.67       | 35.43 |
| L              | .780     | .800  | 19.81       | 20.32 |
| L <sub>1</sub> | .079     | .091  | 2.00        | 2.30  |
| L <sub>2</sub> | .039     | .045  | 1.00        | 1.15  |

NOTE: ALL METAL AREA ARE SOLDER PLATED.

- 1 - GATE
- 2 - DRAIN (COLLECTOR)
- 3 - SOURCE (EMITTER)
- 4 - DRAIN (COLLECTOR)

IXYS reserves the right to change limits, test conditions, and dimensions.

IXYS MOSFETS and IGBTs are covered by one or more of the following U.S. patents:

|           |           |           |           |           |           |             |
|-----------|-----------|-----------|-----------|-----------|-----------|-------------|
| 4,835,592 | 4,881,106 | 5,017,508 | 5,049,961 | 5,187,117 | 5,486,715 | 6,306,728B1 |
| 4,850,072 | 4,931,844 | 5,034,796 | 5,063,307 | 5,237,481 | 5,381,025 |             |







**Figure 1. Saturation Voltage Characteristics**

**Figure 2. Extended Output Characteristics**

**Figure 3. Saturation Voltage Characteristics**

**Figure 4. Temperature Dependence of  $V_{CE(sat)}$** 

**Figure 5. Admittance Curves**

**Figure 6. Capacitance Curves**


Figure 7. Dependence of  $E_{ON}$  and  $E_{OFF}$  on  $I_C$




Figure 8. Dependence of  $E_{ON}$  and  $E_{OFF}$  on  $R_G$




Figure 9. Gate Charge




Figure 10. Turn-off Safe Operating Area




Figure 11. IGBT Transient Thermal Resistance

