
IXYS

GenX3™ 600V IGBT w/ Diode


IXGH36N60B3D1

V_{CES} = 600V
I_{C110} = 36A
$V_{CE(sat)}$ ≤ 1.8V

Medium-Speed Low-Vsat PT IGBT
for 5 - 40kHz Switching



TO-247



G = Gate C = Collector
E = Emitter TAB = Collector

Symbol	Test Conditions	Maximum Ratings	
V_{CES}	T_J = 25°C to 150°C	600	V
V_{CGR}	T_J = 25°C to 150°C, R_{GE} = 1MΩ	600	V
V_{GES}	Continuous	± 20	V
V_{GEM}	Transient	± 30	V
I_{C110}	T_C = 110°C	36	A
I_{F110}	T_C = 110°C	30	A
I_{CM}	T_C = 25°C, 1ms	200	A
SSOA (RBSOA)	V_{GE}= 15V, T_{VJ} = 125°C, R_G = 5Ω Clamped Inductive Load	I_{CM} = 80 $V_{CE} \le V_{CES}$	A
P_C	T_C = 25°C	250	W
T_J		-55 ... +150	°C
T_{JM}		150	°C
T_{stg}		-55 ... +150	°C
T_L	1.6mm (0.062 in.) from Case for 10s	300	°C
T_{SOLD}	Plastic Body for 10s	260	°C
M_d	Mounting Torque	1.13/10	Nm/lb.in.
Weight		6	g

Symbol	Test Conditions (T_J = 25°C Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
BV_{CES}	I_C = 250μA, V_{GE}= 0V	600			V
$V_{GE(th)}$	I_C = 250μA, V_{CE} = V_{GE}	3.0		5.0	V
I_{CES}	V_{CE} = V_{CES}, V_{GE} = 0V			300	μA
	T_J =125°C			1.75	mA
I_{GES}	V_{CE} = 0V, V_{GE} = ± 20V			±100	nA
$V_{CE(sat)}$	I_C = 30A, V_{GE} = 15V, Note 1		1.5	1.8	V

Features

- Optimized for Low Conduction and Switching Losses
- Square RBSOA
- Anti-Parallel Ultra Fast Diode
- International Standard Package

Advantages

- High Power Density
- Low Gate Drive Requirement


Applications

- Power Inverters
- UPS
- Motor Drives
- SMPS
- PFC Circuits
- Battery Chargers
- Welding Machines
- Lamp Ballasts

© 2009 IXYS CORPORATION, All Rights Reserved

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
g_{fs}	I_C = 30A, V_{CE} = 10V, Note 1	28	42		S
C_{ies}	V_{CE} = 25V, V_{GE} = 0V, f = 1MHz		2280		pF
C_{oes}			120		pF
C_{res}			32		pF
Q_g	I_C = 30A, V_{GE} = 15V, V_{CE} = 0.5 • V_{CES}		80		nC
Q_{ge}			12		nC
Q_{gc}			36		nC
$t_{d(on)}$	**Inductive Load, T_J = 25°C** I_C = 30A, V_{GE} = 15V V_{CE} = 400V, R_G = 5Ω		19		ns
t_{ri}			24		ns
E_{on}			0.54		mJ
$t_{d(off)}$			125	200	ns
t_{fi}			100	160	ns
E_{off}			0.8	1.5	mJ
$t_{d(on)}$	**Inductive Load, T_J = 125°C** I_C = 30A, V_{GE} = 15V V_{CE} = 400V, R_G = 5Ω		19		ns
t_{ri}			26		ns
E_{on}			0.9		mJ
$t_{d(off)}$			180		ns
t_{fi}			170		ns
E_{off}			1.5		mJ
R_{thJC}				0.50	°C/W
R_{thCS}			0.21		°C/W

TO-247 Outline (IXGH)



Dim.	Millimeter Min.	Max.	Inches Min.	Max.
A	4.7	5.3	.185	.209
A_1	2.2	2.54	.087	.102
A_2	2.2	2.6	.059	.098
b	1.0	1.4	.040	.055
b_1	1.65	2.13	.065	.084
b_2	2.87	3.12	.113	.123
C	.4	.8	.016	.031
D	20.80	21.46	.819	.845
E	15.75	16.26	.610	.640
e	5.20	5.72	0.205	0.225
L	19.81	20.32	.780	.800
L1		4.50		.177
∅P	3.55	3.65	.140	.144
Q	5.89	6.40	0.232	0.252
R	4.32	5.49	.170	.216
S	6.15 BSC		242 BSC	

Reverse Diode (FRED)

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
V_F	I_F = 30A, V_{GE} = 0V, Note 1			2.8	V
	T_J = 150°C			1.7	V
I_{RM}	I_F = 30A, V_{GE} = 0V, -di_F/dt = 100A/μs, T_J= 100°C		6		A
	V_R = 100V				
t_{rr}	I_F = 1A, -di_F/dt =100A/μs, V_R = 30V		25		ns
	T_J= 100°C		100		ns
R_{thJC}				0.9	°C/W

Note 1. Pulse test, t ≤ 300μs; duty cycle, d ≤ 2%.

IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

IXYS MOSFETs and IGBTs are covered by one or moreof the following U.S. patents: 4,835,592 4,850,072 4,881,106 4,931,844 5,017,508 5,034,796 5,049,961 5,063,307 5,187,117 5,237,481 5,381,025 5,486,715 6,162,665 6,259,123 B1 6,306,728 B1 6,404,065 B1 6,534,343 6,583,505 6,683,344 6,710,405 B2 6,710,463 6,727,585 6,759,692 6,771,478 B2 7,005,734 B2 7,063,975 B2 7,071,537 7,157,338B2

Fig. 1. Output Characteristics @ 25ºC




Fig. 2. Extended Output Characteristics @ 25ºC




Fig. 3. Output Characteristics @ 125ºC




Fig. 4. Dependence of $V_{CE(sat)}$ on Junction Temperature




Fig. 5. Collector-to-Emitter Voltage vs. Gate-to-Emitter Voltage





Fig. 6. Input Admittance



© 2009 IXYS CORPORATION, All Rights Reserved

Fig. 7. Transconductance




Fig. 8. Gate Charge




Fig. 9. Capacitance




Fig. 10. Reverse-Bias Safe Operating Area





Fig. 11. Maximum Transient Thermal Impedance



IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

Fig. 12. Inductive Switching Energy Loss vs. Gate Resistance




Fig. 13. Inductive Switching Energy Loss vs. Collector Current




Fig. 14. Inductive Switching Energy Loss vs. Junction Temperature




Fig. 15. Inductive Turn-off Switching Times vs. Gate Resistance




Fig. 16. Inductive Turn-off Switching Times vs. Collector Current





Fig. 17. Inductive Turn-off Switching Times vs. Junction Temperature



© 2009 IXYS CORPORATION, All Rights Reserved

Fig. 18. Inductive Turn-on Switching Times vs. Gate Resistance




Fig. 19. Inductive Turn-on Switching Times vs. Collector Current





Fig. 20. Inductive Turn-on Switching Times vs. Junction Temperature



IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.




Fig. 21. Forward current I_F versus V_F




Fig. 22. Reverse recovery charge Q_r versus -di_F/dt




Fig. 23. Peak reverse current I_{RM} versus -di_F/dt




Fig. 24. Dynamic parameters Q_r, I_{RM} versus T_{VJ}




Fig. 25. Recovery time t_{rr} versus -di_F/dt




Fig. 26. Peak forward voltage V_{FR} and t_{fr} versus di_F/dt




Fig. 27. Transient thermal resistance junction to case

Constants for Z_{thJC} calculation:

i	R_{thi} (K/W)	t_i (s)
1	0.502	0.0052
2	0.193	0.0003
3	0.205	0.0162

© 2009 IXYS CORPORATION, All Rights Reserved



Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.