

CoolMOS™ [1] Power MOSFET ISOPLUS™ Package

N-Channel Enhancement Mode
Low R_{DSon}, high V_{DSS} MOSFET
Electrically Isolated Back Surface

I_{D25} = 25 A
V_{DSS} = 800 V
$R_{DS(on)\ max}$ = 150 mΩ



ISOPLUS220



E72873

MOSFET			
Symbol	**Conditions**	**Maximum Ratings**	
V_{DSS}	T_{VJ} = 25°C	800	V
V_{GS}		± 20	V
I_{D25}	T_C = 25°C	25	A
I_{D90}	T_C = 90°C	18	A
E_{AS}	$T_{J\ start}$ = 25°C; single pulse; I_D = 3.4 A	670	mJ
E_{AR}	$T_{J\ start}$ = 25°C; repetitive; I_D = 17 A	0.5	mJ
dV/dt	$V_{DS} < V_{DSS}$; I_F = 35 A; T_{VJ} = 150°C; d_{IR}/dt = 100 A/µs	6	V/ns

Symbol	Conditions	Characteristic Values (T_{VJ} = 25°C, unless otherwise specified)			
		min.	typ.	max.	
R_{DSon}	V_{GS} = 10 V; $I_D = I_{D90}$		135	150	mΩ
$V_{GS(th)}$	$V_{DS} = V_{GS}$; I_D = 2 mA	2		4	V
I_{DSS}	$V_{DS} = V_{DSS}$; V_{GS} = 0 V; T_{VJ} = 25°C			50	µA
	$V_{DS} = V_{DSS}$; V_{GS} = 0 V; T_{VJ} = 125°C		250		µA
I_{GSS}	V_{GS} = ± 20 V; V_{DS} = 0 V			±200	nA
C_{iss}	V_{GS} = 0 V; V_{DS} = 25 V; f = 1 MHz		4600		pF
C_{oss}			2500		pF
C_{rss}			120		pF
Q_g	V_{GS} = 0 to 10 V; V_{DS} = 640 V; $I_D = I_{D90}$		180		nC
Q_{gs}			20		nC
Q_{gd}			80		nC
$t_{d(on)}$	V_{GS} = 10 V; V_{DS} = 640 V; T_{VJ} = 125°C; I_D = 35 A; R_G = 2.2 Ω		25		ns
t_r			25		ns
$t_{d(off)}$			75		ns
t_f			10		ns
R_{thJC}				0.5	K/W

Features

- Silicon chip on Direct-Copper-Bond substrate
  - high power dissipation
  - isolated mounting surface
  - 2500 V electrical isolation
- 3rd generation CoolMOS™ [1] power MOSFET
  - high blocking capability
  - lowest resistance
  - avalanche rated for unclamped inductive switching (UIS)
- Low thermal resistance due to reduced chip thickness
- Low drain to tab capacitance (<30 pF)

Applications

- Switched mode power supplies (SMPS)
- Uninterruptible power supplies (UPS)
- Power factor correction (PFC)
- Welding
- Inductive heating

Advantages

- Easy assembly: no screws or isolation foils required
- Space savings
- High power density

[1] CoolMOS™ is a trademark of Infineon Technologies AG.

IXYS reserves the right to change limits, test conditions and dimensions.

© 2008 IXYS All rights reserved

Source-Drain Diode


Symbol	Conditions	Characteristic Values (T_{VJ} = 25°C, unless otherwise specified) min.	typ.	max.	
I_S	V_{GS} = 0 V			34	A
V_{SD}	I_F = 35 A; V_{GS} = 0 V		1.0	1.2	V
t_{rr}	I_F = 35 A; -di_F/dt = 200 A/µs; V_R = 400 V		550		ns
Q_{RM}			30		µC
I_{RM}			100		A


Component

Symbol	Conditions	Maximum Ratings	
T_{VJ}	operating	-55...+150	°C
T_{stg}		-55...+150	°C
V_{ISOL}	RMS, lead-to-tab, 50/60 Hz, f = 1 minute	2500	V~
F_C	mounting force	11-65/2.4-11	N/lb.

Symbol	Conditions	Characteristic Values min.	typ.	max.	
R_{thCH}	with heatsink compound		0.15		K/W
Weight			2.7		g

ISOPLUS220™ Outline





SYM	INCHES MIN	INCHES MAX	MILLIMETERS MIN	MILLIMETERS MAX
A	.157	.197	4.00	5.00
A2	.098	.118	2.50	3.00
b	.035	.051	0.90	1.30
b2	.049	.065	1.25	1.65
b4	.093	.100	2.35	2.55
c	.028	.039	0.70	1.00
D	.591	.630	15.00	16.00
D1	.472	.512	12.00	13.00
E	.394	.433	10.00	11.00
E1	.295	.335	7.50	8.50
e	.100 BASIC		2.55 BASIC	
L	.512	.571	13.00	14.50
L1	.118	.138	3.00	3.50
T°			42.5°	47.5°

NOTE:
1. Bottom heatsink is electrically isolated from Pin 1, 2, or 3.
2. This drawing will meet dimensional requirement of JEDEC SS Product Outline TO-273 except D and D1 dimension.

IXYS reserves the right to change limits, test conditions and dimensions.

© 2008 IXYS All rights reserved




Fig. 1 Power Dissipation




Fig. 2 Typ. Output Characteris-




Fig. 3 Typ. Output Characteris-




Fig. 4 Typ. Drain-Source on Resistance




Fig. 5 Drain-Source On-State Resistance




Fig. 6 Typ. Transfer Characteris-




Fig. 7 Forward Characteristics of Body Diode




Fig. 8 Typ. Gate Charge




Fig. 9 Capacitance

IXYS reserves the right to change limits, test conditions and dimensions.

© 2008 IXYS All rights reserved




Fig. 10 Typ. Avalanche Energy




Fig. 11 Drain-Source Breakdown Voltage




Fig. 12 Maximum Transient Thermal Resistance

IXYS reserves the right to change limits, test conditions and dimensions.

© 2008 IXYS All rights reserved



Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications.Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.