

LINEAR SYSTEMS

Linear Integrated Systems

J/SST111 SERIES

SINGLE N-CHANNEL JFET

FEATURES

DIRECT REPLACEMENT FOR SILICONIX J/SST111 SERIES

LOW GATE LEAKAGE CURRENT	5pA
--------------------------	-----

FAST SWITCHING	4ns
----------------	-----

ABSOLUTE MAXIMUM RATINGS¹

@ 25 °C (unless otherwise stated)

Maximum Temperatures

Storage Temperature	-55 to 150°C
---------------------	--------------

Junction Operating Temperature	-55 to 135°C
--------------------------------	--------------

Maximum Power Dissipation

Continuous Power Dissipation (J)	360mW
----------------------------------	-------

Continuous Power Dissipation (SST)	350mW
------------------------------------	-------

Maximum Currents


Gate Current	50mA
--------------	------

Maximum Voltages


Gate to Drain	-35V
---------------	------

Gate to Source	-35V
----------------	------

J SERIES
TO-92
BOTTOM VIEW



SST SERIES
SOT-23
TOP VIEW



STATIC ELECTRICAL CHARACTERISTICS @25 °C (unless otherwise stated)

SYM.	CHARACTERISTIC	TYP	J/SST111		J/SST112		J/SST113		UNIT	CONDITIONS
			MIN	MAX	MIN	MAX	MIN	MAX		
BV _{GSS}	Gate to Source Breakdown Voltage		-35		-35		-35		V	I _G = -1μA, V _{DS} = 0V
V _{GS(off)}	Gate to Source Cutoff Voltage		-3	-10	-1	-5		-3		V _{DS} = 5V, I _D = 1μA
V _{GS(F)}	Gate to Source Forward Voltage	0.7								I _G = 1mA, V _{DS} = 0V
I _{DSS}	Drain to Source Saturation Current ²		20		5		2		mA	V _{DS} = 15V, V _{GS} = 0V
I _{GSS}	Gate Leakage Current	-0.005		-1		-1		-1	nA	V _{GS} = -15V, V _{DS} = 0V
I _G	Gate Operating Current	-5							pA	V _{DG} = 15V, I _D = 10mA
I _{D(off)}	Drain Cutoff Current	0.005		1		1		1	nA	V _{DS} = 5V, V _{GS} = -10V
r _{DS(on)}	Drain to Source On Resistance			30		50		100	Ω	I _G = 1mA, V _{DS} = 0V

Linear Integrated Systems

• 4042 Clipper Court • Fremont, CA 94538 • Tel: 510 490-9160 • Fax: 510 353-0261

DYNAMIC ELECTRICAL CHARACTERISTICS @25 °C (unless otherwise stated)


SYM.	CHARACTERISTIC	TYP	J/SST111		J/SST112		J/SST113		UNIT	CONDITIONS
			MIN	MAX	MIN	MAX	MIN	MAX		
g_{fs}	Forward Transconductance	6							mS	$V_{DS} = 20V, I_D = 1mA$ $f = 1kHz$
g_{os}	Output Conductance	25							μS	
$r_{ds(on)}$	Drain to Source On Resistance			30		50		100	Ω	$V_{GS} = 0V, I_D = 0mA$ $f = 1kHz$
C_{iss}	Input Capacitance	7		12		12		12	pF	$V_{DS} = 0V, V_{GS} = -10V$ $f = 1MHz$
C_{rss}	Reverse Transfer Capacitance	3		5		5		5		
e_n	Equivalent Noise Voltage	3							nV/ $\sqrt{Hz}$	$V_{DG} = 10V, I_D = 1mA$ $f = 1 kHz$

SWITCHING CHARACTERISTICS

SYM.	CHARACTERISTIC	TYP	UNIT	CONDITIONS
$t_{d(on)}$	Turn On Time	2	ns	$V_{DD} = 10V$ $V_{GS(H)} = 0V$
t_r		2		
$t_{d(off)}$	Turn Off Time	6		
t_f		15		

SWITCHING CIRCUIT CHARACTERISTICS

SYM.	J/SST111	J/SST112	J/SST113
$V_{GS(L)}$	-12V	-7V	-5V
R_L	800 Ω	1600 Ω	3200 Ω
$I_{D(on)}$	12mA	6mA	3mA



NOTES

1. Absolute maximum ratings are limiting values above which serviceability may be impaired.
2. Pulse test: PW $\leq$ 300 μs , Duty Cycle $\leq$ 3%

Information furnished by Linear Integrated Systems is believed to be accurate and reliable. However, no responsibility is assumed for its use; nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Linear Integrated Systems.