

J84-4300 Wipe-key Keyboard



Actual product may vary from the image shown

Slim, low profile, compact keyboard with integrated pointing device: The J84-4300 offers an IP55 rating for protection against dust and spraying liquids. It's ideal for applications requiring frequent disinfection for elimination of germs. Uses include diagnostics equipment, medical carts, rack mount servers, laboratories, and kiosks.

Facts & Features

- Membrane technology provides dust, dirt, and spraying water protection.
- Designed for continuous use – more than 10 Million key operations
- High reliability and uniquely precise tactile keying
- Full 87 US key layout
- Ultra slim - overall height only 19 mm
- Uses Standard Operating System Drivers
- Ideal for use with space limitations

Technical Data:

Housing and Key Color:
Black

Weight
Without Packaging 600 g / 1.3 lbs
With Packaging 730 g / (Approx)1.6 lbs

Cable Length:
Approx. 1.62 m

Keyswitch Lifetime:
Key life: 10 Million operations

Storage Temperature:
-20°C to +60°C / -4° F to 140° F

Technical Data Cont:

Layout:
87 US key layout

Current Consumption:
40mA (MAX)

Interface:
USB

Agency Approvals:
CE
FCC
Class B
BSMI
RoHS

System Requirements:
USB connection

Delivery Volume:
J84-4300, manual

Compatible Operating Systems:
Win 98SE, ME, 2000, XP, XP x 64, Vista, Windows

Packaging Unit:
20 keyboards per master carton
12 master cartons per pallet (240 pcs.)

Dimensions:
Keyboard: 370 x 139 x 19 mm
14.5" x 5.5" x .75"
Packaging: 396 x 210 x 43 mm
15.6" x 8.3" x 1.7"

Warranty:
2 years

**Operating Temperature:**

0° C to +60° C / 31° F to 140° F

Humidity:

0~95% RH

Order Description

Service Design	Order Number	Interface	Color
Medium Use	J84-4300LUAUS-2	USB	Black

Other country versions available upon request. (Special conditions apply)

Cherry Americas, LLC
11200 88th Avenue
Pleasant Prairie, WI 53158
USA
Phone: 262.942.6508
Internet: www.cherryamericas.com

E-Mail: cep_sales@zf.com

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2016 Cherry Americas, LLC, Rev Date: January 6, 2016