

JRL36000S25

POWERPACT AUTOMATIC MOULDED CASE SWITCH 600V 250 A J-Frame

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 4,009.50 USD



Main

Product or component type	Automatic switch
Range of product	PowerPact J
Trip unit technology	Magnetic
Circuit breaker type	J-frame

Complementary

Line Rated Current	250 A
[Ue] rated operational voltage	600 V AC
Mounting mode	Unit mount
Poles description	3P
Short-circuit withstand	200 kA 240 V UL 489 200 kA 480 V UL 489 100 kA 600 V UL 489
Breaking capacity code	R
Electrical connection	Lugs line Lugs load
AWG gauge	AWG 3/0...350 kcmil aluminium/copper)
Terminal identifier	AL250JD
Magnetic tripping current	3125 A
Maximum Height	7.52 in (191.01 mm)
Maximum Width	4.12 in (104.65 mm)
Maximum Depth	5 in (127.00 mm)
Tightening torque	230.12 lbf.in (26 N.m) 0.15...0.29 in ² (95...185 mm ²) AWG 3/0...350 kcmil)

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Product certifications	UL Listed IEC CSA
------------------------	-------------------------

Ordering and shipping details

Category	01108 - H/J HIGH INTERRUPT UNIT MT CB/SW
Discount Schedule	DE2
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes