
Clock Oscillators Surface Mount Type
KC5032A-C1 Series (High Frequency)

KYOCERA

CMOS/ 1.8V, 2.5V, 3.3V/ 5.0×3.2mm



RoHS Compliant

Features

- Wide operating voltage range 1.6 to 3.3V
- ±25×10^{-6} available
- Highly reliable with seam welding
- Miniature ceramic package
- CMOS output

Table 1

Freq. Tol. Code	Freq. Tol. × 10^{-6}	Operating Temperature Range (°C)	Note
0	± 50	−10 to +70	Standard specifications
S	± 30		With only certain frequencies
U	± 25		
F	±100	−40 to +85	
S	± 50		

How to Order

KC5032A 100.000 C 1 0 E 00
① ② ③ ④ ⑤ ⑥ ⑦

① Type (5.0×3.2mm SMD)
② Output Frequency
③ Output Type (CMOS)
④ Supply Voltage (1.8V, 2.5V, 3.3V Compatible)
⑤ Frequency Tolerance (See Table 1)
⑥ Symmetry/ INH Function
(45/ 55%, Stand-by)
⑦ Customer Special Model Suffix
(STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)


Specifications

Item	Symbol	Conditions		Min.	Max.	Units
Output Frequency Range	fo			50	135	MHz
Frequency Tolerance	f_tol	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: −40 to +85°C	−100	+100	×10^{-6}
			Op. Temp.: −10 to +70°C/ −40 to +85°C	−50	+50	
			Op. Temp.: −10 to +70°C	−30	+30	
			Op. Temp.: −10 to +70°C	−25	+25	
Storage Temperature Range	T_stg			−55	+125	°C
Operating Temperature Range	T_use			−40	+85	°C
Max. Supply Voltage	—			−0.3	+4	V
Supply Voltage	Vcc			+1.6	+3.63	V
Current Consumption	Icc	1.6≤Vcc≤2V		—	18	mA
		2<Vcc≤2.8V		—	20	
		2.8<Vcc≤3.63V		—	30	
Stand-by Current	I_std			—	10	µA
Symmetry	SYM	@50% Vcc		45	55	%
Rise/ Fall Time (10% Vcc to 90% Vcc Maximum Loaded)	tr/ tf	1.6≤Vcc≤2V		—	4.5	ns
		2<Vcc≤2.8V		—	3	
		2.8<Vcc≤3.63V		—	2.5	
Low Level Output Voltage	VOL			—	10% Vcc	V
High Level Output Voltage	VOH			90% Vcc	—	V
Output Load	L_CMOS	1.6≤Vcc≤3.63V		—	15	pF
Input Voltage Range	VIN			0	Vcc	V
Low Level Input Voltage	VIL			—	30% Vcc	V
High Level Input Voltage	VIH			70% Vcc	—	V
Disable Time	t_dis			—	150	ns
Enable Time	t_ena			—	5	ms
Start-up Time	t_str	@Minimum operating voltage to be 0 sec.		—	10	ms
1 Sigma Jitter	JSigma	Measured with Wavecrest DTS-2079 *VISI 6.3.1*	50≤fo≤100MHz	—	5	ps
			100<fo≤133MHz	—	4	
Peak to Peak Jitter	JPK-PK		50≤fo≤100MHz	—	40	ps
			100<fo≤133MHz	—	30	

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Dimensions

(Unit: mm)




Plating: Ni+Au
Tolerance: ±0.2

Pad Connections	
#1	INH
#2	Case GND
#3	Output
#4	Vcc

INH Function	
Pad1	Pad3 (Output)
Open	Active
"H" Level	Active
"L" Level	High Z (No-Oscillation)

Recommended Land Pattern

(Unit: mm)



Note: A capacitor of value 0.01µF between Vcc and GND is recommended.