Large Current Positive Voltage Regulator


The KIC3201S/T series are highly precise, low power consumption, positive voltage regulators manufactured using CMOS and laser trimming technologies. The series provides large currents with a significantly small dropout voltage. The KIC3201S/T consists of a driver transistor, a precision reference voltage and an error amplifier. Output voltage is selectable in 0.05V steps between a voltage of 1.2V and 6.0V.

Features

- Maximum Output Current : 400mA
- Dropout Voltage : 150mV @100mA, 300mV @200mA for V_{OUT}=3.0V
- Maximum Operating Voltage : 10V
- Output Voltage Range :
  1.2V ~ 6.0V (selectable in 0.05V steps)
- Highly Accurate : ±2%
- Low Power Consumption : Typ. 8.0uA
- Operational Temperature Range : -40℃ ~ 85℃
- Low ESR Capacitor : Ceramic compatible or Tantalum

Applications

- Battery Powered Equipment
- Reference Voltage Sources
- Digital Cameras, Camcoders
- Palmtop Computers
- Portable Audio Video Equipment




DIM	MILLIMETERS
A	4.70 MAX
B	2.50±0.20
C	1.70 MAX
D	0.45+0.15/-0.10
E	4.25 MAX
F	1.50±0.10
G	0.40 TYP
H	1.75 MAX
J	0.75 MIN
K	0.5+0.10/-0.05

① GND
② V_{IN}
③ V_{OUT}

• Heat Sink is common to ② (V_{IN})

SOT-89




DIM	MILLIMETERS
A	2.9±0.2
B	1.6+0.2/-0.1
C	0.70±0.05
D	0.4±0.1
E	2.8+0.2/-0.3
F	1.9±0.2
G	0.95
H	0.16±0.05
I	0.00-0.10
J	0.25+0.25/-0.15
K	0.60
L	0.55

1. V_{OUT}
2. GND
3. V_{IN}

TSM

Pin Configuration

KIC3201S-XX




SOT-89
(TOP VIEW)

No.	Symbol	Description
1	GND	Ground
2	V_{IN}	Power input
3	V_{OUT}	Output

• Heat Sink is common to ② (V_{IN})

KIC3201T-XX



TSM
(TOP VIEW)

No.	Symbol	Description
1	V_{OUT}	Output
2	GND	Ground
3	V_{IN}	Power input

Line up

$V_{OUT(V)}$	SOT-89		TSM	
	ITEM	Marking	ITEM	Marking
1.2	KIC3201S-12	A2	KIC3201T-12	B2C
1.3	KIC3201S-13	A3	KIC3201T-13	B3C
1.4	KIC3201S-14	A4	KIC3201T-14	B4C
1.5	KIC3201S-15	A5	KIC3201T-15	B5C
1.6	KIC3201S-16	A6	KIC3201T-16	B6C
1.7	KIC3201S-17	A7	KIC3201T-17	B7C
1.8	KIC3201S-18	A8	KIC3201T-18	B8C
1.9	KIC3201S-19	A9	KIC3201T-19	B9C
2.0	KIC3201S-20	B0	KIC3201T-20	C0C
2.1	KIC3201S-21	B1	KIC3201T-21	C1C
2.2	KIC3201S-22	B2	KIC3201T-22	C2C
2.3	KIC3201S-23	B3	KIC3201T-23	C3C
2.4	KIC3201S-24	B4	KIC3201T-24	C4C
2.5	KIC3201S-25	B5	KIC3201T-25	C5C
2.6	KIC3201S-26	B6	KIC3201T-26	C6C
2.7	KIC3201S-27	B7	KIC3201T-27	C7C
2.8	KIC3201S-28	B8	KIC3201T-28	C8C
2.9	KIC3201S-29	B9	KIC3201T-29	C9C
3.0	KIC3201S-30	C0	KIC3201T-30	D0C
3.1	KIC3201S-31	C1	KIC3201T-31	D1C
3.2	KIC3201S-32	C2	KIC3201T-32	D2C
3.3	KIC3201S-33	C3	KIC3201T-33	D3C
3.4	KIC3201S-34	C4	KIC3201T-34	D4C
3.5	KIC3201S-35	C5	KIC3201T-35	D5C

* Other Voltages available, Selectable in 0.05V steps Contact KEC for details

Line up

$V_{OUT(V)}$	SOT-89		TSM	
	ITEM	Marking	ITEM	Marking
3.6	KIC3201S-36	C6	KIC3201T-36	D6C
3.7	KIC3201S-37	C7	KIC3201T-37	D7C
3.8	KIC3201S-38	C8	KIC3201T-38	D8C
3.9	KIC3201S-39	C9	KIC3201T-39	D9C
4.0	KIC3201S-40	D0	KIC3201T-40	E0C
4.1	KIC3201S-41	D1	KIC3201T-41	E1C
4.2	KIC3201S-42	D2	KIC3201T-42	E2C
4.3	KIC3201S-43	D3	KIC3201T-43	E3C
4.4	KIC3201S-44	D4	KIC3201T-44	E4C
4.5	KIC3201S-45	D5	KIC3201T-45	E5C
4.6	KIC3201S-46	D6	KIC3201T-46	E6C
4.7	KIC3201S-47	D7	KIC3201T-47	E7C
4.8	KIC3201S-48	D8	KIC3201T-48	E8C
4.9	KIC3201S-49	D9	KIC3201T-49	E9C
5.0	KIC3201S-50	E0	KIC3201T-50	F0C
5.1	KIC3201S-51	E1	KIC3201T-51	F1C
5.2	KIC3201S-52	E2	KIC3201T-52	F2C
5.3	KIC3201S-53	E3	KIC3201T-53	F3C
5.4	KIC3201S-54	E4	KIC3201T-54	F4C
5.5	KIC3201S-55	E5	KIC3201T-55	F5C
5.6	KIC3201S-56	E6	KIC3201T56	F6C
5.7	KIC3201S-57	E7	KIC3201T-57	F7C
5.8	KIC3201S-58	E8	KIC3201T-58	F8C
5.9	KIC3201S-59	E9	KIC3201T-59	F9C
6.0	KIC3201S-60	F0	KIC3201T-60	G0C

* Other Voltages available, Selectable in 0.05V steps Contact KEC for details

Absolute Maximum Ratings

Characteristics	Symbol	Rating	Units
Input Voltage	V_{IN}	12	V
Output Current	I_{OUT}	500	mA
Output Voltage	V_{OUT}	V_{SS}-0.3 ~ V_{IN}+0.3	V
Power Dissipation(Note)	P_D (SOT-89)	900	mW
	P_D (TSM)		
Operating Temperature	T_{OPR}	-40 ~ 85	℃
Storage Temperature	T_{STG}	-65 ~ 150	℃

Note) Package mounted on a ceramic board (600㎟×0.8㎜)

Electrical Characteristics

(Unless otherwise stated, Ta=25℃, V_{IN} = V_{OUT} + 1.0V)

Parameter	Symbol	Conditions		Min	Typ	Max	Units
Output Voltage	V_{OUT}	I_{OUT}=40mA V_{IN}=V_{OUT} + 1V		V_{OUT} ×0.98	V_{OUT}	V_{OUT} ×1.02	V
Maximum Output Current	$I_{OUT(MAX)}$	V_{OUT}=1.2V~1.5V	V_{OUT} ×0.9 V_{IN}=2.5V	400	-	-	mA
		V_{OUT}=1.6V~2.4V	V_{OUT} ×0.9 V_{IN}=V_{OUT}+1V				
		V_{OUT}=2.5V~2.9V	V_{OUT} ×0.93 V_{IN}=V_{OUT}+1V				
		V_{OUT}=3.0V~6.0V	V_{OUT} ×0.96 V_{IN}=V_{OUT}+1V				
Load Regulation	Reg Load	1mA ≤ I_{OUT} ≤200mA V_{IN}=V_{OUT}+1V		-	40	100	mV
Dropout Voltage	V_{D1}	V_{OUT} =1.8~2.4V, I_{OUT} = 100mA		-	200	300	mV
		V_{OUT} =2.5~2.9V, I_{OUT} = 100mA		-	170	250	
		V_{OUT} =3.0~4.9V, I_{OUT} = 100mA		-	150	220	
		V_{OUT} =5.0~6.0V, I_{OUT} = 100mA		-	100	180	
	V_{D2}	V_{OUT} =1.8~2.4V, I_{OUT} = 200mA		-	400	600	mV
		V_{OUT} =2.5~2.9V, I_{OUT} = 200mA		-	320	500	
		V_{OUT} =3.0~4.9V, I_{OUT} = 200mA		-	300	420	
		V_{OUT} =5.0~6.0V, I_{OUT} = 200mA		-	200	320	
Supply Current	I_{DD}	V_{IN}=$V_{OUT(T)}$+1V		-	8	16	μA
Line Regulations	Reg Line	V_{OUT} +1.0V ≤V_{IN} ≤8V I_{OUT}=40mA		-	0.2	0.3	%/V
Input Voltage	V_{IN}			-	-	10	V
Output Voltage Temperature Characteristics	ΔV_{OUT} / $\Delta T_{OPR} . V_{OUT}$	I_{OUT}=40mA -40℃ ≤T_{OPR} ≤85℃		-	100	-	ppm/℃
Short Circuit Current	I_{SC}	V_{IN} =V_{OUT}+1V, V_{OUT} = 0V		-	50	-	mA

● KIC3201S/T-18

Fig. 1 I_{OUT} - V_{OUT}




Fig. 2 V_{IN} - V_{OUT}




Fig. 3 V_{IN} - I_{SS}




Fig. 4 Ta - V_{OUT}




Fig. 5 Input Transient Response




Fig. 6 Load Transient Response
(I_{OUT} = 40mA)




Fig. 7 Load Transient Response
(I_{OUT} = 200mA)




Fig. 8 PSRR

