



Technical Data Sheet		Rosenberger																									
RET Control Cable (Halogen Free)		L99-C197-XXX																									
Main Features AISG 2.0 Compliant RET Control Cable Feeds Data & DC Power to RET Components RoHS Compliant Halogen Free																											
Electrical Data <table><tr><td>Protocol</td><td>3GPP/AISG 2.0/AISG 1.1</td></tr><tr><td>Voltage, Rated</td><td>300 V</td></tr></table>		Protocol	3GPP/AISG 2.0/AISG 1.1	Voltage, Rated	300 V																						
Protocol	3GPP/AISG 2.0/AISG 1.1																										
Voltage, Rated	300 V																										
Environmental Data <table><tr><td>Operating Temperature Range</td><td>-40°C to +70°C -40°F to +158°F</td></tr><tr><td>Relative Humidity</td><td>5% - 95%</td></tr><tr><td>Weather Protection</td><td>IP67</td></tr><tr><td>Flammability</td><td>UL94-V0</td></tr></table>		Operating Temperature Range	-40°C to +70°C -40°F to +158°F	Relative Humidity	5% - 95%	Weather Protection	IP67	Flammability	UL94-V0																		
Operating Temperature Range	-40°C to +70°C -40°F to +158°F																										
Relative Humidity	5% - 95%																										
Weather Protection	IP67																										
Flammability	UL94-V0																										
Mechanical Data <table><tr><td>AISG Connector A</td><td>8-Pin DIN Female</td></tr><tr><td>AISG Connector B</td><td>8-Pin DIN Male</td></tr><tr><td>Braid Coverage</td><td>Coverage Rate ≥85 %</td></tr><tr><td>Data Conductor Type</td><td>0.32 mm² (24 AWG) twisted pair</td></tr><tr><td>Data Conductors, Quantity</td><td>2</td></tr><tr><td>Power Conductor Type</td><td>0.75 mm² (20 AWG) stranded</td></tr><tr><td>Power Conductors, Quantity</td><td>4</td></tr><tr><td>Total Conductors, Quantity</td><td>6</td></tr><tr><td>Shield Material</td><td>Aluminum</td></tr><tr><td>Jacket Material</td><td>LSZH(Anti-UV)</td></tr><tr><td>Color</td><td>Black</td></tr><tr><td>Diameter Over Jacket</td><td>8.00 mm</td></tr></table>		AISG Connector A	8-Pin DIN Female	AISG Connector B	8-Pin DIN Male	Braid Coverage	Coverage Rate ≥85 %	Data Conductor Type	0.32 mm² (24 AWG) twisted pair	Data Conductors, Quantity	2	Power Conductor Type	0.75 mm² (20 AWG) stranded	Power Conductors, Quantity	4	Total Conductors, Quantity	6	Shield Material	Aluminum	Jacket Material	LSZH(Anti-UV)	Color	Black	Diameter Over Jacket	8.00 mm		
AISG Connector A	8-Pin DIN Female																										
AISG Connector B	8-Pin DIN Male																										
Braid Coverage	Coverage Rate ≥85 %																										
Data Conductor Type	0.32 mm² (24 AWG) twisted pair																										
Data Conductors, Quantity	2																										
Power Conductor Type	0.75 mm² (20 AWG) stranded																										
Power Conductors, Quantity	4																										
Total Conductors, Quantity	6																										
Shield Material	Aluminum																										
Jacket Material	LSZH(Anti-UV)																										
Color	Black																										
Diameter Over Jacket	8.00 mm																										
Rosenberger Hochfrequenztechnik GmbH & Co. KG Tel.: +49 8684 18-0 Fax: +49 8684 18-499 www.rosenberger.de Email : info@rosenberger.de		Rosenberger Technology (Kunshan) Co., Ltd. Tel.: +86 512 86896789 Fax: +86 512 86890666 www.rosenbergerap.com Email: info@rosenbergerap.com																									
		Page 1 / 2																									

Technical Data Sheet					Rosenberger																										
RET Control Cable (Halogen Free)					L99-C197-XXX																										
Part Numbers of Cables <table><tr><td>Part Number</td><td>Length</td></tr><tr><td>L99-C197-500</td><td>0.5 m</td></tr><tr><td>L99-C197-1000</td><td>1 m</td></tr><tr><td>L99-C197-2000</td><td>2 m</td></tr><tr><td>L99-C197-3000</td><td>3 m</td></tr><tr><td>L99-C197-5000</td><td>5 m</td></tr><tr><td>L99-C197-10000</td><td>10 m</td></tr><tr><td>L99-C197-20000</td><td>20 m</td></tr><tr><td>L99-C197-30000</td><td>30 m</td></tr><tr><td>L99-C197-40000</td><td>40 m</td></tr><tr><td>L99-C197-50000</td><td>50 m</td></tr></table>										Part Number	Length	L99-C197-500	0.5 m	L99-C197-1000	1 m	L99-C197-2000	2 m	L99-C197-3000	3 m	L99-C197-5000	5 m	L99-C197-10000	10 m	L99-C197-20000	20 m	L99-C197-30000	30 m	L99-C197-40000	40 m	L99-C197-50000	50 m
Part Number	Length																														
L99-C197-500	0.5 m																														
L99-C197-1000	1 m																														
L99-C197-2000	2 m																														
L99-C197-3000	3 m																														
L99-C197-5000	5 m																														
L99-C197-10000	10 m																														
L99-C197-20000	20 m																														
L99-C197-30000	30 m																														
L99-C197-40000	40 m																														
L99-C197-50000	50 m																														
Pin Assignments: 1. +12 V DC nominal 2. not connected 3. RS485 B 4. RS485 GND 5. RS485 A 6. +24 V DC nominal 7. DC Return 8. not connected   FemaleMale																															
While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.																															
Draft	Date	Checker	Approved	Date	Rev.	Engineering Change Number	Name	Date																							
Hai Chen	18/06/15		J.Gramsamer	02.12.15	100	15-0005	Hai Chen	20/11/15																							
Rosenberger Hochfrequenztechnik GmbH & Co. KG Tel.: +49 8684 18-0 Fax: +49 8684 18-499 www.rosenberger.de					Rosenberger Technology (Kunshan) Co., Ltd. Tel.: +86 512 86896789 Fax: +86 512 86890666 www.rosenbergerap.com			Page 2 / 2																							