



Features

- ✧ For IF SAW filter
- ✧ High attenuation
- ✧ Single-ended operation
- ✧ Dual In-line Package
- ✧ No matching required for operation at 50Ω
- ✧ RoHS compliant (2002/95/EC), Pb-free

Specifications

Parameter	Unit	Minimum	Typical	Maximum
Center Frequency	MHz	119.875	120	120.125
Insertion Loss	dB	-	25.4	27
1.5 dB Bandwidth	MHz	15	15.07	-
3 dB Bandwidth	MHz	-	15.21	-
20 dB Bandwidth	MHz	-	15.73	15.8
25 dB Bandwidth	MHz	-	15.81	16.05
30 dB Bandwidth	MHz	-	15.87	16.5
40 dB Bandwidth	MHz	-	15.98	17.5
Passband Variation	dB	-	0.9	1.5
Absolute Delay	usec	-	2.87	2.95
Ultimate Rejection	dB	40	44	-
Material Temperature coefficient	KHz/°C	-11.28		
Substrate Material	-	YZ LN		
Ambient Temperature	°C	25		
Operating Temperature Range	°C	-40	-	+85
Storage Temperature Range	°C	-45	-	+105
DC Voltage	V	0		
Input Power	dBm	-	-	10
ESD Class	-	1A		
Package Size	DIP3512 (35.0x12.8x4.7mm3)			

Notes:

- All specifications are based on the test circuit shown;
- In production, all specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature;
- Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances;
- This is the optimum impedance in order to achieve the performance show.



SIPAT Co., Ltd.
(CETC No.26 Research Institute)
#14 Nanping Huayuan Road,
Chongqing, China, 400060

Part Number	LBN12012		
Rev. Date	2010-07-30		
Ver.	2.0	Page	1/3


Matching Configuration



Source / Load Impedance=50 ohm

Notes - Component values may change depending
on board layout.

Package Dimension



Pad Configuration:

Input 1
Output 5
Ground All Others

Marking Configuration:

- 1) SIPAT: Manufacturer Name
- 2) LBN12012: Part Number
- 3) XXYY: Date(Year/month)
- 4) ZZ: Identified Code

Package: DIP3512

Unit: mm



SIPAT Co., Ltd.
(CETC No.26 Research Institute)
#14 Nanping Huayuan Road,
Chongqing, China, 400060

Part Number

LBN12012

Rev. Date

2010-07-30

Ver.


2.0

Page 2/3



Typical Performance


Frequency Response



Horizontal: 10MHz/Div

Vertical: 10dB/Div


Passband Response



Horizontal: 5MHz/Div

Vertical: 0.5dB/Div


Group Delay Variation($f_0 \pm 7\text{MHz}$)



Horizontal: 5MHz/Div

Vertical: 100ns/Div


Phase Linearity($f_0 \pm 7\text{MHz}$)




Horizontal: 5MHz/Div

Vertical: 5deg/Div

Smith Chart S11



Smith Chart S22



SIPAT Co., Ltd.
(CETC No.26 Research Institute)
#14 Nanping Huayuan Road,
Chongqing, China, 400060

Part Number

LBN12012

Rev. Date

2010-07-30

Ver.

2.0

Page 3/3