
LCS Series
Subminiature Sealed Snap-acting Switches



Features/Benefits

- *Compact design*
- *Long life and high electrical capacity*
- *Quick connect, solder terminals, PC terminals, wire leads*
- *Wide variety of actuator styles*
- *RoHS compatible, RoHS compliant*
- *IP67*

Typical Applications

- *Motorized equipment*
- *Sump pump*
- *Thermostatic controls*
- *Computers*
- *Air conditioners*

Models Available

Specifications

CONTACT RATING: 6 AMP, 250 V AC and
5 AMP, 125/250 V AC
0.1 AMP, 125/250 V AC®
ELECTRICAL LIFE: 10,000 cycles
INSULATION RESISTANCE: 100 M ohm min.
DIELECTRIC STRENGTH: 1,000 VAC
OPERATING TEMPERATURE:
0°C to +120°C (without wire)
0°C to +85°C (with UL1007 wire)
0°C to +105°C (with UL1015 wire)
0°C to +105°C (with UL1430 wire)
0°C to +80°C (with UL1061 wire)
0°C to +120°C (with UL1330 wire)
OPERATING FORCE: (see ACTUATOR'S option sections).
MOUNTING: 2-56 screws, torque 2.3 in/lbs max.

NOTE: Specifications and materials listed above are for switches with standard options.
For information on specific and custom switches, consult Customer Service center.

Materials

SWITCH HOUSING: Thermoplastic polyester or high temperature thermoplastic (PTS) (UL 94V-0).
ACTUATOR BUTTON: Thermoplastic polyester.
SPRING: Copper alloy.
PIVOT: Copper alloy.
MOVABLE CONTACTS: Silver nickel
STATIONARY CONTACTS: Silver nickel on copper alloy.
TERMINALS: Copper alloy.
ACTUATOR LEVEL: Stainless steel.

Build-A-Switch

To order, simply select desired option from each category and place in the appropriate box. Available options are shown and described on pages J-27 thru J-29. For additional options not shown in catalog, consult Customer Service Center.

L	C	S												

Series
LCS

Contact Rating
05 5 AMP, 125/250 V AC
6 AMP, 250 V AC
01 0.1 AMP, 125/250 V AC

Operating Force
1 150 grams
2 203 grams

Actuator
P00 Pin plunger
T00 11.9 mm short lever
T05 17.4 mm short lever
T07 19.4 mm short lever
T13 25.5 mm lever
T19 33.3 mm lever
T28 40.7 mm lever
T43 55.9 mm lever
S26 18.6 mm simulated lever
A05 17.2 mm lever roller

Terminations
S Solder
Q 0.110 Quick Connect
P PC Thru Hole
W Wire leads potted
Z Wire leads non-potted

Wire Side (when required)
A Wire out the bottom
B Wire out the right side
C Wire out the left side
D None

Wire Type AWG
20 20 AWG
22 22 AWG
24 24 AWG
26 26 AWG
28 28 AWG
30 30 AWG


Wire UL #
(when required)
A UL1007
B UL1015
C UL1430
D UL1061
E UL1330

Circuitry
C SPDT
W SPST N.C.
Y SPST N.O.

Dimensions are shown: mm
Specifications and dimensions subject to change

SERIES

LCS



ELECTRICAL RATING

RoHS COMPLIANT *	RoHS COMPATIBLE *	OPTION CODE	ELECTRICAL RATING
YES	YES	05	5 AMP, 125/250 V AC 6 AMP, 250 V AC
YES	YES	01	0.1 AMP, 125/250 V AC

OPERATING FORCE

OPTION CODE	OPERATING FORCES (grams)
1	150 g. max.
2	203 g. max.


Third Angle Projection

Dimensions are shown: mm
Specifications and dimensions subject to change


LCS Series
Subminiature Sealed Snap-acting Switches

ACTUATOR


P00




T19




T07




A05




T00




T28




T13




S26





T05





T43












ACTUATOR OPTION CODE	A mm LENGTH OF LEVER	B mm OVER TRAVEL (MIN)	C mm PRE TRAVEL (MAX)	D mm OPERATING POSITION	E mm FREE POSITION (MAX)	DIFF. MOTION (MAX) mm 150 grams	DIFF. MOTION (MAX) mm 203 grams	OPERATING FORCE (MIN) Grams 150 grams	OPERATING FORCE (MIN) Grams 203 grams	RELEASE FORCE (MIN) Grams 150 grams	RELEASE FORCE (MIN) Grams 203 grams
P00	button	0.6	1.2	8.4 ±.3	9.9	0.2	0.2	150	203	30	50
T00	11.9	0.6	3.2	8.8 ±.9	11.1	0.5	0.5	66	98	10	21
T05	17.40	0.9	4.3	8.8 ±1.1	12	0.6	0.6	73	82	14	16
T07	19.40	1	4.8	8.8 ±1.2	12.4	0.7	0.7	55	66	11	13
T13	25.5	1.6	6.3	8.8 ±1.6	13.5	0.9	0.9	29	54	6	11
T19	33.3	1.95	8.0	8.8 ±2.0	15.0	1.75	1.75	32	40	2	5
T28	40.7	2.1	10.1	8.8 ±2.6	16.3	2.3	1.4	33	39	1	8
T43	55.9	2.9	13.8	8.8 ±3.5	19.1	3.6	2.0	23	33	1	7
S26	18.6	1	4.6	10.7 ±1.2	14.1	0.95	0.65	42	68	7	14
A05	17.20	0.9	4.3	14.5 ±1.1	17.7	0.6	0.6	60	72	12	15

Third Angle Projection


Dimensions are shown: mm
Specifications and dimensions subject to change

TERMINATIONS


S SOLDER




Q QUICK CONNECT 2.8mm / 0.110"




P PC THRU HOLE




Z or W "A" WIRE ORIENTATION




Z or W "B" WIRE ORIENTATION
"Y" OR "W" CIRCUITRY




Z or W "C" WIRE ORIENTATION
"Y" OR "W" CIRCUITRY



Z or W "B" WIRE ORIENTATION
"C" CIRCUITRY



Z or W "C" WIRE ORIENTATION
"C" CIRCUITRY



CIRCUITRY

C SPDT (Single Pole, Double Throw)

W SPST N.C. (Single Pole, Single Throw, Normally Closed)

Y SPST N.O. (Single Pole, Single Throw, Normally Open)

Third Angle Projection

Dimensions are shown: mm
Specifications and dimensions subject to change