September 2005

National Semiconductor

LM3519
High Frequency Boost White LED Driver with High-Speed PWM Brightness Control

General Description

The LM3519 drives up to 4 white LEDs with constant current to provide LCD backlighting in handheld devices. The LED current is internally set to 20mA. The series connection allows the LED current to be identical for uniform brightness and minimizes the number of traces to the LEDs. Brightness control is achieved by applying a PWM signal on enable with frequencies up to 30kHz.

The LM3519 features a proprietary PFM regulation architecture with switching frequencies between 2MHz to 8MHz, minimizing inductor size.

Over-voltage protection circuitry and high frequency operation permit the use of low-cost small output capacitors. During shutdown, the output is disconnected from the input in order to avoid leakage current path through the LEDs to ground.

The LM3519 is available in a tiny 6-pin SOT23 package.

Features

- Drives 2 to 4 LEDs at 20mA
- Up to 30kHz PWM Dimming Control Capability
- >80% Peak Efficiency
- Up to 8MHz Switching Frequency
- Small External Components: 1µH - 3.3µH(typ.2.2µH) Inductor and 1µF Output Capacitor
- True Shutdown Isolation
- Over-Voltage Protection
- Wide Input Voltage Range: 2.7V to 5.5V
- Small Footprint SOT23-6 Package

Applications

- LCD, White LED Backlighting on Mobile Phones
- Digital Still Cameras and PDAs
- General Purpose LED Lighting in Handheld Devices

Typical Application





FIGURE 1. Typical Application Circuit

Connection Diagram

6-Lead SOT23 Package



Top View

Pin Descriptions

Pin #	Name	Description
1	En	Device Enable Connection
2	Gnd	Ground Connection
3	V_{OUT}	Output Voltage Connection
4	LED_rtn	White LED Current Sensing Input Connection
5	S_W	Drain Connection of the Internal Power Field Effect Transistor (FET) Switch
6	V_{IN}	Input or Supply Voltage Connection

Ordering Information

Current Option	Order Number	Package Marking	Supplied As
20 mA	LM3519MK-20	D52B	1000 Units, Tape-and-Reel
	LM3519MKX-20	D52B	3000 Units, Tape-and-Reel

Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/ Distributors for availability and specifications.

V_{IN} , En, & LED_rtn Pin	−0.3V to +6.5V
V_{OUT} , Sw Pin	−0.3V to +21V
Maximum Junction Temperature (T_{J-MAX})	+150˚C
Storage Temperature Range	−65˚C to +150˚C

ESD Rating (Note 2)

Human Body Model:	2kV
Machine Model:	200V

Operating Ratings

Junction Temperature (T_J) Range	−40˚C to +125˚C
Ambient Temperature (T_A) Range	−40˚C to +85˚C
Input Voltage Range	2.7V to 5.5V

Thermal Properties (Note 4)

Junction-to-Ambient Thermal Resistance (θ_{JA})	220˚C/W

Electrical Characteristics (Note 5) Limits in standard typeface are for T_J = +25˚C. Limits in **bold typeface** apply over the full operating junction temperature range (−40˚C ≤ T_J ≤ +125˚C). V_{IN} = 3.6V, unless otherwise stated.

Symbol	Parameter	Conditions	Min	Typ	Max	Units
I_Q	Supply Current	Shutdown: V_{EN} = 0V		0.1		µA
		Not Switching: V_{EN} = 1.8V		360	**500**	
		Switching: V_{EN} = 1.8V, LED_rtn current = 30mA		550	**900**	
$I_{LED(TOL)}$	LED Current Tolerance/Variation	V_{IN} = 3.6V, 2.2µH, 4LEDs	**−10**	5.5	**10**	%
OVP	Over-Voltage Protection Threshold	OVP ON OVP OFF	**18** **17.8**	18.9 18.6	**20** **19.8**	V
I_{LIM}	Switch Current Limit	L = 2.2µH		750		mA
$R_{DS(ON)}$	Power NMOS Switch ON Resistance			455		mΩ
$I_{LEAKAGE}$	Switch Leakage	V_{SW} = 3.6V, V_{EN} = 0V		0.1	**2**	µA
$R_{LED_rtn(ON)}$	LED_rtn NMOS Switch ON Resistance			8.0		Ω
F_S	Switching Frequency	I_{LED} = 20 mA , L = 1µH 4LEDs		5.4		MHz
I_{EN}	Enable Pin Bias Current (Note 3)	V_{EN} = 0V V_{EN} = 1.8V		0.1 1.1	 **2**	µA
En	Enable Threshold	Device On Device Off	**0.9**		 **0.3**	V

Note 1: Absolute maximum ratings indicate limits beyond which damage to the device may occur. Operating Ratings are conditions under which operation of the device is guaranteed. Operating Ratings do not imply guaranteed limits. For guaranteed performance limits and associated test conditions, see the Electrical Characteristics table.

Note 2: The human body model is a 100pF capacitor discharged through a 1.5kΩ resistor into each pin. The machine model is a 200pF capacitor discharged directly into each pin.

Note 3: Current flows into the pin.

Note 4: The maximum allowable power dissipation is a function of the maximum junction temperature, T_J(MAX), the junction-to-ambient thermal resistance, θ_{JA}, and the ambient temperature, T_A. See Thermal Properties for the thermal resistance. The maximum allowable power dissipation at any ambient temperature is calculated using: $P_D(MAX) = (T_J(MAX) - T_A)/\theta_{JA}$. Exceeding the maximum allowable power dissipation will cause excessive die temperature.

Note 5: Min and max limits are guaranteed by design, test, or statistical analysis. Typical numbers are not guaranteed, but do represent the most likely norm.

Block Diagram




FIGURE 2. Block Diagram

Circuit Description

The LM3519 is a step-up converter for white LED applications that uses a unique and proprietary pulse frequency modulation (PFM) architecture to optimize high efficiency at high frequency operation. Unlike most PFM architecture implementations, the LM3519's unique architectural implementation results in non-pulse skipping variable frequency operation. The regulator is forced to operate at the edge of Continous Conduction Mode (CCM). The error amplifier will set the end of the on-time (I_{PEAK} of inductor) based on the load (LEDs) current. During this operation, the inductor current ramps up and reaches a peak current at end of the on-time. At this point, the internal power switch is turned off until the inductor current reaches zero, and the cycle repeats again. The switching frequency is set based on the charge (on-time) and discharge(off-time) of the inductor current. The frequency can range between 2MHz to 8MHz over the operating input range.


The LM3519 operation can be best understood through an examination of the block diagram in *Figure 2*. When LED current is out of regulation, the LED_rtn voltage falls below or rises above the internal reference voltage (VREF). The error amplifier will output a signal to increase or decrease the proper on-time duration of N1 power FET. This correction allows the inductor's stored energy to increase or decrease to a sufficient level that when transferred to the load will bring the LED_rtn current back into regulation.

During steady-state operation for a typical switching cycle, the oscillator sets the driver logic and turns on N1 power device. N1 conducts current through the inductor and reverse biases the external diode. The LED current is supplied by the output capacitor when N1 is conducting. Once N1 on-time period is concluded, the internal power device is turned off and the external diode is forward baised. The inductor current then flows through the diode to the LED load to replenish the output capacitor and keep the LED current regulated at the trimmed target.

Typical Performance Characteristics


(See Typical Application Circuit : V_{IN} = 3.6V, C_{IN} = 4.7µF and C_{OUT} = 1µF, L = 2.2µH and 4 LEDs. T_A = +25˚C, unless otherwise stated.)

Efficiency vs V_{IN}




20160251

Efficiency vs V_{IN}




20160231

Efficiency vs V_{IN}




20160232

Efficiency vs V_{IN}




20160233

$I_{OUT_ACCURACY}$ vs V_{IN}



20160249


$I_{OUT_ACCURACY}$ vs V_{IN}



20160250


Typical Performance Characteristics (See Typical Application Circuit : V_{IN} = 3.6V, C_{IN} = 4.7µF and C_{OUT} = 1µF, L = 2.2µH and 4 LEDs. T_A = +25˚C, unless otherwise stated.) (Continued)

I_{OUT} vs V_{IN}




20160234

I_{OUT} vs V_{IN}




20160235

I_{OUT} vs V_{IN}




20160253

I_{OUT} vs PWM Duty Cycle (V_{IN} = 3.6V, L = 2.2µH)




20160260

I_{OUT} vs PWM Duty Cycle (V_{IN}= 3.6V, L = 2.2µH)



20160261


I_{OUT} vs PWM Duty Cycle (V_{IN} = 3.6V, L = 1µH)



20160259


Typical Performance Characteristics (See Typical Application Circuit : V_{IN} = 3.6V, C_{IN} = 4.7µF and C_{OUT} = 1µF, L = 2.2µH and 4 LEDs. T_A = +25˚C, unless otherwise stated.) (Continued)

I_{OUT} vs PWM Duty Cycle (V_{IN} = 3.6V, L = 1µH)




20160244

Switching Frequency vs V_{IN}




20160207

Switching Frequency vs V_{IN}




20160209

Switching Frequency vs V_{IN}




20160245

Switching Frequency vs V_{IN}



20160246


Peak Inductor Current vs V_{IN}



20160204


Typical Performance Characteristics (See Typical Application Circuit : V_{IN} = 3.6V, C_{IN} = 4.7µF and C_{OUT} = 1µF, L = 2.2µH and 4 LEDs. T_A = +25˚C, unless otherwise stated.) (Continued)

Peak Inductor Current vs V_{IN}




20160206

Peak Inductor Current vs V_{IN}




20160208

Current Limit vs V_{IN} (4LEDs, 1µH)




20160247

Current Limit vs V_{IN}




20160248

Iq (non switching) vs Temperature



20160255


Iq (switching) vs Temperature



20160256


Typical Performance Characteristics (See Typical Application Circuit : V_{IN} = 3.6V, C_{IN} = 4.7µF and C_{OUT} = 1µF, L = 2.2µH and 4 LEDs. T_A = +25˚C, unless otherwise stated.) (Continued)

LED Switch R_{DS_ON} vs Temperature




20160257

Power Switch R_{DS_ON} vs Temperature




20160258

Start-up, (V_{IN} = 3.6V, 4LEDs, 2.2µH)




20160210

Start-up (V_{IN} = 3.6V, 4LEDs, 3.3µH)




20160219

Start-up (V_{IN} = 3.6V, 2LEDs, 3.3µH)



20160220


Start-up, (V_{IN} = 3.6V, 2LEDs, 2.2µH)



20160211


Typical Performance Characteristics (See Typical Application Circuit : V_{IN} = 3.6V, C_{IN} = 4.7µF and C_{OUT} = 1µF, L = 2.2µH and 4 LEDs. T_A = +25˚C, unless otherwise stated.) (Continued)

Typical Switching Waveform (V_{IN} = 3.6V, 4LEDs, 3.3µH)




20160218

Typical Switching Waveform (V_{IN} = 3.6V, 4LEDs, 2.2µH)




20160212

Typical Switching Waveform (V_{IN} = 3.6V, 3LEDs, 2.2µH)




20160214

Typical Switching Waveform (V_{IN} = 3.6V, 2LEDs, 2.2µH)




20160215

Typical Switching Waveform (V_{IN} = 3.6V, 3LEDs, 1µH)



20160228

Typical Switching Waveform (V_{IN} = 3.6V, 4LEDs, 1µH)



20160229

Application Information

CAPACITOR SELECTION

To minimize output and input voltage ripple, low equivalent series resistance (ESR) ceramic capacitors are the best choice to use for the input and output filters. For most display applications, a 4.7µF capacitor is recommended for C_{IN} and 1µF for C_{OUT} .

Larger output capacitors can be used to reduce ripple voltage. To guarantee good performance, a minimum of 0.47µF C_{OUT} is required to trade off for large ripple voltage. Care must be taken to account for the true capacitance of a multilayer ceramic capacitor. Smaller case size capacitors typically have less capacitance for a given bias voltage as compared to a larger case size capacitor with the same bias voltage. Please confirm with capacitor manufacturer data before selecting the capacitor.

Some recommended capacitor manufacturers include but are not limited to:

Manufacturer	Description	Case Size
AVX	06033D105MAT-25V	0603
	06036D475MAT-6.3V	0603
TDK	C2012X5R1A475M-10V	0805
Taiyo Yuden	TMK212BJ105KG-J	0805
	EM212BJ475MG-16V	0805
muRata	GRM40-034B105K25	0805
	GRM39X5R475K6.3	0603

INDUCTOR SELECTION

In order to maintain sufficient inductance, the saturation current rating of the inductor used with the LM3519 should be higher than the peak inductor current in the target application. Inductors with low DCR values have less power loss and higher efficiency. Larger inductor values such as 2.2µH and 3.3µH can be used to optimize efficiency, frequency and peak current. If 1µH is used, the peak inductor current, frequency will be higher and the efficiency will be lower. Note that the switching frequency ranges will be higher at lower inductance. Typical frequency range is between 4 to 8MHz for 1µH, 2 to 5MHz for 2.2µH and 2 to 4MHz for 3.3µH over the input range. Below is a sample list of low profile inductors.

Some recommended inductor manufacturers include but are not limited to:

Manufacturer	L	Case Size	I_{SAT}
CoilCraft: DO3314-102	1µH	3.3x3.3x1.4mm	2.1A
DO3314-222	2.2µH		1.6A
DO3314-332	3.3µH		1.4A
Coilcraft: LPO3310-102ML	1µH	3.3x3.3x1.0 mm	1.6A
LPO3310-222ML	2.2µH		1.1A
LPO3310-332ML	3.3µH		0.95A
Cooper: SD31121R0	1µH	3.1x3.1x1.4 mm	2.07A
SD3114-2R2	2.2µH		1.48A
SD3114-3R3	3.3uH		1.15A
Taiyo Yuden: NR3015T1R0N	1µH	3.0x3.0x1.5 mm	2.1A
NR3015T2R2M	2.2µH		1.48A
NR3015T3R3M	3.3µH		1.21A

DIODE SELECTION

Diodes with low forward voltage ratings (V_F) and low junction capacitance magnitudes (C_J or C_T or C_D) are conducive to high efficiency. The chosen diode must have a reverse breakdown voltage rating (V_R and/or V_{RRM}) that is larger than the output voltage. The following criteria should be followed when choosing a diode:

1. V_R (Diode Blocking Voltage Range) and V_{RRM} (Diode Peak Repetitive Reverse Voltage Rating) > V_{OUT} (Output Voltage)
2. I_F or I_O (Diode Average Forward Current Rating) ≥ I_{LOAD} (Load Current)
3. I_{FRM} (Diode Peak Repetitive Forward Current Rating) ≥ I_{Lpeak} (Peak Inductor Current)

Some recommended diode manufacturers include but are not limited to:

Maufacturer	Description
Vishay	SS12(1A/20V)
	SS14(1A/40V)
	SS16(1A/60V)
Central Semiconductor	CMSH1- 40M(1A/40V)
ONSemi	MBRS1540T3(1.5A/40V)

PWM DIMMING

The LED current is set internally by the LM3519 to 20mA (typical); dimming control may be realized by applying a pulse width modulated(PWM) signal to the En pin. For example, a 50% duty cycle waveform will produce an average current of 10mA. A control signal frequency between 17kHz and 30kHz is suitable for dimming.


Although the LM3519 is capable of operation outside this frequency range, it is not recommended to operate below 17kHz for the following reasons: 1) frequency below 100Hz is likely to cause visible flicker in the light emitted by the LED string. 2) frequency below 17kHz may induce audible noise due to combinations of some capacitance/PCB. A PWM frequency above 30kHz is possible but the current linearity vs duty cycle will be affected.

If it is not possible to operate the dimming control above 17kHz, audible noise emission may be minimized by using capacitors with low susceptibility to piezoelectric induced stresses, such as poly film designs. Minimum audible noise is most likely to occur when the PWM frequency is less than 2kHz. It is recommended that any application using a PWM control signal below 17kHz be thoroughly evaluated for undesirable audible or visible noise.

DRIVING 2 LEDs

The LM3519 is optimized to drive up to 4LEDs. When driving 2LEDs, a minimum inductance of 2.2µH is required to maintain good loop regulation and current accuracy. If a smaller inductor is used, the LED current will have more variation with input voltage than a typical application. The following curve illustrates the behavior.

Application Information (Continued)




20160239

LAYOUT GUIDELINES

The input capacitor, C_{IN}, must be placed close to the LM3519. Placing C_{IN} close to the device will reduce the metal trace resistance effect on input voltage ripple. Metal trace connections for the C_{OUT} capacitor can increase the effective series resistance, which affects output voltage ripple and efficiency. Trace connections to the inductor should be short and wide to reduce power dissipation, increase overall efficiency and reduce EMI radiation. The diode, like the inductor, should have trace connections that are short and wide to reduce power dissipation and increase overall efficiency. For more details regarding layout guidelines for switching regulators, refer to Applications Note AN-1149.

Physical Dimensions inches (millimeters) unless otherwise noted



6-Lead SOT23-6 Package
NS Package Number MK06A

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.

For the most current product information visit us at www.national.com.

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

BANNED SUBSTANCE COMPLIANCE

National Semiconductor manufactures products and uses packing materials that meet the provisions of the Customer Products Stewardship Specification (CSP-9-111C2) and the Banned Substances and Materials of Interest Specification (CSP-9-111S2) and contain no ''Banned Substances'' as defined in CSP-9-111S2.

Leadfree products are RoHS compliant.

National Semiconductor
Americas Customer
Support Center
Email: new.feedback@nsc.com
Tel: 1-800-272-9959

www.national.com

National Semiconductor
Europe Customer Support Center
Fax: +49 (0) 180-530 85 86
Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 69 9508 6208
English Tel: +44 (0) 870 24 0 2171
Français Tel: +33 (0) 1 41 91 8790

National Semiconductor
Asia Pacific Customer
Support Center
Email: ap.support@nsc.com

National Semiconductor
Japan Customer Support Center
Fax: 81-3-5639-7507
Email: jpn.feedback@nsc.com
Tel: 81-3-5639-7560