LINEAR SYSTEMS

LS3250A
MONOLITHIC DUAL
NPN TRANSISTOR

micross

Linear Systems Log Conformance Monolithic Dual NPN

The LS3250A is a monolithic pair of NPN transistors mounted in a single P-DIP package. The monolithic dual chip design reduces parasitics and is ideal for use in tracking applications.

The 8 Pin P-DIP provides ease of manufacturing, and the symmetrical pinout prevents improper orientation.

(See Packaging Information).

LS3250A Features:

- Tight matching
- Low Output Capacitance

FEATURES	
TIGHT MATCHING	≤ 2mV
THERMAL TRACKING	≤ 3µV/ °C
ABSOLUTE MAXIMUM RATINGS [1] @ 25°C (unless otherwise noted)	
Maximum Temperatures	
Storage Temperature	-65°C to +150°C
Operating Junction Temperature	-55°C to +150°C
Maximum Power Dissipation	
Continuous Power Dissipation	TBD
Maximum Currents	
Collector Current	50mA
Maximum Voltages	
Collector to Collector Voltage	80V

MATCHING CHARACTERISTICS @ 25°C (unless otherwise stated)

SYMBOL	CHARACTERISTIC	MIN	TYP	MAX	UNITS	CONDITIONS
$\lvert V_{BE1} - V_{BE2} \rvert$	Base Emitter Voltage Differential	--	--	2	mV	I_C = 10mA, V_{CE} = 5V
$\Delta\lvert(V_{BE1} - V_{BE2})\rvert / \Delta T$	Base Emitter Voltage Differential Change with Temperature	--	-	3	µV/°C	I_C = 10µA, V_{CE} = 5V T_A = -40°C to +85°C
$\lvert I_{B1} - I_{B2} \rvert$	Base Current Differential	--	--	10	nA	I_C = 10µA, V_{CE} = 5V
$\lvert\Delta (I_{B1} - I_{B2})\rvert / \Delta T$	Base Current Differential Change with Temperature	--	--	0.5	nA/°C	I_C = 10µA, V_{CE} = 5V T_A = -40°C to +85°C
h_{FE1}/h_{FE2}	DC Current Gain Differential	--	--	10	%	I_C = 10µA, V_{CE} = 5V

Click To Buy

ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTICS	MIN.	TYP.	MAX.	UNITS	CONDITIONS
BV_{CBO}	Collector to Base Voltage	45	--	--	V	I_C = 10mA, I_E = 0
BV_{CEO}	Collector to Emitter Voltage	45	--	--	V	I_C = 10µA, I_B = 0
BV_{EBO} [2]	Emitter-Base Breakdown Voltage	6.2	--	--	V	I_E = 10µA, I_C = 0
BV_{CCO}	Collector to Collector Voltage	80	--	--	V	I_C = 10µA, I_E = 0
h_{FE}	DC Current Gain	150	--	--		I_C = 10µA, V_{CE} = 5V
		120	--	--		I_C = 100µA, V_{CE} = 5V
		100	--	--		I_C = 1mA, V_{CE} = 5V
V_{CE}(SAT)	Collector Saturation Voltage	--	--	0.25	V	I_C = 100mA, I_B = 10mA
I_{EBO}	Emitter Cutoff Current	--	--	0.2	nA	I_C = 0A, V_{CB} = 3V
I_{CBO}	Collector Cutoff Current	--	--	0.2	nA	I_E = 0A, V_{CB} = 20V
C_{OBO}	Output Capacitance	--	--	2	pF	I_E = 0A, V_{CB} = 10V
I_{C1C2}	Collector to Collector Leakage Current	--	--	1	nA	V_{CC} = ±80V
f_T	Current Gain Bandwidth Product	--	--	600	MHz	I_C = 1mA, V_{CE} = 5V
NF	Narrow Band Noise Figure	--	--	3	dB	I_C = 100µA, V_{CE} = 5V, BW=200Hz, R_B= 10Ω, f = 1KHz

Notes:
1. Absolute Maximum ratings are limiting values above which serviceability may be impaired
2. The reverse base-to-emitter voltage must never exceed 6.2 volts; the reverse base-to-emitter current must never exceed 10µA.

micross


Available Packages:

LS3250A in P-DIP
LS3250A available as bare die

Please contact Micross for full package and die dimensions:

Email: chipcomponents@micross.com
Web: www.micross.com/distribution.aspx

P-DIP (Top View)



Information furnished by Linear Integrated Systems and Micross Components is believed to be accurate and reliable. However, no responsibility is assumed for its use; nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Linear Integrated Systems.